

Product Information 02.20.97

14-07-2025

Syngear XLD 75W-90

Description

Syngear XLD 75W-90 is a modern fuel-saving synthetic 75W-90 transmission oil. Using low-viscosity, synthetic base oils and highly advanced technology results in a high-quality long-life transmission oil with the following unique properties:

- Ensures effective gear-changing in cold or warm conditions
- Ensures fuel saving: up to 2% cost saving
- Suitable for very long replacement intervals, if supported by the OEM
- A very strong lubricant film, even under the toughest conditions
- Excellent protection against wear and micro-pitting
- Effective friction reduction, resulting in lower operating temperatures and enhanced efficiency
- Does not affect seals: prevents leakages

Application

Syngear XLD 75W-90 is a synthetic fuel-saving transmission oil for heavy transport applications (including trucks and buses). This product is suitable for extended maintenance intervals, if supported by the manufacturer. Syngear XLD 75W-90 has been specially developed for use in the most heavily-loaded powertrains such as manual transmissions, transfer boxes and final drives. Always consult the Kroon-Oil advisory database for optimal use.

Specifications

API GL5, MT1

SAE J 2360 (PRI GL 0582)

DAF

Mack GO-J

MAN 342 Typ S1, 341 GA-2

Meritor 076-N, Meritor (EU) Verlengde olieerv.ter

Scania STO 2:0 G / 2:0 A FS

Volvo 97312

ZF TE-ML 05B, 12L, 12N, 16F, 17B, 19C, 21B

Typicals

Density at 15 °C, kg/l 0,878

Viscosity 100 °C, mm²/s 14,50

Flash Point COC, °C 210

Available packagings



37898
20 L can



36604
60 L drum



36605
208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.