

## Product Information 01.60.10

18-06-2024

### Atlantic 4T 10W-30

#### Description

Atlantic 4T 10W-30 is a 4-stroke motor oil for outboard engines. The product is based on premium base oils combined with special additives and features the following properties:

- Lubrication of all engine parts
- Very powerful detergency, which ensures the engine is cleaner
- Good cold start properties
- Very effective resistance to corrosion, oxidation and wear
- Outstanding shear stability

#### Application

Atlantic 4T 10W-30 is particularly suitable for use in high-speed, heavy-duty outboard motors. Because 4-stroke outboard motors place different requirements on motor oil, this oil is not suitable for use in cars.

#### Specifications

NMMA FC-W

#### Typicals

|                                      |       |
|--------------------------------------|-------|
| Density at 15 °C, kg/l               | 0,863 |
| Viscosity -25 °C, mPa.s              | 5420  |
| Viscosity 40 °C, mm <sup>2</sup> /s  | 82,80 |
| Viscosity 100 °C, mm <sup>2</sup> /s | 12,10 |
| Viscosity Index                      | 141   |
| Flash Point COC, °C                  | 232   |
| Pour Point, °C                       | -45   |
| Total Base Number, mgKOH/g           | 7,4   |
| Sulphate Ash, %                      | 0,79  |

#### Available packagings



33435  
1 L bottle



33527  
20 L pail



33526  
60 L drum



33528  
208 L drum



37627  
1000 L IBC

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.