



## Product Information 02.35.43

26-04-2024

### ATF Safeguard 6HP

#### Description

ATF Safeguard 6HP is a premium-quality, amber colored Long Life ATF, specifically designed for the latest generation of automatic 6HP transmissions produced by the transmission manufacturer ZF. Specially selected, premium-quality base oils, combined with the latest additives, provide ATF Safeguard 6HP with the following properties:

- Extremely high resistance to oxidation
- Excellent and very stable friction characteristics that enable longer oil-replacement intervals
- Outstanding lubrication properties
- Excellent protection against corrosion and resistance to foaming
- Excellent properties at low temperatures
- Fully compatible with the seal agents used by ZF

#### Application

ATF Safeguard 6HP is a premium amber colored synthetic ATF, specially formulated for use in the latest generation of ZF 6HP 6-speed automatic transmissions.

#### Specifications

Bentley PY112995 PA

BMW 8322 014516

Hyundai 040000C90SG

Jaguar Fluid 8432

Land Rover LR 023288

Maserati 231601

VAG G 055 005

Allison C4 / TES-389 / TES-295

BMW 7045E / 8072B / LA2634 / LT71141

DTFR 13C110 / 13C140 / 13C150 / 13C170 / 13C180

Ford Mercon V / Mercon / WSS-M2C922-A1

GM Dexron II/IIID/IIIE/IIIG/IIIH / TASA

Jaguar JLM 20238/20292/21044, JASO M315 Type 1A

Mazda M-III/Type T-IV / JWS 3309

MB 236.5 / 236.6 / 236.7 / 236.8

MB 236.9 / 236.10 / 236.11 / 236.91 / 236.93

Toyota DII/T/T-III/T-IV, Volvo 97341 / 1161540

VW G 052 025 / 052 055

VW G 052 162 / 052 990 / 055 025

ZF TE-ML 11A / 11B

ZF ATF 1375.4 (6HP Transmissions)

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

### Typicals

Density at 15 °C, kg/l	0,861
Viscosity -30 °C, mPa.s	2980
Viscosity 40 °C, mm <sup>2</sup> /s	33,10
Viscosity 100 °C, mm <sup>2</sup> /s	7,10
Viscosity Index	185
Flash Point COC, °C	200
Pour Point, °C	-54

### Available packagings



32762  
1 L bottle



36752  
5 L can



37536  
15 L Bag in  
Box



32803  
20 L pail



32804  
60 L drum



32805  
208 L drum