Product Information 07.10.34

25-04-2024

Gear Grease EP 1

Description

Gear Grease EP 1 is a multipurpose grease for central and gear lubrication. This grease has been manufactured from well-refined, high-viscosity base oils and a lithium complex soap thickener, under addition of Extreme Pressure- and other additives to obtain the following properties:

- Great adhesion to metals
- Excellent water-displacing capacity
- Very good stability
- Very effective against wear and corrosion
- Good pumping qualities
- Excellent Extreme Pressure (EP) properties

Application

Gear Grease EP 1 is extremely well applicable for centralized lubricating systems.

Specifications

NLGI Grade 1
DIN 51 502: KP1K-30
ISO 6743: L-XCCFB1

Typicals

Penetration (worked), 0,1 mm	325
Dropping Point, °C	>180
Temperature Limits, °C	-30 / +130
Base oil Viscosity, 40 °C, mm²/s	200,00
4-ball welding load, N	2600

Available packagings

33535
18 kg pail

33656
180 kg drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Kroon-Oil B.V. Dollegoorweg 15 7602 EC Almelo Phone +31 (0)546-818165. Sales +31 (0)546-816184. Fax +31 (0)546-817367. E-mail sales@kroon-oil.com