

Product Information 01.41.06

29-10-2020

Emperol 0W-30

Description

Emperol 0W-30 is a modern, synthetic, fuel-saving, universal motor oil. The product is based on synthetic base oils that have a naturally high viscosity index. It is supplemented with highly advanced additives to achieve the following properties:

- Fuel saving: up to 3%
- Extremely high viscosity index and high resistance to shearing
- A smooth cold start
- Protective lubricant film, even at extremely high operating temperatures
- Excellent dispersion and detergency
- Very high resistance to wear, corrosion and foaming

Application

Emperol 0W-30 is a universal, fuel-saving synthetic motor oil. The product is suitable for all petrol and diesel engines, both with and without turbochargers, in cars and vans. Always consult the product advisory database for optimal use.

Specifications

ACEA A5/B5

API SL

Volvo VCC 95200377

Typicals

Density at 15 °C, kg/l	0,843
Viscosity -35 °C, mPa.s	5770
Viscosity 40 °C, mm ² /s	53,10
Viscosity 100 °C, mm ² /s	10,10
Viscosity Index	181
Flash Point COC, °C	230
Pour Point, °C	-42
Total Base Number, mgKOH/g	10,1
Sulphate Ash, %	1,09
Noack, %	12,0

Available packagings



36805
208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.