

## Product Information 98.70.13

23-06-2024

### Kroon-Oil Neutralizer Oil Pro

#### Description

Neutralizer Oil Pro (NOP) is a neutralizing motor oil with an extra cleaning additive package and is used for every professional Flush treatment. This prevents any residual Flush agent from mixing directly with new engine oil. It effectively removes all remaining contaminated (Flush) engine oil and pollution residues, so that the new engine oil can start with a 100% cleaned engine and is not immediately tainted with any contaminated (Flush) engine oil.

#### Application

1) Remove Flushing Oil Pro engine oil while the engine is warm and replace the engine oil filter 2) Fill the engine with Neutralizer Oil Pro (NOP) 3) Let the engine idle for ± 10 minutes and occasionally increase to max. 2500 rpm. Do not drive with load! 4) Remove NOP and replace the engine oil filter. 5) Refill the engine with the correct quantity & applicable Kroon-Oil engine oil, see www.kroon-oil.com.

#### Typicals

|                                      |       |
|--------------------------------------|-------|
| Density at 15 °C, kg/l               | 0,886 |
| Viscosity -15 °C, mPa.s              | 5000  |
| Viscosity 40 °C, mm <sup>2</sup> /s  | 68,00 |
| Viscosity 100 °C, mm <sup>2</sup> /s | 8,00  |
| Viscosity Index                      | 98    |
| Flash Point COC, °C                  | 215   |
| Pour Point, °C                       | -24   |
| Total Base Number, mgKOH/g           | 3,5   |
| Sulphate Ash, %                      | 0,55  |

#### Available packagings



36886  
5 L can



36887  
15 L Bag in  
Box



36888  
60 L drum



36889  
208 L drum