

Product Information 98.70.13

15-07-2025

Kroon-Oil Neutralizer Oil Pro

Description

Neutralizer Oil Pro (NOP) is a neutralizing motor oil with an extra cleaning additive package and is used for every professional Flush treatment. This prevents any residual Flush agent from mixing directly with new engine oil. It effectively removes all remaining contaminated (Flush) engine oil and pollution residues, so that the new engine oil can start with a 100% cleaned engine and is not immediately tainted with any contaminated (Flush) engine oil.

Application

1. Remove Flushing Oil Pro engine oil while the engine is warm and replace the engine oil filter
2. Fill the engine with Neutralizer Oil Pro (NOP)
3. Let the engine idle for \pm 10 minutes and occasionally increase to max. 2500 rpm. Do not drive with load!
4. Remove NOP and replace the engine oil filter.
5. Refill the engine with the correct quantity & applicable Kroon-Oil engine oil, see www.kroon-oil.com.

Typicals

Density at 15 °C, kg/l	0,886
Viscosity -15 °C, mPa.s	5000
Viscosity 40 °C, mm ² /s	68,00
Viscosity 100 °C, mm ² /s	8,00
Viscosity Index	98
Flash Point COC, °C	215
Pour Point, °C	-24
Total Base Number, mgKOH/g	3,5
Sulphate Ash, %	0,55

Available packagings



36886
5 L can



36887
15 L Bag-in-
Box



36888
60 L drum



36889
208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.