Product Information 01.30.86

04-05-2024

Emperol 10W-30

Description

Emperol 10W-30 is an ultra-modern, fuel-saving, universal motor oil based on mineral and synthetic base oils that naturally have a high viscosity index. It is supplemented with carefully balanced additives to achieve the following properties:

- Fuel saving, up to 2%
- Extremely high viscosity index and high resistance to shearing
- A smooth cold start
- A protective lubricant film at high temperatures
- Excellent dispersion and detergency: thereby preventing a high build-up of black sludge
- Very high resistance to wear, corrosion and foaming
- Suitable for use in cars with the latest catalytic converter technologies

Application

Emperol 10W-30 is a universal, fuel-saving semi-synthetic motor oil. It is suitable for all petrol and diesel engines, both with and without turbochargers, in cars and vans. Always consult the product advisory database for optimal use.

Specifications

ACEA A3/B4

API SN/CF

VW 502.00/505.00

Typicals

Density at 15 °C, kg/l	0,861
Viscosity -25 °C, mPa.s	3850
Viscosity 40 °C, mm²/s	75,00
Viscosity 100 °C, mm²/s	12,15
Viscosity Index	160
Flash Point COC, °C	230
Pour Point, °C	-39
Total Base Number, mgKOH/g	10,8
Sulphate Ash, %	1,32

Available packagings

32892	36925	32893	36919
1 L bottle	4 L can	5 L can	208 L drum