



Product Information 01.20.70

23-04-2024

Kroon-Oil Dieselfleet 20W-50

Description

Dieselfleet CD+ 20W-50 is a 'new generation' gasoline- and diesel engine oil, formulated with solvent refined base oils and a well-balanced choice of additives. This engine oil has the following properties:

- Very powerful detergency prevents deposits in the engine
- Very strong dispersion that prevents from precipitation and sludge
- Powerful activity against corrosion and foam
- High and stable viscosity index
- Low sulphated ash number
- Powerful activity against wear resulting in strongly reduced wear of piston-rings and cylinder-liners

Application

Dieselfleet CD+ 20W-50 is applicable to gasoline and diesel engines (normally- or turbo-aspirated) even under the toughest operation conditions, all the year round. This engine oil has a special additive system and may therefore be used, when fuels with relatively high sulphur contents are involved. This engine oil is mainly developed to allow extended oil drain intervals and to prevent 'Boor Polishing' in diesel engines. Also suitable for application in EURO 3 and EURO 4 engines.

Specifications

ACEA E7

API CI-4 / SL

Cummins CES 20077 / 20078

Deutz DQC III-18

DTFR 15B110

Global DHD-1

MB 228.3

Typicals

Density at 15 °C, kg/l	0,895
Viscosity -15 °C, mPa.s	7500
Viscosity 40 °C, mm ² /s	156,30
Viscosity 100 °C, mm ² /s	17,50
Viscosity Index	123
Flash Point COC, °C	230
Pour Point, °C	-30
Total Base Number, mgKOH/g	11,1
Acid number, mgKOH/g	3,89
Sulphate Ash, %	1,43

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Available packagings



32469
5 L can



58026
20 L pail



33027
60 L drum



33613
200 L drum



33028
208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.