

## Product Information 09.10.20

02-07-2025

### Kroon-Oil Coolant SP 18

#### Description

Coolant SP 18 is a new-generation, ready-to-use premium Long Life coolant with frost-protection down to -37 °C. Special advanced and patented LOBRID PSI-OAT additive technology, based on organic inhibitors, phosphates and silicates, guarantees exceptional and long-lasting corrosion protection and long-term stability. Coolant SP 18 very quickly offers complete and long-term corrosion protection for newly installed corrosion-sensitive aluminium components. This product also offers excellent protection against overheating of modern downsized engines which often have increased thermal load and also provides very good protection against cavitation. Coolant SP 18 is completely free of amines, nitrites and borates.

#### Application

Coolant SP 18 is a green, ready-to-use Long Life coolant specifically developed for modern alloy cooling systems of the new generation of downsized engines which often have higher thermal loading than conventional engines. The product is suitable for use in various passenger car models including Volvo and BMW where the Volvo and BMW qualities claimed for this product are prescribed.

#### Specifications

ASTM D3306

JIS K 2234

BMW LC-18 / LC-87 / LC-97

CNH JIC-501

Cummins 85T8-2

Deutz DQC CA-14

Volvo 128 6083 / 002

#### Typicals

Density at 15 °C, kg/l 1,072

Refraction Index 20°C 1,387

pH - value 8,2

#### Available packagings



36963  
1 L bottle



38110  
5 L can



36991  
15 L Bag-in-  
Box



36964  
20 L can

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.