

Product Information 06.30.23

25-04-2024

Kroon-Oil SP Fluid 6033

Description

SP Fluid 6033 is a unique fluid that has been specially developed for use in Haldex/BorgWarner four-wheel drive systems. High-quality base oils, combined with an advanced additive package, give the product the following unique properties:

- Optimal friction properties, specifically tailored to the friction material of the wet clutch plates
- Excellent anti-stick-slip properties, guaranteeing a comfortable and silent functioning of the system
- An excellent "shear stability"
- Extremely high viscosity index, which means that the system also functions reliably under cold winter conditions
- The excellent resistance to oxidation prevents deposits in the system and vitrification of the friction plates
- Excellent EP properties

Application

SP Fluid 6033 is a high-quality hydraulic friction fluid specially developed for use in generation II, III, IV and V BorgWarner/Haldex four-wheel drive systems, which are used by various car manufacturers in their four-wheel drive models. Store this product in a dry and well-ventilated area, above 15°C.

Specifications

BMW HOC (BMW 83 22 2 413 513)

Ford 8U7J-8708687-AA

GM 1940057 / GM 93165387

JLR SL01-301 / JLR SL12-301

Volvo 1161641 / 31367940

VW G 052 175 / VW G 055 175

Typicals

Density at 15 °C, kg/l	0,866
Viscosity 40 °C, mm ² /s	28,50
Viscosity 100 °C, mm ² /s	6,00
Viscosity Index	166
Flash Point COC, °C	208
Pour Point, °C	-45

Available packagings



36978

850 ml bottle

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.