

Product Information VG.30.02

30-01-2023

VatOil PSF 115 LV

Description

PSF 115 LV is a special synthetic hydraulic fluid for power steering. The product is based on advanced base oils blended with special additives. The PSF 115 LV properties:

- Smooth suspension and levelling under all circumstances
- Extremely high and stable viscosity index
- Very low pouring point
- Day-to-day driving in summer and winter

Application

PSF 115 LV is used as a hydraulic medium for a wide variety of hydraulic systems, such as: power steering systems, level control systems, hydro-pneumatic suspension systems, shock absorbers, hydrostatic drives, ABS/ASR and ASC systems, hydraulically operated clutches and electro-hydraulic folding roof control systems, etc. Always consult the VatOil advisory database for optimal use.

Specifications

DIN 51524-T3

ISO 7308

MAN M 3289

PSA S71 2710

VW TL 52146

MB 345.0

Typicals

Density at 15 °C, kg/l	0,818
Viscosity -20 °C, mm ² /s	248
Viscosity 40 °C, mm ² /s	17,9
Viscosity 100 °C, mm ² /s	6,12
Viscosity Index	340
Flash Point COC, °C	174
Pour Point, °C	-63

Available packagings



50792
1 L bottle



50889
20 L can



50890
60 L drum



50891
210 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.