Product Information VM.20.54

30-01-2023

VatOil ProTech 10W-30

Description

ProTech 10W-30 is a modern, fuel-saving, universal motor oil based on mineral and synthetic base oils that naturally have a high viscosity index. It is supplemented with carefully balanced additives to achieve the following properties:

- Fuel saving (up to 2%)
- A very high viscosity index and high resistance to shearing
- A smooth cold start
- A protective lubricant film at high temperatures
- Excellent dispersion and detergency, thereby preventing a high build-up of black sludge
- Very high resistance to wear, corrosion and foaming
- Suitable for use in motor vehicles with the latest catalytic converter technologies

Application

ProTech 10W-30 is a universal, fuel-saving motor oil, suitable for all petrol and diesel engines, both with and without turbochargers, in cars and vans. Consult the product specifications in the product sheet for correct usage.

Specifications

ACEA A3/B3
API SL/CF

Typicals

Density at 15 °C, kg/l	0,861
Viscosity -25 °C, mPa.s	3520
Viscosity 40 °C, mm²/s	76,7
Viscosity 100 °C, mm²/s	12,10
Viscosity Index	154
Flash Point COC, °C	217
Pour Point, °C	-36
Total Base Number, mgKOH/g	9,9
Sulphate Ash, %	1,25
Magnesium, mg/kg	0

Available packagings


50793
4 L can


50820
5 L can


50865
20 L can


50866
60 L drum


50867
210 L drum

VatOil Dollegoorweg 15 7602 EC Almelo Phone +31 (0)546-818165. Sales +31 (0)546-816184. Fax +31 (0)546-817367. E-mail sales@vatoil.com