

Product Information 01.20.78

02-05-2024

Fleetoil Super 15W-40

Description

Fleetoil Super 15W-40 is a moderne diesel motor oil based om mineral base oils, supplemented with carefully balanced additives. Fleetoil Super 15W-40 features the following properties:

- Excellent detergency, thereby preventing deposits in the hot zone of the engine
- Excellent dispersion, which acts to prevent the formation of sediment and sludge
- High resistance to wear, corrosion and foaming
- A high and stable viscosity index
- A low ash content

Application

Fleetoil Super 15W-40 is a motor oil suitable for petrol and diesel engines both with and without turbochargers, under all operating conditions in all seasons. Fleetoil Super 15W-40 has a special additive package which makes it suitable for use in cases where a diesel fuel with a relative low sulphur content is used. This product is suitable for Euro 4 ad Euro 5 engines.

Specifications

ACEA E7

API CI-4 / SL

Cat ECF-1-a / ECF-2

Cummins CES 20077/20078

Detroit Diesel 93K215

Deutz DQC III-18

DTFR 15B110

Global DHD-1

JASO DH-1

Mack EO-N/EO-M Plus

MAN M 3275-1

MB 228.3

MTU Type 2

Renault VI RLD-2

Volvo VDS-3

Allison C3, CAT TO-2

ZF 04C / 04P / 07C / 07D / 21K

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Typicals

Density at 15 °C, kg/l	0,873
Viscosity -20 °C, mPa.s	5060
Viscosity 40 °C, mm ² /s	106,00
Viscosity 100 °C, mm ² /s	14,60
Viscosity Index	142
Flash Point COC, °C	228
Pour Point, °C	-33
Total Base Number, mgKOH/g	11,1
Sulphate Ash, %	1,43

Available packagings



37139
20 L can



36597
200 L drum



37124
208 L drum