Product Information 01.41.09

12-10-2024

Duranza MSP ECO 0W-20

Description

Duranza MSP ECO 0W-20 is a fuel-saving, state-of-the-art synthetic motor oil, specially developed for the new Ford EcoBlue diesel engines. This product is based on the latest generation of high-quality synthetic base oils with the addition of an advanced additive package to achieve the following properties:

- A very high level of fuel saving
- A very high and stable viscosity index
- Significant resistance to shearing
- A very smooth cold start, even at extremely low temperatures
- Protective lubricant film at extremely high operating temperatures
- Reduced formation of combustion residues
- Excellent dispersion and detergency
- Very high resistance to wear, corrosion and foaming

Application

Duranza MSP ECO 0W-20 is an ultra-thin fuel-saving synthetic motor oil, specially developed for use in the new Ford EcoBlue diesel engines for which Ford has set the specification WSS-M2C-952. In addition to being used in the new Ford EcoBlue engines, Duranza MSP ECO 0W-20 can also be used where car manufacturers prescribe an ACEA C5, C6, API SP quality SAE 0W-20 motor oil or one of the OE specifications listed.

Specifications

ACEA C5, C6
API SP
Jaguar Land Rover STJLR.03.5006
GM dexos D
Ford WSS-M2C952-A1
MB 229.71
Opel OV 040 1547 - A20

Typicals

Density at 15 °C, kg/l	0,845
Viscosity -35 °C, mPa.s	5120
Viscosity 40 °C, mm²/s	39,70
Viscosity 100 °C, mm²/s	8,26
Viscosity Index	190
Flash Point COC, °C	220
Pour Point, °C	-39
Total Base Number, mgKOH/g	9,4
Sulphate Ash, %	0,80

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Kroon-Oil B.V. Dollegoorweg 15 7602 EC Almelo Phone +31 (0)546-818165. Sales +31 (0)546-816184. Fax +31 (0)546-817367. E-mail sales@kroon-oil.com

Available packagings

37125	37126	37490	37127	37128	37129	37130	37746
1 L bottle	5 L can	15 L Bag in Box	20 L Bag in Box	20 L pail	60 L drum	208 L drum	1000 L IBC

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Kroon-Oil B.V. Dollegoorweg 15 7602 EC Almelo Phone +31 (0)546-818165. Sales +31 (0)546-816184. Fax +31 (0)546-817367. E-mail sales@kroon-oil.com