

Product Information 09.20.20

10-08-2022

Kroon-Oil Multi Grease FGG H1

Description

Multi Grease FGG H1 is a non-toxic, transparent, white grease formulated from a pure, medicinal base oil and PTFE. It is supplemented with special additives to achieve the following properties:

- Very strong adhesion
- Outstanding resistance to water and steam
- Effective protection against corrosion
- Effective moisture dispersant
- Very powerful protection against wear
- Effective anti stick-slip properties
- Outstanding penetrating ability

Application

Multi Grease FGG H1 is an H1-registered grease with a highly universal character. The special composition means that the product can be used for the following purposes, among others:

- Food industry
- Various types of bearings, including roller bearings and ball bearings
- Chains
- Cables
- A range of power drive systems, even in damp environments
- All kinds of guide-tracks and rods

Specifications

NLGI Grade 0/1

DIN 51825, KPGOG0,5N-30

Typicals

| | |
|------------------------------|-------|
| Density at 15 °C, kg/l | 0,900 |
| Penetration (worked), 0,1 mm | 280 |
| Dropping Point, °C | 300 |

Available packagings



33744

400 ml aerosol

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.