



Product Information 01.50.18

26-04-2024

Kroontrak MTH 10W-30

Description

Kroontrak MTH 10W-30 is a multifunctional oil for use in agricultural and earth-moving machinery. The product is based on premium, mineral base oils with additives, to achieve the following properties:

- Powerful dispersion and detergency
- High resistance to wear, corrosion and foaming
- Very high resistance to oxidation
- Excellent EP properties
- A high and stable viscosity index

Application

Kroontrak MTH 10W-30 is a so-called STOU: Super Tractor Oil Universal. It is therefore suitable for use as a universal lubricant for:

- Petrol engines
- Diesel engines
- Transmissions, including wet brakes
- Hydraulic systems Kroontrak MTH 10W-30 is suitable for all applications where one of the specifications below is required. This product can also be ideal for use in cases where a SAE 15W30 STOU is required.

Specifications

API SF/CG-4/GL-4

ACEA E3, MIL-L-2104D

Allison C4

Cat TO-2

Ford M2C159-C / M2C134-D

John Deere J27 / J20C

Massey Ferguson CMS M1145 / M1144 / M1139

Massey Ferguson CMS M1143 / M1135

MB 227.1

NH 410B

ZF TE-ML 06B / 07B

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Typicals

Density at 15 °C, kg/l	0,876
Viscosity -25 °C, mPa.s	4730
Viscosity 40 °C, mm ² /s	70,60
Viscosity 100 °C, mm ² /s	11,40
Viscosity Index	154
Flash Point COC, °C	228
Pour Point, °C	-33
Total Base Number, mgKOH/g	11,3
Sulphate Ash, %	1,57

Available packagings



37159
5 L can



37494
15 L Bag in
Box



37161
20 L pail



37162
60 L drum



37163
208 L drum



37164
1000 L IBC

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.