

## Product Information 01.50.19

12-07-2025

### Kroontrak CVT 10W-40

#### Description

Kroontrak CVT 10W-40 is a modern multifunctional oil for use in agricultural and earth-moving machinery. The product is based on a blend of high-grade "Group II/II+" base oils and an advanced additive package that gives the product the following unique properties:

- Excellent low temperature properties
- Excellent resistance to mechanical stress
- Very low volatility, which means less oil evaporates during operation
- Powerful dispersion and detergency
- High resistance to wear, corrosion and foaming
- Very high resistance to oxidation
- Excellent EP properties
- A high and stable viscosity index

#### Application

Kroontrak CVT 10W-40 is a high-grade, multi-purpose oil and is therefore ideally suited for use as a universal lubricant for the following applications:

- Petrol engines
- Diesel and turbo diesel engines
- Transmissions, including modern automatic CVTs
- Also suitable for systems with wet brakes
- Hydraulic systems

#### Specifications

API SF/CG-4/GL-4

ACEA E3, MIL-L-2104D

Allison C4

Cat TO-2

Ford M2C159-C / M2C134-D

John Deere J27 / J20C

Massey Ferguson CMS M1145 / M1144

MB 228.1 / 227.1

ZF TE-ML 06B / 07B

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

### Typicals

Density at 15 °C, kg/l	0,869
Viscosity -25 °C, mPa.s	5440
Viscosity 40 °C, mm <sup>2</sup> /s	87,60
Viscosity 100 °C, mm <sup>2</sup> /s	13,10
Viscosity Index	148
Flash Point COC, °C	242
Pour Point, °C	-39
Total Base Number, mgKOH/g	11,3
Sulphate Ash, %	1,57
HTHS, mPa.s	3,78
Noack, %	10,9

### Available packagings



37166  
5 L can



37491  
15 L Bag-in-  
Box



37938  
20 L can



37169  
60 L drum



37170  
208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.