

Product Information 05.40.10

05-12-2022

Atlantic 2T Outboard

Description

Atlantic 2T Outboard is a 2-stroke motor oil based on carefully selected premium base oils. It is supplemented with special, ashless 2-stroke additives to achieve the following properties:

- Optimal lubrication of all engine parts
- Effective detergency and resistance to wear and corrosion
- Limited smoke formation

Application

Atlantic 2T Outboard is suitable for all 2-stroke outboard motors and is used at a mixing ratio of 1 part oil to 50 parts fuel, or the mixing ratio required by the engine manufacturer.

Specifications

NMMA TC-W3

Typicals

Density at 15 °C, kg/l	0,876
Viscosity 40 °C, mm ² /s	35,60
Viscosity 100 °C, mm ² /s	6,29
Viscosity Index	126
Flash Point PM, °C	107
Pour Point, °C	-30
Total Base Number, mgKOH/g	8,7

Available packagings



00217
1 L bottle



35051
20 L pail



10130
60 L drum



33061
208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.