

## Product Information PW.30.02

21-05-2024

### DOT 5 Silicon Brake Fluid

#### Description

DOT 5 Silicone Brake Fluid is a silicone-based brake fluid. It has a wide temperature range from -40°C to over +260°C and ensures the optimal functioning of the brake system. The product extends the service life of the brake system and does not affect varnish or paint. DOT 5 Silicone Brake Fluid can be used safely in hydraulic brake and clutch systems on (race) motorcycles and karts provided they have seals that are resistant to a silicon brake fluid.

Please note! Completely remove the old brake fluid from the brake system. Never mix with other brake fluids. Replace the brake fluid every two years.

#### Application

Putoline Oil is a high-quality supplier of a wide range of lubricants and maintenance products. We only supply products for motorised two-wheelers and that makes us unique! Our years of experience, combined with continuous research results in the best price/quality ratio. Manufacturing our own products guarantees a consistently high quality. Putoline Oil, Driven by Technology!

Please refer to the advisory database for use of the correct product.

#### Specifications

FMVSS 116 DOT 5

SAE J1703, ISO 4925

MIL-B-46176

#### Typicals

Density at 15 °C, kg/l	0,953
Viscosity -40 °C, mm <sup>2</sup> /s	103
Viscosity 100 °C, mm <sup>2</sup> /s	5,80
Flash Point PM, °C	190
Boiling Point (reflux) , °C	260
Wet Boiling Point, °C	180

#### Available packagings



74042

500 ml bottle



74540

20 L Bag in  
Box

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.