



## Product Information 01.40.89

15-07-2024

### Presteza MSP 0W-30

#### Description

Presteza MSP 0W-30 is a modern, fuel-saving, fully synthetic motor oil, developed in accordance with the latest Mid SAPS technologies for use in cars with particulate filters and/or catalytic converters. It is supplemented with specially selected, synthetic base oils and advanced additives to achieve the following properties:

- Fuel saving
- Reduced formation of combustion residues due to lower SAPS content
- Extended service life of particulate filters and catalytic converters
- A smooth cold start
- A protective lubricant film at high operating temperatures
- Extended oil change intervals
- Excellent dispersion and detergency
- Very high resistance to wear, corrosion and foaming

#### Application

Presteza MSP 0W-30 is a fully synthetic, fuel-saving Long Life motor oil specifically for BMW models requiring the BMW Longlife-12 FE specification. It is also suitable for cars that require one of the specifications listed below. Always check the product recommendation database on [www.kroon-oil.com/en](http://www.kroon-oil.com/en) and/or the vehicle manufacturer's lubrication instructions.

#### Specifications

ACEA C2, A5/B5

API SP Resource Conserving

ILSAC GF-6A

BMW Longlife-12 FE

MB-Approval 229.61

DTFR 15D100

Ford WSS-M2C950-A

MB 227.61

VW VWC 53035

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

### Typicals

Density at 15 °C, kg/l	0,845
Viscosity -35 °C, mPa.s	5800
Viscosity 40 °C, mm <sup>2</sup> /s	48,50
Viscosity 100 °C, mm <sup>2</sup> /s	9,70
Viscosity Index	195
Flash Point COC, °C	226
Pour Point, °C	-48
Total Base Number, mgKOH/g	9,3
Sulphate Ash, %	0,80
HTHS, mPa.s	3,03
Noack, %	10,9

### Available packagings



37319  
1 L bottle



37320  
5 L can



37468  
15 L Bag in  
Box



37321  
20 L Bag in  
Box



37322  
20 L pail



37323  
60 L drum



37324  
208 L drum