



Product Information 09.40.04

04-02-2023

Kroon-Oil Drauliquid-LV Super DOT 4

Description

Drauliquid-LV Super DOT 4 is a premium brake fluid, specially developed for the latest generation of car with electronic safety systems. A rapid response time is essential for the vehicle to operate well, even at extremely low temperatures. That is why extra leeway is required in relation to the boiling points. For these reasons, Drauliquid-LV Super DOT 4 provides a relatively high safety margin compared to a normal DOT 4 brake fluids are used. Drauliquid-LV Super DOT 4 features the following properties:

- Extremely low viscosity, even in extremely cold conditions
- High boiling point, both wet and dry
- Does not affect seals
- Provides outstanding protection against corrosion

Application

Drauliquid-LV Super DOT 4 is a modern low-viscosity, synthetic brake fluid of a very high quality. The product is ideally suited for use in modern cars with electronic safety systems such as ABS, ASR, ESP, EBD, BAS and all of its variations. Drauliquid-LV Super DOT 4 can be easily mixed with other DOT 4 brake fluids.

Specifications

FMVSS 116 DOT 4

ISO 4925 Class 6

SAE J 1704

BMW QV 34001

Ford WSS-M6C65-A2

GMW 3356

MB 331.0

Toyota

VW 501.14 (TL 766-Z)

Typicals

Density at 15 °C, kg/l	1,035
Viscosity -40 °C, mm ² /s	665
Viscosity 40 °C, mm ² /s	6,4
Viscosity 100 °C, mm ² /s	2,20
Flash Point PM, °C	150
Flash Point COC, °C	110
Boiling Point (reflux) , °C	270
Wet Boiling Point, °C	170

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.



Available packagings



33820
1 L bottle



36902
20 L Bag in
Box



33868
20 L pail



33869
60 L drum



33552
208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.