

Product Information 10.10.09

22-05-2024

Kroon-Oil Coolant SP 14+

Description

Coolant SP 14+ is a high-quality, ready-to-use Long Life coolant (frost protection down to -37 °C), using a patented silicate-free P-OAT technology (Phosphated Organic Acid Technology). Application of this advanced technology gives this product the following benefits:

- Long service life due to the use of advanced P-OAT corrosion inhibitors
- Excellent cavitation protection
- Excellent corrosion protection of all common metals in modern cooling systems, including aluminium and ferro-alloys
- Unique inhibitor package also neutralises the negative effects of flux residue that arises in the production process of aluminium radiators
- Superior cooling properties due to silicate-free formula.

Application

Coolant SP 14+ is a modern green/blue, ready-to-use coolant for use in modern cooling systems of various Japanese and Korean models. This product is also suitable for various models of the Stellantis group and, among others, the Renault group (including Dacia, Nissan and Mitsubishi). Consult our product recommendation database at www.kroon-oil.com to see if Coolant SP 14+ is also suitable for your vehicle.

Specifications

ASTM D3306 / D6210

JIS K 2234

Fiat 9.55523

Ford WSS-M97B57-A2

MB 326.7

PSA B71 1111

Renault 41-01-001 -V / RNES-B-00014 v2.1

Typicals

Density at 15 °C, kg/l 1,071

pH - value 7,9

Crystallizationpoint, °C -37

Available packagings



37338
1 L bottle



37339
5 L can



37340
20 L can



37341
60 L drum



37342
208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.