

Product Information 08.30.09 20-05-2024

Kroon-Oil Emtor BF-5200

Description

Emtor BF-5200 is a high-quality water-miscible, boron-free, amine-containing EP metalworking fluid for the universal machining of a wide range of metals, including steel, cast iron, aluminium and stainless steel.

Emtor BF-5200 is particularly characterised by:

- Good anti-foaming behaviour
- Completely free of boric acid and biocide
- Strong flushing effect
- Extremely finely dispersed, highly stable emulsion
- Good corrosion protection
- Outstanding 'EP' properties
- Dermatologically tested, good protection against skin conditions
- Long-lasting emulsion stability ensuring minimal maintenance.

Application

Emtor BF-5200 is excellent for the turning, drilling and milling of steel, cast iron, stainless steel and aluminium. The concentration of the emulsion can be determined with a refractometer. The measured Brix value X refractometer factor = concentration in %.

Storage:

Protect against frost, heat and direct sunlight. Recommended temperature for storage and transport: 5 - 40°C.

Mixing ratio (refractometer factor 1.5) Steel, cast iron and high-tensile steel: 8%

Aluminium alloys: 8%

Typicals

Density at 15 °C, kg/l	0,990
Viscosity 20 °C, mm ² /s	114,00
Flash Point PM, °C	120

Available packagings













37393 37394 500 ml bottle 5 L can

15 L Bag in Box

20 L can

37396 60 L drum

37397 208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification