

Product Information 10.10.10

27-07-2024

Kroon-Oil Antifreeze SP 15+

Description

Antifreeze SP 15+ is a premium, orange, Long Life antifreeze for which a patented, silicate-free OAT additive technology has been used. This "Organic Acid Technology" guarantees excellent and long-lasting corrosion protection and stability. This product has a very high acid-neutralising capacity, allowing very long change intervals. Unique additives also neutralise the negative effects of flux residue that arises in the production process of aluminium radiators. Antifreeze SP 15+ is completely free of nitrites, borates and 2-ethylhexanoic acid (2-EHA).

Application

Antifreeze SP 15+ is a modern, orange, Long Life antifreeze. The product is specifically developed for the modern cooling systems of "Heavy-Duty" diesel engines in trucks, buses, agricultural vehicles, earth-moving machinery and industrial vehicles. This product is also suitable for passenger vehicles and other vehicles for which any of the quality levels listed below is prescribed. Dilute the product with demineralised water before use.

Specifications

ASTM D3306-20 / D6210-17

CNH MAT 3624 / 3724

DAF 74002

Detroit Diesel DFS 93 K217

Deutz DQC CB-14

DTFR 29C110

Ford WSS-M97B44-D

GM GMW 3420

Komatsu 07.892

Jaguar Land Rover STJLR.03.5212

MAN 324 Typ SNF

MB 325.3

Voith

Volvo VCS-2

Typicals

Density at 15 °C, kg/l	1,121
pH - value	8,6
Reserve alkalinity, pH	6,4
Crystallizationpoint: 33 vol%, °C	-18
Crystallizationpoint: 40 vol%, °C	-24
Crystallizationpoint: 50 vol%, °C	-38

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.



Available packagings



37380
1 L bottle



37381
20 L can

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.