Product Information 01.40.75

24-04-2024

Presteza MSP 5W-30

Description

Presteza MSP 5W-30 is a fuel-saving, synthetic motor oil, specially developed for the latest generation of cars that are equipped with a particulate filter and/or a catalytic converter. The special Mid SAPS technologies extend the service life. It is supplemented with specially selected base oils and advanced additives to achieve the following properties:

- Fuel saving
- Reduced formation of combustion residues (Mid SAPS)
- A smooth cold start
- A protective lubricant film at high operating temperatures
- Extended oil change intervals
- Excellent dispersion and detergency
- Very high resistance to wear, corrosion and foaming

Application

Presteza MSP 5W-30 is a fuel-saving synthetic motor oil. Suitable for petrol and diesel engines in cars and vans. If the manufacturer so requires, extended oil change intervals are possible. The product complies with the Mid SAPS requirements by Mercedes-Benz (MB 229.51) and BMW (BMW LL-04). Highly suitable for use in the latest BMW and Mercedes-Benz models equipped with a particulate filter and for all vehicles that require ACEA C3 motor oil.

Specifications

ACEA C2, C3
API SP
BMW Longlife-04
MB 229.51 / 229.52 / 229.31
Opel OV 040 1547 - D30 / G30
GM dexos 2
VW 505.00 / 505.01

Typicals

Density at 15 °C, kg/l	0,852
Viscosity -30 °C, mPa.s	5890
Viscosity 40 °C, mm²/s	72,00
Viscosity 100 °C, mm²/s	12,20
Viscosity Index	168
Flash Point COC, °C	226
Pour Point, °C	-36
Total Base Number, mgKOH/g	7,5
Sulphate Ash, %	0,74

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Kroon-Oil B.V. Dollegoorweg 15 7602 EC Almelo Phone +31 (0)546-818165. Sales +31 (0)546-816184. Fax +31 (0)546-817367. E-mail sales@kroon-oil.com

Available packagings

33228	34540	33229	37462	32722	33152	33154	33156
1 L bottle	5 L can	5 L can	15 L Bag in Box	20 L Bag in Box	20 L pail	60 L drum	208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Kroon-Oil B.V. Dollegoorweg 15 7602 EC Almelo Phone +31 (0)546-818165. Sales +31 (0)546-816184. Fax +31 (0)546-817367. E-mail sales@kroon-oil.com