

# **Product Information 01.40.60** 04-05-2024

## Asyntho 5W-30

#### Description

Asyntho 5W-30 is a modern, universal, fuel-saving, Long Life motor oil based on synthetic base oils with a naturally high viscosity index. It is supplemented with advanced additives to achieve the following properties:

- Fuel saving
- Limited evaporation losses
- A very high 'natural' viscosity index
- Significant resistance to shearing
- Smooth and effective lubrication on cold starts
- Protective lubricant film, even at extremely high operating temperatures
- Excellent dispersion and detergency
- Very high resistance to wear, corrosion and foaming

#### **Application**

Asyntho 5W-30 is a synthetic motor oil suitable for petrol and diesel engines, with and without turbochargers, in cars and vans insofar as they require the following specifications.

#### **Specifications**

| API | SN/ | 'CF |
|-----|-----|-----|
|-----|-----|-----|

| ACEA A3/B4       |
|------------------|
| BMW Longlife-01  |
| MB 229.3/226.5   |
| Renault RN0700   |
| VW 502.00/505.00 |
|                  |

GM LL-A-025/LL-B-025

#### **Typicals**

| Density at 15 °C, kg/l               | 0,857 |
|--------------------------------------|-------|
| Viscosity -30 °C, mPa.s              | 5870  |
| Viscosity 40 °C, mm²/s               | 72,80 |
| Viscosity 100 °C, mm <sup>2</sup> /s | 12,15 |
| Viscosity Index                      | 162   |
| Flash Point COC, °C                  | 251   |
| Pour Point, °C                       | -39   |
| Total Base Number, mgKOH/g           | 10,8  |
| Acid number, mgKOH/g                 | 2,10  |
| Sulphate Ash, %                      | 1,32  |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.



### **Available packagings**

















31070 1 L bottle

34668 4 L can

20029 5 L can

3/4/1 15 L Bag in Box

32724 in 20 L Bag in Box

45030 20 L pail

20031 60 L drum 2

20032 208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.