

Product Information PF.20.01

03-07-2024

Formula GP SAE 10

Description

Formula GP 10W is a premium-grade fork oil. The product is based on modern additives which give the product the following properties:

- Unsurpassed lubricating properties
- Reduces friction
- Better contact between tyre and road surface
- Counteracts foaming
- Stable viscosity
- Prevents loss of absorption Formula GP 10W has been specially developed for competition purposes.

Application

Putoline Oil is a high-quality supplier of a wide range of lubricants and maintenance products. We only supply products for motorised two-wheelers and that makes us unique! Our years of experience, combined with continuous research results in the best price/quality ratio. Manufacturing our own products guarantees a consistently high quality. Putoline Oil, Driven by Technology!

Please refer to the advisory database for use of the correct product.

Typicals

| | |
|--------------------------------------|-------|
| Density at 15 °C, kg/l | 0,846 |
| Viscosity -25 °C, mPa.s | 4960 |
| Viscosity 40 °C, mm ² /s | 52,40 |
| Viscosity 100 °C, mm ² /s | 8,96 |
| Viscosity Index | 152 |
| Flash Point COC, °C | 244 |
| Pour Point, °C | -33 |
| Acid number, mgKOH/g | 0,01 |

Available packagings



70135
1 L bottle



74633
15 L Bag in
Box



74275
20 L Bag in
Box