

Product Information 07.10.16

14-04-2024

Ball Bearing grease

Description

Ball Bearing Grease is based on highly refined base oils with lithium soap as a thickening agent, supplemented with additives to achieve the following properties:

- Strong adhesion to metal
- Outstanding water displacement
- Excellent stability
- Effective resistance to corrosion and wear
- Excellent pumpability

Application

Ball Bearing Grease is used for the lubrication of small to medium-sized ball bearings. Suitable for a wide range of applications.

Specifications

N.L.G.I. Klasse 2

DIN 51 502, KP 2 K-30

Typicals

Penetration (worked), 0,1 mm	280
Dropping Point, °C	190
Temperature Limits, °C	-30/130
Base oil Viscosity, 40 °C, mm ² /s	195,00
4-ball welding load, N	2600

Available packagings



03009

60 g tin

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.