

## Product Information PW.30.03

03-07-2024

### Putoline DOT 5.1 Brake Fluid

#### Description

DOT 5.1 Brake Fluid is a high-grade, synthetic brake fluid. The product exceeds the requirements of motorcycle manufacturers. Instructions for use:

- Replace the brake fluid every two years to continue to guarantee correct functioning
- Only use DOT 5.1 Brake Fluid when specified. Please consult your instruction book for the correct specifications
- Can be mixed with synthetic DOT 3 and DOT 4

#### Application

Putoline Oil is a high-quality supplier of a wide range of lubricants and maintenance products. We only supply products for motorised two-wheelers and that makes us unique! Our years of experience, combined with continuous research results in the best price/quality ratio. Manufacturing our own products guarantees a consistently high quality. Putoline Oil, Driven by Technology!

Please refer to the advisory database for use of the correct product.

#### Specifications

FMVSS 116 DOT 5.1

SAE J1703, ISO 4925

#### Typicals

Density at 15 °C, kg/l	1,070
Viscosity -40 °C, mm <sup>2</sup> /s	776
Viscosity 100 °C, mm <sup>2</sup> /s	2,30
Flash Point PM, °C	150
Boiling Point (reflux) , °C	275
Wet Boiling Point, °C	195
pH - 50% in ethanolsolution	8,5

#### Available packagings



74043

500 ml bottle



74586

15 L Bag in  
Box



74287

20 L Bag in  
Box