

Product Information 06.30.22

24-04-2024

Kroon-Oil SP Fluid 3023

Description

SP Fluid 3023 is a special hydraulic oil. The product has been specially developed for level-control systems in cars manufactured by Mercedes-Benz. Premium base oils, combined with the special additives, provide the product with the following unique properties:

- A high viscosity index that enables a highly beneficial level of viscosity to be achieved: the product even retains its optimal fluidity under extreme temperatures
- An extremely low pour point the product can still be used at low temperatures
- Very resistant to foaming: safety
- Does not affect seals: prevents leakages

Application

SP Fluid 3023 is a premium hydraulic fluid. Modern cars often incorporate several hydraulic applications that require a special product. SP Fluid 3023 has been developed for level control systems in Mercedes-Benz cars. It can be used when the MB 343.0 specification is required.

Specifications

MB 343.0

Typicals

Density at 15 °C, kg/l	0,860
Viscosity 40 °C, mm ² /s	21,00
Viscosity 100 °C, mm ² /s	5,10
Viscosity Index	186
Flash Point COC, °C	101
Pour Point, °C	-50

Available packagings



33943
1 L bottle



33945
20 L pail



32665
60 L drum



32666
208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.