



## Product Information 01.20.62

26-04-2024

### Dieselfleet MSP 15W40

#### Description

Dieselfleet MSP 15W-40 is a multigrade, diesel motor oil of the latest generation, perfect for use in the latest heavy-duty 4-stroke diesel engines. Meets the latest standard issued by truck manufacturers. Premium, solvent-refined base oils combined with unique Low SAPS additives provide the product with the following properties:

- Meets or exceeds the latest emission requirements
- Very powerful detergency: minimal deposits in the hot zone of the engine
- Very strong dispersion: deposits and sludge formation are severely restricted
- Very high resistance to corrosion and foaming
- A high and stable viscosity index
- A low sulfate ash content
- Powerful wear resistance: resulting in reduced wear of piston rings and cylinder wall

#### Application

Dieselfleet MSP 15W-40 is a heavy-duty motor oil suitable for both road and off-road use. Dieselfleet MSP 15W-40 contributes to low exhaust gas emissions and low particulate emissions, thereby extending the service-life of catalytic converters and particulate filters. Because this Low SAPS complies with the requirements of both European and North American truck manufacturers, it has a wide range of potential applications.

#### Specifications

ACEA E7, E9, E11

API CK-4 / SN

Mack EOS-4.5

Renault VI RLD-3

Volvo VDS-4.5

Cat ECF-3

Cummins CES 20086

Detroit Diesel 93K222

Deutz DQC III-18 LA

DTFR 15C100

Ford WSS M2C171-F1

JASO DH-2

MAN M 3775

MB 228.31

MTU Type 2.1

Allison TES-439

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

### Typicals

Density at 15 °C, kg/l	0,877
Viscosity -20 °C, mPa.s	5400
Viscosity 40 °C, mm <sup>2</sup> /s	108,00
Viscosity 100 °C, mm <sup>2</sup> /s	14,30
Viscosity Index	135
Flash Point COC, °C	240
Pour Point, °C	-42
Total Base Number, mgKOH/g	9,7
Sulphate Ash, %	0,99

### Available packagings



35951  
4 L can



37504  
15 L Bag in  
Box



32730  
20 L Bag in  
Box



33955  
20 L pail



36895  
20 L can



33963  
60 L drum



34016  
200 L drum



33819  
208 L drum



34497  
1000 L IBC

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.