

## Product Information 07.10.06

19-04-2024

### Atlantic Shipping Grease

#### Description

Atlantic Shipping Grease is based on highly refined base oils containing lithium soap as a thickening agent. It is supplemented with additives to achieve the following properties:

- Good adhesion to metal
- Outstanding resistance to fresh and salt water
- High mechanical stability
- Excellent resistance to corrosion and oxidation
- Excellent pumpability in automatic lubrication devices

#### Application

Atlantic Shipping Grease has been specially developed for lubricating propeller shafts. Atlantic Shipping Grease can be universally applied in any propeller shaft tube. Furthermore, the formulation of this grease means that it is ideally suited as a universal on-board grease for sliding and ball bearings.

#### Specifications

N.L.G.I. Klasse 2

DIN 51 502, KP 2 K-30

#### Typicals

Penetration (worked), 0,1 mm	280
Dropping Point, °C	190
Temperature Limits, °C	-30/130
Base oil Viscosity, 40 °C, mm <sup>2</sup> /s	100,00
4-ball welding load, N	2600

#### Available packagings



03014

400 g cartridge



34075

600 g pot



03309

5 kg canister



38028

18 kg pail



13109

50 kg drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.