

Product Information 05.30.15

09-07-2025

Tornado Snow

Description

Tornado Snow is a fully synthetic, 2-stroke motor oil specially designed for snow mobiles. Its special 2-stroke additives provide the product with the following properties:

- Outstanding lubrication of all engine parts due to its high adherence, thereby reducing wear and increasing the service life of the engine
- Powerful detergency that ensures that the combustion chamber and the exhaust ports remain clear of deposits, even at high operating temperatures
- Almost complete combustion so that the spark plugs remain clean, ensuring optimal engine performance
- Excellent corrosion and wear resistance
- Limited formation of smoke and odour
- Can also be mixed with unleaded petrol

Application

Tornado Snow is suitable for high speed and heavy-duty 2-stroke snowmobile engines. Tornado Snow is often used at a mixing ratio of 1 part oil to 50 parts fuel, or the mixing ratio required by the engine manufacturer. Tornado Snow is a self-mixing motor oil that can also be used in automatic lubrication systems.

Specifications

API TC

JASO FD

Husqvarna

ISO-L-EGD

Piaggio Hexagon

Typicals

Density at 15 °C, kg/l	0,878
Viscosity 40 °C, mm ² /s	70,50
Viscosity 100 °C, mm ² /s	11,00
Viscosity Index	147
Flash Point PM, °C	78
Pour Point, °C	-45
Total Base Number, mgKOH/g	2,9
Sulphate Ash, %	0,12