

Product Information 05.30.15

17-05-2025

Tornado Snow

Description

Tornado Snow is a fully synthetic, 2-stroke motor oil specially designed for snow mobiles. Its special 2-stroke additives provide the product with the following properties:

- Outstanding lubrication of all engine parts due to its high adherence, thereby reducing wear and increasing the service life of the engine
- Powerful detergency that ensures that the combustion chamber and the exhaust ports remain clear of deposits, even at high operating temperatures
- Almost complete combustion so that the spark plugs remain clean, ensuring optimal engine performance
- Excellent corrosion and wear resistance
- Limited formation of smoke and odour
- Can also be mixed with unleaded petrol

Application

Tornado Snow is suitable for high speed and heavy-duty 2-stroke snowmobile engines. Tornado Snow is often used at a mixing ratio of 1 part oil to 50 parts fuel, or the mixing ratio required by the engine manufacturer. Tornado Snow is a self-mixing motor oil that can also be used in automatic lubrication systems.

Specifications

API TC

JASO FD

Husqvarna

ISO-L-EGD

Piaggio Hexagon

Typicals

Density at 15 °C, kg/l 0,878

Viscosity 40 °C, mm²/s 70,50

Viscosity 100 °C, mm²/s 11,00

Viscosity Index 147

Flash Point PM, °C 78

Pour Point, °C -45

Total Base Number, mgKOH/g 2,9

Sulphate Ash, % 0,12

Available packagings



34164

1 L bottle

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.