

Product Information 01.40.87 25-04-2024

Kroon-Oil Duranza LSP 5W-30

Description

Duranza LSP 5W-30 is a modern, fuel-saving, synthetic motor oil, developed in accordance with the latest Low SAPS technologies for use in cars with particulate filters and/or catalytic converters. It is supplemented with specially selected, synthetic base oils and advanced additives to achieve the following properties:

- Fuel saving
- Reduced formation of combustion residues due to lower SAPS content
- Extended service life of particulate filters and catalytic converters
- A smooth cold start
- A protective lubricant film at high operating temperatures
- Extended oil change intervals
- Excellent dispersion and detergency
- Very high resistance to wear, corrosion and foaming

Application

Duranza LSP 5W-30 is a fuel-saving, synthetic motor oil for the latest generation of cars with a particulate filter and/or catalytic converter. The product is also highly suitable for the latest generation of Ford cars and vans equipped with modern three-way catalytic converters and particulate filters. It can be used if the Ford specification M2C-913-D is recommended and in cases in which one of the older Ford M2C-913-C, M2C-913-B or M2C-913-A specifications is required.

Specifications

ACEA A5/B5, A1/B1	
API SL/CF	
Ford WSS-M2C913-D	
Jaguar Land Rover STJLR.03.5003	
Renault RN0700	
VW VWC 53036	

Typicals

Density at 15 °C, kg/l	0,853
Viscosity -30 °C, mPa.s	3890
Viscosity 40 °C, mm²/s	54,50
Viscosity 100 °C, mm²/s	9,90
Viscosity Index	170
Flash Point COC, °C	220
Pour Point, °C	-39
Total Base Number, mgKOH/g	10,1
Sulphate Ash, %	1,09

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.



Available packagings



















34202 1 L bottle

35685 4 L can

34203 5 L can

15 L Bag in

32725 20 L Bag in Box

34204 20 L pail

32371 20 L can

34205 3 60 L drum 208

34206 208 L drum



32953 1000 L IBC

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.