



# Gas Engine Oil Bio-LF 40

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830  
Date of issue: 22-5-2018 Revision date: 22-5-2018 Version: 1.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Trade name : Gas Engine Oil Bio-LF 40  
Product code : 01.10.35  
Type of product : Lubricants  
Product group : Trade product

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Main use category : Industrial use, Professional use, Consumer use  
Use of the substance/mixture : Engine oil

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

Kroon Oil BV  
Dollegoorweg 15  
7602 EC Almelo - Netherlands  
T 0031 (0)546 81 81 65  
[vib@kroon\\_oil.nl](mailto:vib@kroon_oil.nl)

#### 1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
United Kingdom	National Poisons Information Service (Cardiff Centre) Gwenwyn Ward, Llandough Hospital	Penarth CF64 2XX Cardiff	0344 892 0111	

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP] Mixtures/Substances: SDS EU 2015: According to Regulation (EU) 2015/830 (REACH Annex II)

Not classified

#### Adverse physicochemical, human health and environmental effects

To our knowledge, this product does not present any particular risk, provided it is handled in accordance with good occupational hygiene and safety practice.

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

EUH-statements : EUH208 - Contains Calcium di(alkyl(C20-C24, even numbered) branched)-methyl benzenesulfonate(722503-68-6), A mixture of: calcium bis(C10-14 branched alkylsalicylate); calcium bis(C18-30 alkyl salicylate); calcium bis(C18-30 alkyl phenolate); calcium bis(C10-14 branched alkyl phenolate); lubricating oil (C15-30). May produce an allergic reaction.  
EUH210 - Safety data sheet available on request.

#### 2.3. Other hazards

No additional information available

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Comments : Highly refined mineral oils and additives.

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Amines, polyethylenepoly-, reaction products with succinic anhydride polyisobutenyl derivatives	(CAS-No.) 84605-20-9 (EC-No.) 617-593-2	1 - 2,5	Aquatic Chronic 4, H413
Phenol, dodecyl-, sulfured, carbonates, calcium salts, overbased	(CAS-No.) 68784-26-9 (EC-No.) 272-234-3 (REACH-no) 01-2119524004-56	0,1 - 2,5	Aquatic Chronic 4, H413

# Gas Engine Oil Bio-LF 40

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Comments : The highly refined mineral oil contains <3% (w/w) DMSOextract, according to IP346.

Full text of H-statements: see section 16

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures general : If you feel unwell, seek medical advice (show the label where possible).  
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.  
First-aid measures after skin contact : Wash skin with plenty of water.  
First-aid measures after eye contact : Rinse eyes with water as a precaution.  
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell. Do not induce vomiting.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : No additional information available. Not expected to present a significant hazard under anticipated conditions of normal use.

Symptoms/effects after ingestion : May result in aspiration into the lungs, causing chemical pneumonia.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.  
Unsuitable extinguishing media : Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Combustible liquid.  
Hazardous decomposition products in case of fire : Toxic fumes may be released. Incomplete combustion releases dangerous carbon monoxide, carbon dioxide and other toxic gases.

#### 5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area.

##### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material.  
Other information : Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

For further information refer to section 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Provide good ventilation in process area to prevent formation of vapour.  
Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep container closed when not in use. Keep in a cool, well-ventilated place away from heat.  
Storage temperature : 0 - 40 °C

#### 7.3. Specific end use(s)

No additional information available

# Gas Engine Oil Bio-LF 40

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### Gas Engine Oil Bio-LF 40

EU	Exposure limits/standards for materials that can be formed when handling this product. When mists/aerosols can occur the following is recommended: 5 mg/m <sup>3</sup> - ACGIH TLV (inhalable fraction).
----	--

#### 8.2. Exposure controls

##### Appropriate engineering controls:

Ensure good ventilation of the work station.

##### Materials for protective clothing:

Wear suitable protective clothing

##### Hand protection:

Protective gloves

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Reusable gloves	Nitrile rubber (NBR), Neoprene rubber (HNBR)	5 (> 240 minutes), 6 (> 480 minutes)	>=0,35		EN 374

##### Eye protection:

Safety glasses

Type	Use	Characteristics	Standard
Safety glasses	Droplet	clear	EN 166

##### Skin and body protection:

Wear suitable protective clothing

##### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

##### Personal protective equipment symbol(s):



##### Environmental exposure controls:

Avoid release to the environment.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: brown.
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: -27 °C - ASTM D5950 (pour point)
Boiling point	: No data available
Flash point	: 270 °C - ASTM D92 (COC)
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 0,872 kg/l (15 °C) - ASTM D4052

# Gas Engine Oil Bio-LF 40

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Solubility	: Water : Practically not miscible.
Log Pow	: No data available
Viscosity, kinematic	: 124,4 mm <sup>2</sup> /s (40 °C) - ASTM D7279
Viscosity, dynamic	: No data available
Explosive properties	: Presents no particular fire or explosion hazard.
Oxidising properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

VOC content	: 0 %
-------------	-------

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use. Reacts violently with (strong) oxidizers.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

No decomposition if stored normally.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

### Gas Engine Oil Bio-LF 40

Viscosity, kinematic	124,4 mm <sup>2</sup> /s (40 °C) - ASTM D7279
----------------------	---

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Acute aquatic toxicity	: Not classified
Chronic aquatic toxicity	: Not classified

### Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased (68784-26-9)

LC50 fish 1	> 1000 mg/l (OECD 203 method)
EC50 Daphnia 1	> 1000 mg/l 48h (Daphnia magna) [OECD 202]
EC50 other aquatic organisms 1	> 100 mg/l 96h (Crangon crangon)
ErC50 (algae)	> 500 mg/l (OECD 201 method)
NOEC (acute)	> 1000 mg/l 96h (Pimephales promelas) [OECD 203]
NOEC chronic algae	> 500 mg/l 96h (Pseudokirchneriella subcapitata) [OECD 201]

# Gas Engine Oil Bio-LF 40

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 12.2. Persistence and degradability

#### Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased (68784-26-9)

Persistence and degradability	Not readily biodegradable.
Biodegradation	13,4 % Directive 67/548/CEE, Annex V, C.4.C.

### 12.3. Bioaccumulative potential

#### Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased (68784-26-9)

Bioconcentration factor (BCF REACH)	2,2
Log Pow	9,5

### 12.4. Mobility in soil

#### Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased (68784-26-9)

Ecology - soil	Product adsorbs little onto the soil.
----------------	---------------------------------------

### 12.5. Results of PBT and vPvB assessment

#### Component

Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased (68784-26-9)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
---	---

### 12.6. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods	: Do not allow into drains or water courses. Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.
European List of Waste (LoW) code	: 13 02 05* - mineral-based non-chlorinated engine, gear and lubricating oils

## SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.2. UN proper shipping name</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.3. Transport hazard class(es)</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.4. Packing group</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.5. Environmental hazards</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

No supplementary information available

### 14.6. Special precautions for user

#### Overland transport

Not applicable

#### Transport by sea

Not applicable

#### Air transport

Not applicable

#### Inland waterway transport

Not applicable

#### Rail transport

Not applicable

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

# Gas Engine Oil Bio-LF 40

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### 15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:	
3(c) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1	Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased
3. Liquid substances or mixtures which are regarded as dangerous in accordance with Directive 1999/45/EC or are fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008	Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

VOC content : 0 %

Directive 2012/18/EU (SEVESO III)

##### 15.1.2. National regulations

No additional information available

#### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

### SECTION 16: Other information

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
vPvB	Very Persistent and Very Bioaccumulative

Full text of H- and EUH-statements:	
Aquatic Chronic 4	Hazardous to the aquatic environment — Chronic Hazard, Category 4
H413	May cause long lasting harmful effects to aquatic life.

# Gas Engine Oil Bio-LF 40

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

EUH208	Contains Calcium di(alkyl(C20-C24, even numbered) branched)-methyl benzenesulfonate(722503-68-6), A mixture of: calcium bis(C10-14 branched alkylsalicylate); calcium bis(C18-30 alkyl salicylate); calcium bis(C18-30 alkyl phenolate); calcium bis(C10-14 branched alkyl phenolate); lubricating oil (C15-30). May produce an allergic reaction.
EUH210	Safety data sheet available on request.

SDS EU (REACH Annex II)

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*