



Kroon-Oil SP Matic 2094

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 22-5-2018 Revision date: 30-9-2022 Supersedes version of: 26-7-2022 Version: 3.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : Kroon-Oil SP Matic 2094
Product code : 02.35.41
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public
Main use category : Industrial use, Professional use, Consumer use
Use of the substance/mixture : Transmission oil
Function or use category : Lubricants and additives

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Kroon Oil BV B.V.
Dollegoorweg, 15
NL- 7602 EC Almelo
Netherlands
T 0031 (0)546 81 81 65
vib@kroon-oil.nl

1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
United Kingdom	National Poisons Information Service (Cardiff Centre) University Hospital Llandough	Penlan Road CF64 2XX Llandough	0344 892 0111	Only for healthcare professionals

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Acute toxicity (inhalation:dust,mist) Category 4 H332
Aspiration hazard, Category 1 H304
Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Harmful if inhaled. May be fatal if swallowed and enters airways.

Kroon-Oil SP Matic 2094

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS07

GHS08

Signal word (CLP)

: Danger

Contains

: Distillates (petroleum), solvent-dewaxed light paraffinic, Dec-1-ene, dimers, hydrogenated, Distillates (petroleum), hydrotreated heavy paraffinic, Distillates (petroleum), hydrotreated light paraffinic, Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based

Hazard statements (CLP)

: H304 - May be fatal if swallowed and enters airways.
H332 - Harmful if inhaled.

Precautionary statements (CLP)

: P101 - If medical advice is needed, have product container or label at hand.
P102 - Keep out of reach of children.
P261 - Avoid breathing mist, vapours.
P271 - Use only outdoors or in a well-ventilated area.
P301+P310+P331 - IF SWALLOWED: Immediately call a doctor. Do NOT induce vomiting.
P312 - Call a POISON CENTRE or doctor if you feel unwell.
P405 - Store locked up.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
EUH-statements : EUH208 - Contains 4,4'-thiodiethylene hydrogen -2-octadecenylsuccinate. May produce an allergic reaction.

2.3. Other hazards

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

Component	
Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
4,4'-thiodiethylene hydrogen -2-octadecenylsuccinate (93882-40-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

Kroon-Oil SP Matic 2094

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

3.2. Mixtures

Comments : Highly refined mineral oils and additives.

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Distillates (petroleum), hydrotreated heavy paraffinic (Note L)	CAS-No.: 64742-54-7 EC-No.: 265-157-1 EC Index-No.: 649-467-00-8 REACH-no: 01-2119484627-25	50 – 80	Asp. Tox. 1, H304
Dec-1-ene, dimers, hydrogenated	CAS-No.: 68649-11-6 EC-No.: 500-228-5 REACH-no: 01-2119493069-28	25 – 50	Acute Tox. 4 (Inhalation:dust,mist), H332 Asp. Tox. 1, H304
Oil Soluble Polyalkylene Glycol	-	2,5 – 5	Aquatic Chronic 3, H412
Distillates (petroleum), hydrotreated light paraffinic (Note L)	CAS-No.: 64742-55-8 EC-No.: 265-158-7 EC Index-No.: 649-468-00-3 REACH-no: 01-2119487077-29	1 – 2,5	Asp. Tox. 1, H304
Distillates (petroleum), solvent-dewaxed light paraffinic substance with a Community workplace exposure limit (Note L)	CAS-No.: 64742-56-9 EC-No.: 265-159-2 EC Index-No.: 649-469-00-9 REACH-no: 01-2119480132-48	0,1 – 2,5	Asp. Tox. 1, H304
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate	CAS-No.: 125643-61-0 EC-No.: 406-040-9 EC Index-No.: 607-530-00-7 REACH-no: 01-0000015551-76	0,1 – 2,5	Aquatic Chronic 4, H413
Reaction products of fatty acids, C14-C18 (branched and linear) and C18 (unsaturated) with tetraethylenepentamine (linear, branched, cyclic)	EC-No.: 701-204-9 REACH-no: 01-2119960832-33	0,1 – 2,5	Skin Irrit. 2, H315 Eye Irrit. 2, H319
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (Note L)	CAS-No.: 72623-87-1 EC-No.: 276-738-4 EC Index-No.: 649-483-00-5 REACH-no: 01-2119474889-13	0,1 – 2,5	Asp. Tox. 1, H304
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (Note L)	CAS-No.: 72623-86-0 EC-No.: 276-737-9 EC Index-No.: 649-482-00-X REACH-no: 01-2119474878-16	0,1 – 2,5	Asp. Tox. 1, H304
Phosphonic acid, dibutyl ester, reaction products with 2-(octylthio)- ethanol	EC-No.: 424-820-7 REACH-no: 01-0000017126-75	0,1 – 0,3	Acute Tox. 4 (Dermal), H312 Skin Corr. 1B, H314 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=10)
4,4'-thiodiethylene hydrogen -2-octadecenylsuccinate	CAS-No.: 93882-40-7 EC-No.: 299-434-3 REACH-no: 01-2120735527-50	< 0,3	Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411

Comments : The highly refined mineral oil contains <3% (w/w) DMSOextract, according to IP346.

Kroon-Oil SP Matic 2094

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Note L : The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346 'Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions — Dimethyl sulphoxide extraction refractive index method', Institute of Petroleum, London. This note applies only to certain complex oil-derived substances in Part 3. Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Call a physician immediately.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.
First-aid measures after skin contact	: Wash skin with plenty of water.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after ingestion	: Risk of lung oedema.
----------------------------------	------------------------

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Combustible liquid.
Hazardous decomposition products in case of fire	: Toxic fumes may be released. Incomplete combustion releases dangerous carbon monoxide, carbon dioxide and other toxic gases.

5.3. Advice for firefighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
--------------------------------	--

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures	: Ventilate spillage area. Avoid breathing dust/fume/gas/mist/vapours/spray.
----------------------	--

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	---

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	: Take up liquid spill into absorbent material.
Other information	: Dispose of materials or solid residues at an authorized site.

Kroon-Oil SP Matic 2094

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Provide good ventilation in process area to prevent formation of vapour.
Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep container closed when not in use. Keep in a cool, well-ventilated place away from heat.
Storage temperature : 0 – 40 °C

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Kroon-Oil SP Matic 2094	
EU - Indicative Occupational Exposure Limit (IOEL)	
Exposure limits/standards for materials that can be formed when handling this product. When mists/aerosols can occur the following is recommended	5 mg/m ³ - ACGIH TLV (inhalable fraction).
Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	5 mg/m ³
Oil Soluble Polyalkylene Glycol	
EU - Indicative Occupational Exposure Limit (IOEL)	
Exposure limits/standards for materials that can be formed when handling this product. When mists/aerosols can occur the following is recommended	5 mg/m ³ - ACGIH TLV (inhalable fraction).

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

Kroon-Oil SP Matic 2094

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

Eye protection			
Type	Field of application	Characteristics	Standard
Safety glasses	Droplet	clear	EN 166

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

Hand protection					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Reusable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	≥0.35		EN ISO 374

Other skin protection

Materials for protective clothing:

Wear suitable protective clothing

8.2.2.3. Respiratory protection

Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Blue.
Odour	: characteristic.
Odour threshold	: Not available
Melting point	: Not applicable

Kroon-Oil SP Matic 2094

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Freezing point	: -57 °C - ASTM D5950 (pour point)
Boiling point	: Not available
Flammability	: Not applicable
Explosive properties	: Presents no particular fire or explosion hazard.
Explosive limits	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: 188 °C - ASTM D92 (COC)
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: 18,8 mm ² /s (40 °C) - ASTM D7279
Solubility	: Water: Insoluble / Slightly miscible
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50 °C	: Not available
Density	: 0,835 kg/l (15 °C) - ASTM D4052
Relative density	: Not available
Relative vapour density at 20 °C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

VOC content : 0 %

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use. Reacts violently with (strong) oxidizers.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

No decomposition if stored normally.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Harmful if inhaled.

Kroon-Oil SP Matic 2094

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Kroon-Oil SP Matic 2094	
ATE CLP (dust,mist)	4,206 mg/l/4h
Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 5000 mg/kg
LC50 Inhalation - Rat (Dust/Mist)	5,53 mg/l/4h
Dec-1-ene, dimers, hydrogenated (68649-11-6)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 3000 mg/kg
LC50 Inhalation - Rat (Dust/Mist)	1,17 mg/l/4h
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)	
LD50 oral rat	> 2000 mg/kg (OECD 401 method)
LD50 dermal rat	> 2000 mg/kg (OECD 402 method)
Phosphonic acid, dibutyl ester, reaction products with 2-(octylthio)- ethanol	
LD50 oral rat	> 2000 mg/kg bodyweight
LD50 dermal rabbit	> 500 mg/kg bodyweight
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 Inhalation - Rat	> 5,53 mg/l/4h
4,4'-thiodiethylene hydrogen -2-octadecenylsuccinate (93882-40-7)	
LD50 oral rat	> 10000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rabbit	> 3160 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 Inhalation - Rat (Dust/Mist)	5,53 mg/l/4h
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method)
LD50 dermal rabbit	> 2000 mg/kg (OECD 402 method)
LC50 Inhalation - Rat	5,53 mg/l/4h (OECD 403 method)
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)	
LD50 oral rat	> 5000 mg/kg (OECD 401 method)
LD50 dermal rabbit	> 2000 mg/kg (OECD 402 method)
LC50 Inhalation - Rat	> 5,53 mg/l (OECD 403 method)
Skin corrosion/irritation	: Not classified

Kroon-Oil SP Matic 2094

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)	
pH	7
Serious eye damage/irritation	: Not classified
Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)	
pH	7
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day
NOAEL (subchronic, oral, animal/male, 90 days)	≥ 2000 mg/kg bodyweight
NOAEL (subchronic, oral, animal/female, 90 days)	≥ 2000 mg/kg bodyweight
4,4'-thiodiethylene hydrogen -2-octadecenylsuccinate (93882-40-7)	
NOAEL (oral, rat, 90 days)	300 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)
Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Aspiration hazard	: May be fatal if swallowed and enters airways.
Kroon-Oil SP Matic 2094	
Viscosity, kinematic	18,8 mm ² /s (40 °C) - ASTM D7279
Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)	
Viscosity, kinematic	< 20,5 mm ² /s
Aliphatic, alicyclic or aromatic hydrocarbon	Yes
Dec-1-ene, dimers, hydrogenated (68649-11-6)	
Viscosity, kinematic	≤ 20,5 mm ² /s (40°C)
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)	
Viscosity, kinematic	6,2 mm ² /s
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
Viscosity, kinematic	< 20,5 mm ² /s
Aliphatic, alicyclic or aromatic hydrocarbon	Yes
Oil Soluble Polyalkylene Glycol	
Viscosity, kinematic	46 mm ² /s (40 °C) - ASTM D7279
Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)	
Viscosity, kinematic	< 20,5 mm ² /s

Kroon-Oil SP Matic 2094

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)	
Aliphatic, alicyclic or aromatic hydrocarbon	Yes

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)	
Viscosity, kinematic	< 20,5 mm ² /s (40 °C) - ASTM D7279
Aliphatic, alicyclic or aromatic hydrocarbon	Yes

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)	
Viscosity, kinematic	< 20,5 mm ² /s (40 °C) - ASTM D7279
Aliphatic, alicyclic or aromatic hydrocarbon	Yes

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified
Not rapidly degradable	

Kroon-Oil SP Matic 2094	
LC50 - Fish [1]	> 100 mg/l The data are derived from the evaluations or test results achieved with similar products
EC50 - Crustacea [1]	> 100 mg/l The data are derived from the evaluations or test results achieved with similar products
EC50 72h - Algae [1]	> 100 mg/l The data are derived from the evaluations or test results achieved with similar products

Dec-1-ene, dimers, hydrogenated (68649-11-6)	
LC50 - Fish [1]	> 1000 mg/l
EC50 - Crustacea [1]	> 1000 mg/l (48h, Daphnia magna)
EC50 72h - Algae [1]	> 1000 mg/l (72h, Scenedesmus capricornutum)
NOEC chronic crustacea	125 mg/l (21d, Daphnia magna)

reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)	
LC50 - Fish [1]	> 74 mg/l Brachydanio rerio (zebra-fish) - (OECD 203 method)
EC50 - Crustacea [1]	> 100 mg/l Daphnia magna (Water flea) - (OECD 202 method)
EC50 72h - Algae [1]	> 3 mg/l Desmodesmus subspicatus - (OECD 201 method)
NOEC (acute)	≥ 3 mg/l (Desmodesmus subspicatus, 72h) (OECD 201 method)

Phosphonic acid, dibutyl ester, reaction products with 2-(octylthio)- ethanol	
LC50 - Fish [1]	1,5 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	0,09 mg/l (Daphnia magna, 48h, OECD 202)

Kroon-Oil SP Matic 2094

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Phosphonic acid, dibutyl ester, reaction products with 2-(octylthio)- ethanol	
ErC50 algae	0,31 mg/l (Pseudokirchneriella subcapitata, 72h)
NOEC (chronic)	0,14 mg/l Test organisms (species): Duration: '21 d'
NOEC chronic algae	0,14 mg/l (Daphnia, 21d)
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LC50 - Fish [1]	> 100 mg/l (Pimephales promelas, 96h) (OECD 203 method)
EC50 - Crustacea [1]	> 10000 mg/l (Gammarus pulex, 48h) (OECD 202 method)
EC50 72h - Algae [1]	> 100 mg/l
NOEC (acute)	≥ 100 mg/l (Pseudokirchnerella subcapitata, 72h) (OECD 201 method)
NOEC chronic crustacea	10 mg/l (Daphnia magna, 21d) (OECD 211 method)
4,4'-thiodiethylene hydrogen -2-octadecenylsuccinate (93882-40-7)	
EC50 - Other aquatic organisms [1]	9,5 mg/l
ErC50 algae	100 mg/l
Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)	
LC50 - Fish [1]	> 100 mg/l 96h
EC50 - Crustacea [1]	> 10000 mg/l
EC50 72h - Algae [1]	≥ 100 mg/l
NOEC chronic crustacea	10 mg/l 21d
Reaction products of fatty acids, C14-C18 (branched and linear) and C18 (unsaturated) with tetraethylenepentamine (linear, branched, cyclic)	
LC50 - Fish [1]	> 1000 mg/l (4d, Pimephales promelas)
EC50 - Crustacea [1]	> 1000 mg/l (2d, Daphnia magna (Water flea))
EC50 96h - Algae [1]	> 94 mg/l (4d, Selenastrum capricornutum)
NOEC chronic crustacea	32 mg/l
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)	
LC50 - Fish [1]	> 100 mg/l (Pimephales promelas, 96h) (OECD 203 method)
LC50 - Other aquatic organisms [1]	> 10000 mg/l (Gammarus pulex, 48h) (OECD 202 method)
NOEC (acute)	≥ 100 mg/l (Pseudokirchnerella subcapitata, 72h) (OECD 201 method)
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)	
LC50 - Fish [1]	> 100 mg/l
EC50 - Crustacea [1]	> 10000 mg/l
NOEC (acute)	≥ 100 mg/l (Pseudokirchnerella subcapitata, 72h) (OECD 211 method)
NOEC chronic fish	> 1000 mg/l
NOEC chronic crustacea	> 10 mg/l (Daphnia magna, 21d) (OECD 211 method)
NOEC chronic algae	≥ 100 mg/l

12.2. Persistence and degradability

Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)	
Persistence and degradability	Potentially biodegradable.

Kroon-Oil SP Matic 2094

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)	
Persistence and degradability	Not readily biodegradable.
Phosphonic acid, dibutyl ester, reaction products with 2-(octylthio)- ethanol	
Biodegradation	52,9 % (60d, OECD 301 B)
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
Biodegradation	31 % (28d) (OECD 301F method)
4,4'-thiodiethylene hydrogen -2-octadecenylsuccinate (93882-40-7)	
Persistence and degradability	Not readily biodegradable.
Oil Soluble Polyalkylene Glycol	
Persistence and degradability	Not readily biodegradable.
Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)	
Persistence and degradability	Not established.
Biodegradation	31 % (OECD 301F method)
Reaction products of fatty acids, C14-C18 (branched and linear) and C18 (unsaturated) with tetraethylenepentamine (linear, branched, cyclic)	
Biodegradation	4,5 % (28d, (OECD 301B method))
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)	
Biodegradation	31 % (28d) (OECD 301F method)
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)	
Persistence and degradability	Not readily biodegradable.
Biodegradation	31 % (28d) (OECD 301F method)
12.3. Bioaccumulative potential	
Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)	
Partition coefficient n-octanol/water (Log Pow)	> 3
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)	
Bioconcentration factor (BCF REACH)	260 (Oncorhynchus mykiss, 35d) (OECD 305 method)
Partition coefficient n-octanol/water (Log Pow)	9,2
4,4'-thiodiethylene hydrogen -2-octadecenylsuccinate (93882-40-7)	
Bioaccumulative potential	Bioaccumulative potential.
Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)	
Partition coefficient n-octanol/water (Log Pow)	> 6
Bioaccumulative potential	Not established.
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)	
Partition coefficient n-octanol/water (Log Pow)	> 6
Bioaccumulative potential	Bioaccumulative potential.

Kroon-Oil SP Matic 2094

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.4. Mobility in soil

Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)

Ecology - soil	Insoluble in water.
----------------	---------------------

reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)

Ecology - soil	Product adsorbs little onto the soil.
----------------	---------------------------------------

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)

Mobility in soil	Product adsorbs onto the soil
------------------	-------------------------------

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)

Ecology - soil	Insoluble in water.
----------------	---------------------

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.
European List of Waste (LoW) code	: 13 02 06* - synthetic engine, gear and lubricating oils

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.2. UN proper shipping name				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available				

Kroon-Oil SP Matic 2094

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

14.6. Special precautions for user

Overland transport

Not regulated

Transport by sea

Not regulated

Air transport

Not regulated

Inland waterway transport

Not regulated

Rail transport

Not regulated

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)

Reference code	Applicable on
3.	Dec-1-ene, dimers, hydrogenated ; reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate ; Phosphonic acid, dibutyl ester, reaction products with 2-(octylthio)- ethanol ; 4,4'-thiodiethylene hydrogen -2-octadeceny succinate
3(b)	Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based ; Distillates (petroleum), hydrotreated heavy paraffinic ; Dec-1-ene, dimers, hydrogenated ; Phosphonic acid, dibutyl ester, reaction products with 2-(octylthio)- ethanol ; 4,4'-thiodiethylene hydrogen -2-octadeceny succinate
3(c)	reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate ; Phosphonic acid, dibutyl ester, reaction products with 2-(octylthio)- ethanol ; 4,4'-thiodiethylene hydrogen -2-octadeceny succinate

REACH Annex XIV (Authorisation List)

Contains no REACH Annex XIV substances

REACH Candidate List (SVHC)

Contains no substance on the REACH candidate list

PIC Regulation (Prior Informed Consent)

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

POP Regulation (Persistent Organic Pollutants)

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

Ozone Regulation (1005/2009)

Contains no substance subject to REGULATION (EU) No 1005/2009 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 September 2009 on substances that deplete the ozone layer.

VOC Directive (2004/42)

VOC content : 0 %

Kroon-Oil SP Matic 2094

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Biocide Regulation (528/2012)

Child-resistant fastening : Applicable
Tactile warning : Applicable

Explosives Precursors Regulation (2019/1148)

Contains no substance subject to Regulation (EU) 2019/1148 of the European Parliament and of the Council of 20 June 2019 on the marketing and use of explosives precursors.

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on drug precursors)

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

For the following substances of this mixture a chemical safety assessment has been carried out:

Distillates (petroleum), solvent-dewaxed light paraffinic

SECTION 16: Other information

Indication of changes			
Section	Changed item	Change	Comments
	Revision date	Modified	
	Supersedes	Modified	
1.2	Use of the substance/mixture	Added	
1.2	Function or use category	Added	
1.2	Intended for general public	Added	
2.1	Intended for general public	Added	
2.2	Precautionary statements (CLP)	Modified	

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association

Kroon-Oil SP Matic 2094

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Full text of H- and EUH-statements:	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Aquatic Chronic 4	Hazardous to the aquatic environment – Chronic Hazard, Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
EUH208	Contains 4,4'-thiodiethylene hydrogen -2-octadecenylsuccinate. May produce an allergic reaction.
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.

Kroon-Oil SP Matic 2094

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.