



Kroon-Oil Racing Chainlube

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 20-9-2018 Revision date: 17-10-2022 Supersedes version of: 16-6-2021 Version: 1.5

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : Kroon-Oil Racing Chainlube
UFI : W600-K0TC-V00V-0HG3
Product code : 06.20.35
Type of product : Lubricants
Vaporizer : Aerosol
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public
Main use category : Industrial use, Professional use, Consumer use
Use of the substance/mixture : Chain lubricant
Function or use category : Lubricant

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Kroon Oil BV B.V.
Dollegoorweg, 15
NL- 7602 EC Almelo
Netherlands
T 0031 (0)546 81 81 65
vib@kroon-oil.nl

1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
United Kingdom	National Poisons Information Service (Cardiff Centre) University Hospital Llandough	Penlan Road CF64 2XX Llandough	0344 892 0111	Only for healthcare professionals

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1 H222;H229
Skin corrosion/irritation, Category 2 H315
Specific target organ toxicity – Single exposure, Category 3, Narcosis H336
Aspiration hazard, Category 1 H304
Hazardous to the aquatic environment – Chronic Hazard, Category 2 H411
Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. May cause drowsiness or dizziness. Causes skin irritation. May be fatal if swallowed and enters airways. Toxic to aquatic life with long lasting effects.

Kroon-Oil Racing Chainlube

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

Contains

Hazard statements (CLP)

Precautionary statements (CLP)

- : Danger
- : Pentane, Hydrocarbons, C6, isoalkanes, <5% n-hexane
- : H222 - Extremely flammable aerosol.
H229 - Pressurised container: May burst if heated.
H315 - Causes skin irritation.
H336 - May cause drowsiness or dizziness.
H411 - Toxic to aquatic life with long lasting effects.
- : P101 - If medical advice is needed, have product container or label at hand.
P102 - Keep out of reach of children.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 - Do not spray on an open flame or other ignition source.
P251 - Do not pierce or burn, even after use.
P271 - Use only outdoors or in a well-ventilated area.
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

Component	
Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Distillates (petroleum), hydrotreated light paraffinic (Note L)	CAS-No.: 64742-55-8 EC-No.: 265-158-7 EC Index-No.: 649-468-00-3 REACH-no: 01-2119487077-29	25 – 50	Asp. Tox. 1, H304

Kroon-Oil Racing Chainlube

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Propane substance with a Community workplace exposure limit (Note U)	CAS-No.: 74-98-6 EC-No.: 200-827-9 EC Index-No.: 601-003-00-5 REACH-no: 01-2119486944-21	10 – 25	Flam. Gas 1A, H220 Press. Gas (Comp.), H280
Pentane substance with national workplace exposure limit(s) (GB, IE); substance with a Community workplace exposure limit	CAS-No.: 109-66-0 EC-No.: 203-692-4 EC Index-No.: 601-006-00-1 REACH-no: 01-2119459286-30	10 – 25	Flam. Liq. 1, H224 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 EUH066
Hydrocarbons, C6, isoalkanes, <5% n-hexane	EC-No.: 931-254-9	10 – 25	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Butane substance with national workplace exposure limit(s) (GB, IE) (Note K)	CAS-No.: 106-97-8 EC-No.: 203-448-7 EC Index-No.: 601-004-00-0 REACH-no: 01-2119474691-32	2,5 – 10	Flam. Gas 1A, H220 Press. Gas (Comp.), H280
isobutane substance with national workplace exposure limit(s) (IE) (Note K)	CAS-No.: 75-28-5 EC-No.: 200-857-2 REACH-no: 01-2119485395-27	1 – 2,5	Flam. Gas 1A, H220 Press. Gas (Comp.), H280

Note K : The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w 1,3-butadiene (EINECS No 203-450-8). If the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-)P210-P403 should apply. This note applies only to certain complex oil-derived substances in Part 3.

Note L : The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346 'Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions — Dimethyl sulphoxide extraction refractive index method', Institute of Petroleum, London. This note applies only to certain complex oil-derived substances in Part 3.

Note U (Table 3): When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case.

Product subject to CLP Article 1.1.3.7. The disclosure rules of the components is modified in this case.

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Call a physician immediately.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Irritation. Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after ingestion	: Risk of lung oedema.

Kroon-Oil Racing Chainlube

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol. Combustible liquid.
Explosion hazard : Pressurised container: May burst if heated.
Hazardous decomposition products in case of fire : Toxic fumes may be released. Incomplete combustion releases dangerous carbon monoxide, carbon dioxide and other toxic gases.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.
Methods for cleaning up : Mechanically recover the product.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. Wear personal protective equipment.
Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

Kroon-Oil Racing Chainlube

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.
Storage temperature	: < 40 °C

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Kroon-Oil Racing Chainlube	
EU - Indicative Occupational Exposure Limit (IOEL)	
Exposure limits/standards for materials that can be formed when handling this product. When mists/aerosols can occur the following is recommended	5 mg/m ³ - ACGIH TLV (inhalable fraction).
Propane (74-98-6)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA [ppm]	1000 ppm
Ireland - Occupational Exposure Limits	
Local name	Aliphatic hydrocarbon gases Alkanes (C1-C3): Propane
Remark	Asphx. (Gaseous chemical substances which may not produce significant physiological effects in the exposed employee, but when present in high concentrations will act as simple asphyxiants)
Regulatory reference	Chemical Agents Code of Practice 2021
Pentane (109-66-0)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Pentane
IOEL TWA	3000 mg/m ³ 3000 mg/m ³
IOEL TWA [ppm]	1000 ppm
Regulatory reference	COMMISSION DIRECTIVE 2006/15/EC COMMISSION DIRECTIVE 2006/15/EC
Ireland - Occupational Exposure Limits	
Local name	Pentane
OEL TWA [1]	3000 mg/m ³
OEL TWA [2]	1000 ppm
Remark	IOELV (Indicative Occupational Exposure Limit Values)
Regulatory reference	Chemical Agents Code of Practice 2021
United Kingdom - Occupational Exposure Limits	
Local name	Pentane
WEL TWA (OEL TWA) [1]	1800 mg/m ³

Kroon-Oil Racing Chainlube

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Pentane (109-66-0)	
WEL TWA (OEL TWA) [2]	600 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Butane (106-97-8)	
Ireland - Occupational Exposure Limits	
Local name	Butane, all isomers: Butane
OEL STEL [ppm]	1000 ppm
Regulatory reference	Chemical Agents Code of Practice 2021
United Kingdom - Occupational Exposure Limits	
Local name	Butane
WEL TWA (OEL TWA) [1]	1450 mg/m ³
WEL TWA (OEL TWA) [2]	600 ppm
WEL STEL (OEL STEL)	1810 mg/m ³
WEL STEL (OEL STEL) [ppm]	750 ppm
Remark	Carc (Capable of causing cancer and/or heritable genetic damage, only applies if Butane contains more than 0.1% of buta-1,3-diene)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
isobutane (75-28-5)	
Ireland - Occupational Exposure Limits	
Local name	Butane, all isomers: Isobutane
OEL STEL [ppm]	1000 ppm
Regulatory reference	Chemical Agents Code of Practice 2021

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



Kroon-Oil Racing Chainlube

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Colourless to Amber.
Appearance	: Aerosol.
Odour	: characteristic.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: -44 °C
Flammability	: Extremely flammable aerosol.
Explosive properties	: Pressurised container: May burst if heated.
Explosive limits	: Not available
Lower explosion limit	: 1,1 vol %
Upper explosion limit	: 10,9 vol %
Flash point	: -97 °C
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: < 20,5 mm ² /s (40°C)
Solubility	: Water: Insoluble / Slightly miscible
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: 8300 hPa
Vapour pressure at 50°C	: Not available
Density	: 0,681 g/cm ³
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

% of flammable ingredients	: 87,49999999999995
Critical temperature	: 200 °C

9.2.2. Other safety characteristics

VOC content	: 384,3 g/l
-------------	-------------

Kroon-Oil Racing Chainlube

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use. Reacts violently with (strong) oxidizers.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Pentane (109-66-0)	
LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), Guideline: EU Method B.1 (Acute Toxicity (Oral))
LC50 Inhalation - Rat	> 25,3 mg/l Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)

Hydrocarbons, C6, isoalkanes, <5% n-hexane	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 3000 mg/kg
LC50 Inhalation - Rat (Dust/Mist)	> 10000 mg/l/4h

Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 Inhalation - Rat (Dust/Mist)	5,53 mg/l/4h

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Not classified
Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
STOT-single exposure : May cause drowsiness or dizziness.

Pentane (109-66-0)	
STOT-single exposure	May cause drowsiness or dizziness.

Kroon-Oil Racing Chainlube

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hydrocarbons, C6, isoalkanes, <5% n-hexane	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
Pentane (109-66-0)	
NOAEC (inhalation, rat, vapour, 90 days)	30 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study), Guideline: other.: Guideline: EPA OTS 798.2450 (90-Day Inhalation Toxicity), Guideline: other.: Guideline: other:
Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Aspiration hazard	: May be fatal if swallowed and enters airways.
Kroon-Oil Racing Chainlube	
Vaporizer	Aerosol
Viscosity, kinematic	< 20,5 mm ² /s (40°C)
Pentane (109-66-0)	
Viscosity, kinematic	0,356 mm ² /s
Hydrocarbons, C6, isoalkanes, <5% n-hexane	
Viscosity, kinematic	0,46 mm ² /s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm ² /s)'
Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)	
Viscosity, kinematic	< 20,5 mm ² /s
Aliphatic, alicyclic or aromatic hydrocarbon	Yes
11.2. Information on other hazards	
No additional information available	
SECTION 12: Ecological information	
12.1. Toxicity	
Ecology - general	: Toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Toxic to aquatic life with long lasting effects.
Pentane (109-66-0)	
LC50 - Fish [1]	4,26 mg/l 96h
EC50 - Crustacea [1]	2,7 mg/l 48h
Hydrocarbons, C6, isoalkanes, <5% n-hexane	
LC50 - Fish [1]	> 2 mg/l
Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)	
LC50 - Fish [1]	> 100 mg/l 96h
EC50 - Crustacea [1]	> 10000 mg/l
EC50 72h - Algae [1]	≥ 100 mg/l

Kroon-Oil Racing Chainlube

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)

NOEC chronic crustacea	10 mg/l 21d
------------------------	-------------

12.2. Persistence and degradability

Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)

Persistence and degradability	Not established.
Biodegradation	31 % (OECD 301F method)

12.3. Bioaccumulative potential

Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)

Partition coefficient n-octanol/water (Log Pow)	> 6
Bioaccumulative potential	Not established.

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
HP Code : HP5 - "Specific Target Organ Toxicity (STOT)/Aspiration Toxicity:" waste which can cause specific target organ toxicity either from a single or repeated exposure, or which cause acute toxic effects following aspiration.
HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

SECTION 14: Transport information






In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 1950	UN 1950	UN 1950	UN 1950	UN 1950
14.2. UN proper shipping name				
AEROSOLS (Hydrocarbons, C6, isoalkanes, <5% n-hexane)	AEROSOLS (Hydrocarbons, C6, isoalkanes, <5% n-hexane)	Aerosols, flammable (Hydrocarbons, C6, isoalkanes, <5% n-hexane)	AEROSOLS (Hydrocarbons, C6, isoalkanes, <5% n-hexane)	AEROSOLS (Hydrocarbons, C6, isoalkanes, <5% n-hexane)

Kroon-Oil Racing Chainlube

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
Transport document description				
UN 1950 AEROSOLS (Hydrocarbons, C6, isoalkanes, <5% n-hexane), 2.1, (D), ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS (Hydrocarbons, C6, isoalkanes, <5% n-hexane), 2.1, MARINE POLLUTANT/ENVIRONME NTALLY HAZARDOUS	UN 1950 Aerosols, flammable (Hydrocarbons, C6, isoalkanes, <5% n- hexane), 2.1, ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS (Hydrocarbons, C6, isoalkanes, <5% n-hexane), 2.1, ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS (Hydrocarbons, C6, isoalkanes, <5% n-hexane), 2.1, ENVIRONMENTALLY HAZARDOUS
14.3. Transport hazard class(es)				
2.1	2.1	2.1	2.1	2.1
				
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
No supplementary information available				

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: 5F
Special provisions (ADR)	: 190, 327, 344, 625
Limited quantities (ADR)	: 1I
Excepted quantities (ADR)	: E0
Packing instructions (ADR)	: P207
Special packing provisions (ADR)	: PP87, RR6, L2
Mixed packing provisions (ADR)	: MP9
Transport category (ADR)	: 2
Special provisions for carriage - Packages (ADR)	: V14
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV9, CV12
Special provisions for carriage - Operation (ADR)	: S2
Tunnel restriction code (ADR)	: D

Transport by sea

Special provisions (IMDG)	: 63, 190, 277, 327, 344, 381, 959
Limited quantities (IMDG)	: SP277
Excepted quantities (IMDG)	: E0
Packing instructions (IMDG)	: P207, LP200
Special packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D
EmS-No. (Spillage)	: S-U
Stowage category (IMDG)	: None
Stowage and handling (IMDG)	: SW1, SW22
Segregation (IMDG)	: SG69

Air transport

PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG

Kroon-Oil Racing Chainlube

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provisions (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L

Inland waterway transport

Classification code (ADN)	: 5F
Special provisions (ADN)	: 190, 327, 344, 625
Limited quantities (ADN)	: 1 L
Excepted quantities (ADN)	: E0
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01, VE04
Number of blue cones/lights (ADN)	: 1

Rail transport

Classification code (RID)	: 5F
Special provisions (RID)	: 190, 327, 344, 625
Limited quantities (RID)	: 1L
Excepted quantities (RID)	: E0
Packing instructions (RID)	: P207, LP200
Special packing provisions (RID)	: PP87, RR6, L2
Mixed packing provisions (RID)	: MP9
Transport category (RID)	: 2
Special provisions for carriage – Packages (RID)	: W14
Special provisions for carriage - Loading, unloading and handling (RID)	: CW9, CW12
Colis express (express parcels) (RID)	: CE2
Hazard identification number (RID)	: 23

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

VOC Directive (2004/42)

VOC content : 384,3 g/l

Kroon-Oil Racing Chainlube

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Biocide Regulation (528/2012)

Child-resistant fastening : Not applicable
Tactile warning : Not applicable

Seveso Directive (Disaster Risk Reduction)

Seveso III Part I (Categories of dangerous substances)	Qualifying quantity (tonnes)	
	Lower-tier	Upper-tier
P3a FLAMMABLE AEROSOLS 'Flammable' aerosols Category 1 or 2, containing flammable gases Category 1 or 2 or flammable liquids Category 1	150	500
E2 Hazardous to the Aquatic Environment in Category Chronic 2	200	500

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes			
Section	Changed item	Change	Comments
	Limited quantities (IMDG)	Added	
	Excepted quantities (IMDG)	Added	
	Type of product	Added	
1.2	Function or use category	Added	
1.2	Use of the substance/mixture	Added	
4.1	First-aid measures general	Modified	
4.2	Symptoms/effects after ingestion	Modified	
4.2	Symptoms/effects	Modified	
5.2	Hazardous decomposition products in case of fire	Modified	
5.2	Fire hazard	Modified	
10.3	Possibility of hazardous reactions	Modified	
16	Abbreviations and acronyms	Modified	

Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate

Kroon-Oil Racing Chainlube

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Full text of H- and EUH-statements:	
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
EUH066	Repeated exposure may cause skin dryness or cracking.
Flam. Gas 1A	Flammable gases, Category 1A
Flam. Liq. 1	Flammable liquids, Category 1

Kroon-Oil Racing Chainlube

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
Flam. Liq. 2	Flammable liquids, Category 2
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H224	Extremely flammable liquid and vapour.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
Press. Gas (Comp.)	Gases under pressure : Compressed gas
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.