

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 Issue date: 10-10-2018 Revision date: 29-7-2020 Supersedes: 4-11-2019 Version: 2.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	: Mixture
Trade name	: Polish Wax
Product code	: 06.20.81
Type of product	: Detergent
Vaporizer	: Aerosol
Product group	: Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public Main use category Use of the substance/mixture

: Industrial use,Professional use,Consumer use : Cleaner

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Kroon Oil BV Dollegoorweg 15 7602 EC Almelo - Netherlands T 0031 (0)546 81 81 65 vib@kroon-oil.nl

1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
United Kingdom	National Poisons Information Service (Cardiff Centre) Gwenwyn Ward, Llandough Hospital	Penarth CF64 2XX Cardiff	0344 892 0111	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1 Skin sensitisation, Category 1 Full text of H statements : see section 16 H222;H229 H317

Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. May cause an allergic skin reaction.

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

2.2. Label elements

Labelling according to Regulation (EC) No. 12	72/2008 [CLP]
Hazard pictograms (CLP)	GHS02 GHS07
Signal word (CLP)	: Danger
Hazardous ingredients	: 2-Methyl-2H-isothiazol-3-one
Hazard statements (CLP)	: H222 - Extremely flammable aerosol.
	H229 - Pressurised container: May burst if heated.
	H317 - May cause an allergic skin reaction.
Precautionary statements (CLP)	 P101 - If medical advice is needed, have product container or label at hand. P102 - Keep out of reach of children. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 - Do not spray on an open flame or other ignition source. P251 - Do not pierce or burn, even after use. P261 - Avoid breathing vapours, mist, spray. P280 - Wear protective gloves. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Butane substance with national workplace exposure limit(s) (GB, IE) (Note K)	(CAS-No.) 106-97-8 (EC-No.) 203-448-7 (EC Index-No.) 601-004-00-0 (REACH-no) 01-2119474691-32	10 – 25	Flam. Gas 1A, H220 Press. Gas (Comp.), H280
Propane substance with a Community workplace exposure limit substance with national workplace exposure limit(s) (IE) (Note U)	(CAS-No.) 74-98-6 (EC-No.) 200-827-9 (EC Index-No.) 601-003-00-5 (REACH-no) 01-2119486944-21	2,5 – 10	Flam. Gas 1A, H220 Press. Gas (Comp.), H280
isobutane substance with national workplace exposure limit(s) (IE) (Note K)	(CAS-No.) 75-28-5 (EC-No.) 200-857-2 (REACH-no) 01-2119485395-27	1 – 2,5	Flam. Gas 1A, H220 Press. Gas (Comp.), H280

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

2-Methyl-2H-isothiazol-3-one	(CAS-No.) 2682-20-4	≥ 0.0015-	Acute Tox. 3 (Oral), H301
	(EC-No.) 220-239-6 (EC Index-No.) 613-326-00-9	<0.025	Acute Tox. 3 (Dermal), H311 Acute Tox. 2 (Inhalation), H330
			Skin Corr. 1B, H314
			Skin Sens. 1A, H317 STOT SE 3, H335
			Aquatic Acute 1, H400
			Aquatic Chronic 2, H411

Note K : The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w 1,3butadiene (EINECS No 203-450-8). If the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-)P210-P403 (Table 3.1) or the S-phrases (2-)9-16 (Table 3.2) should apply. This note applies only to certain complex oil-derived substances in Part 3.

Note U (Table 3): When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case.

Full text of H-statements: see section 16

SECTION 4: First aid measures	
4.1. Description of first aid measures	
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.
4.2. Most important symptoms and effects	, both acute and delayed
Symptoms/effects Symptoms/effects after skin contact Symptoms/effects after ingestion	 Not expected to present a significant hazard under anticipated conditions of normal use. May cause an allergic skin reaction. May result in aspiration into the lungs, causing chemical pneumonia.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures	
5.1. Extinguishing media	
Suitable extinguishing media Unsuitable extinguishing media	Sand. Water spray. Dry powder. Foam. Carbon dioxide.Do not use a heavy water stream.
5.2. Special hazards arising from the subst	ance or mixture
Fire hazard Explosion hazard Hazardous decomposition products in case of fire	 May form flammable vapour-air mixture. Combustible liquid. Extremely flammable aerosol. Pressurised container: May burst if heated. Incomplete combustion releases dangerous carbon monoxide, carbon dioxide and other toxic gases.
5.3. Advice for firefighters	
Firefighting instructions Protection during firefighting	 Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment. Do not enter fire area without proper protective equipment, including respiratory protection. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 6: Accidental release measures		
6.1. Personal precautions, protective equip	ment and emergency procedures	
General measures	: Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking.	
6.1.1. For non-emergency personnel		
Emergency procedures	: Ventilate spillage area. Evacuate unnecessary personnel. No open flames, no sparks, and no smoking. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.	
6.1.2. For emergency responders		
Protective equipment	Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".	
Emergency procedures	: Ventilate area.	
6.2. Environmental precautions		
Avoid release to the environment. Prevent entry to s	ewers and public waters. Notify authorities if liquid enters sewers or public waters.	
6.3. Methods and material for containment	and cleaning up	
Methods for cleaning up	: Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials. Mechanically recover the product.	
Other information	: Dispose of materials or solid residues at an authorized site.	
6.4. Reference to other sections		
See Heading 8. Exposure controls and personal pro	tection. For further information refer to section 13.	
SECTION 7: Handling and storage		

dditional hazards when processed Precautions for safe handling lygiene measures	 Handle empty containers with care because residual vapours are flammable. Ensure good ventilation of the work station. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. No open flames. No smoking. Use only non-sparking tools. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. Wear personal protective equipment. Wash hands, forearms and face thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do
	not eat, drink or smoke when using this product. Always wash hands after handling the product.
7.2. Conditions for safe storage, inclu	ding any incompatibilities
echnical measures	: Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof Avoid the build-up of electrostatic charge equipment.
torage conditions	: Keep only in the original container in a cool, well ventilated place away from : Ignition sources. Keep in fireproof place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a well-ventilated place. Keep cool.
ncompatible materials	: Sources of ignition. Direct sunlight. Heat sources.
torage temperature	: <40 °C

No additional information available

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Polish Wax	
EU - Occupational Exposure Limits	
Exposure limits/standards for materials that can be formed when handling this product. When mists/aerosols can occur the following is recommended	5 mg/m ³ - ACGIH TLV (inhalable fraction).

Butane (106-97-8)		
Ireland - Occupational Exposure Limits		
Local name	Butane, all isomers: Butane	
OEL (15 min ref) (ppm)	1000 ppm	
Regulatory reference	Chemical Agents Code of Practice 2020	
United Kingdom - Occupational Exposure Limits		
Local name	Butane	
WEL TWA (mg/m³)	1450 mg/m³	
WEL TWA (ppm)	600 ppm	
WEL STEL (mg/m ³)	1810 mg/m³	
WEL STEL (ppm)	750 ppm	
Remark (WEL)	Carc (Capable of causing cancer and/or heritable genetic damage, only applies if Butane contains more than 0.1% of buta-1,3-diene)	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	

Propane (74-98-6)		
EU - Occupational Exposure Limits		
IOELV TWA (ppm)	1000 ppm	
Ireland - Occupational Exposure Limits		
Local name	Aliphatic hydrocarbon gases Alkanes (C1-C3): Propane	
Notes (IE)	Asphx. (Gaseous chemical substances which may not produce significant physiological effects in the exposed employee, but when present in high concentrations will act as simple asphyxiants)	
Regulatory reference	Chemical Agents Code of Practice 2020	

isobutane (75-28-5)		
Ireland - Occupational Exposure Limits		
Local name	Butane, all isomers: Isobutane	
OEL (15 min ref) (ppm)	1000 ppm	
Regulatory reference	Chemical Agents Code of Practice 2020	

8.2. Exposure controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Personal protective equipment:

Avoid all unnecessary exposure.

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Materials for protective clothing:			
Wear suitable protective clothing			
Condition	Material	Standard	
		EN 13034	

Hand protection:					
Wear protective gloves.					
Туре	Material	Permeation	Thickness (mm)	Penetration	Standard
Reusable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	≥ 0.35		EN ISO 374

Eye protection:			
Chemical goggles or safety glasses	. Safety glasses		
Туре	Use	Characteristics	Standard
Safety glasses	Droplet	clear	EN 166

Skin and body protection: Wear suitable protective clothing

Respiratory protection:

In the event of insufficient ventilation:

Device	Filter type	Condition	Standard
	Type AX - Low-boiling (<65 °C) organic compounds, Type P2		
	АВЕК, Туре Р2		

Personal protective equipment symbol(s):



Environmental exposure controls: Avoid release to the environment.

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical	properties	
9.1. Information on basic physical and	chemical properties	
Physical state	: Liquid	
Appearance	: Aerosol.	
Colour	: No data available	
Odour	: characteristic.	
Odour threshold	: No data available	
pH	: No data available	
Relative evaporation rate (butylacetate=1)	: No data available	
Melting point	: Not applicable	
Freezing point	No data available	
Boiling point	: -44,5 °C	

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Flash point	: -97 °C
Critical temperature	: 236 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Extremely flammable aerosol.
Vapour pressure	: 2100 hPa (20°C)
Relative vapour density at 20 °C	No data available
Relative density	: No data available
Density	: 0,846 g/cm³ (20°C)
Solubility	: Water: Insoluble / Slightly miscible
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: Pressurised container: May burst if heated.
Oxidising properties	: No data available
Lower explosive limit (LEL)	: 0,7 vol %
Upper explosive limit (UEL)	: 10,9 vol %

9.2. Other information

: 241,1 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

VOC content

Extremely flammable aerosol. Pressurised container: May burst if heated.

10.2. Chemical stability

Highly flammable liquid and vapour. May form flammable/explosive vapour-air mixture.

10.3. Possibility of hazardous reactions

Not established. Reacts violently with (strong) oxidizers.

10.4. Conditions to avoid

Direct sunlight. Open flame. High temperature. Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide. May release flammable gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) Acute toxicity (dermal) Acute toxicity (inhalation)	: Not classified : Not classified : Not classified
Skin corrosion/irritation Serious eye damage/irritation Respiratory or skin sensitisation Germ cell mutagenicity Carcinogenicity	 Not classified Not classified May cause an allergic skin reaction. Not classified Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

STOT-repeated exposure :	Not classified
Aspiration hazard :	Not classified
Polish Wax	
Vaporizer	Aerosol

SECTION 12: Ecological information	
12.1. Toxicity	
Ecology - general Hazardous to the aquatic environment, short-term (acute) Hazardous to the aquatic environment, long-term (chronic)	 The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment. Not classified Not classified
12.2. Persistence and degradability	
No additional information available	
12.3. Bioaccumulative potential	
No additional information available	
12.4. Mobility in soil	
No additional information available	
12.5. Results of PBT and vPvB assessment	
No additional information available	
12.6. Other adverse effects	
No additional information available	
SECTION 13: Disposal considerations	

13.1. Waste treatment methods

Waste treatment methods Product/Packaging disposal recommendations

Additional information Ecology - waste materials European List of Waste (LoW) code

HP Code

: Dispose of contents/container in accordance with licensed collector's sorting instructions. Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to a hazardous or special waste collection point. Handle empty containers with care because residual vapours are flammable. Avoid release to the environment. 08 01 11* - waste paint and varnish containing organic solvents or other dangerous substances 15 01 04 - metallic packaging : HP3 - "Flammable:" - flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and \leq 75 °C; - flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air; - flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction;

— flammable gaseous waste: gaseous waste which is flammable in air at 20 $^\circ\text{C}$ and a standard pressure of 101.3 kPa;

— water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities;

— other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste.

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

n accordance with ADR / RID) / IMDG / IATA / ADN			
ADR	IMDG	ΙΑΤΑ	ADN	RID
14.1. UN number				1
UN 1950	UN 1950	UN 1950	UN 1950	UN 1950
14.2. UN proper shipping	g name			1
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS
Transport document descr	iption			
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1	UN 1950 AEROSOLS, 2.1	UN 1950 AEROSOLS, 2.1
14.3. Transport hazard c	class(es)			<u> </u>
2.1	2.1	2.1	2.1	2.1
2				
14.4. Packing group	· ·			
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental haz	ards			•
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No	Dangerous for the environment : No	Dangerous for the environment : No

14.6. Special precautions for user

Overland transport

Classification code (ADR)	:	5F
Special provisions (ADR)	:	190, 327, 344, 625
Limited quantities (ADR)	:	11
Excepted quantities (ADR)	:	E0
Packing instructions (ADR)	:	P207
Special packing provisions (ADR)	:	PP87, RR6, L2
Mixed packing provisions (ADR)	:	MP9
Transport category (ADR)	:	2
Special provisions for carriage - Packages (ADR)	:	V14
Special provisions for carriage - Loading, unloading	:	CV9, CV12
and handling (ADR)		
Special provisions for carriage - Operation (ADR)	:	S2
Tunnel restriction code (ADR)	:	D
Transport by sea		
Special provisions (IMDG)	:	63, 190, 277, 327, 344, 381, 959
Packing instructions (IMDG)	:	P207, LP200
Special packing provisions (IMDG)	:	PP87, L2
EmS-No. (Fire)	:	F-D
EmS-No. (Spillage)	:	S-U
Stowage category (IMDG)	:	None
Stowage and handling (IMDG)	:	SW1, SW22
Segregation (IMDG)	:	SG69
Air transport		
PCA Excepted quantities (IATA)	:	E0
PCA Limited quantities (IATA)	:	Y203
PCA limited quantity max net quantity (IATA)	:	30kgG
,		-

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

PCA packing instructions (IATA)	:	203
PCA max net quantity (IATA)	:	75kg
CAO packing instructions (IATA)	:	203
CAO max net quantity (IATA)	:	150kg
Special provisions (IATA)	:	A145, A167, A802
ERG code (IATA)	:	10L
Inland waterway transport		
Classification code (ADN)	:	5F
Special provisions (ADN)	:	190, 327, 344, 625
Limited quantities (ADN)	:	1 L
Excepted quantities (ADN)	:	E0
Equipment required (ADN)	:	PP, EX, A
Ventilation (ADN)	:	VE01, VE04
Number of blue cones/lights (ADN)	:	1
Rail transport		
Classification code (RID)	:	5F
Special provisions (RID)	:	190, 327, 344, 625
Limited quantities (RID)	:	1L
Excepted quantities (RID)	:	E0
Packing instructions (RID)	:	P207, LP200
Special packing provisions (RID)	:	PP87, RR6, L2
Mixed packing provisions (RID)	:	MP9
Transport category (RID)	:	2
Special provisions for carriage – Packages (RID)	:	W14
Special provisions for carriage - Loading, unloading	:	CW9, CW12
and handling (RID)		
Colis express (express parcels) (RID)	:	CE2
Hazard identification number (RID)	:	23

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

VOC content	:	241,1 g/l
Child-resistant fastening	:	Not applicable
Tactile warning	:	Not applicable

Detergent Regulation : Labelling of contents (648/2004/EC):		
Component	%	
aliphatic hydrocarbons	15-30%	
non-ionic surfactants	<5%	
METHYLISOTHIAZOLINONE		
perfumes		

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Directive 2012/18/EU (SEVESO III)

Seveso III Part I (Categories of dangerous substances)	Qualifying quantity (tonnes)	
	Lower-tier	Upper-tier
P3a FLAMMABLE AEROSOLS 'Flammable' aerosols Category 1 or 2, containing flammable gases Category 1 or 2 or flammable liquids Category 1	150	500

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes:			
Section	Changed item	Change	Comments
2.2	Precautionary statements (CLP)	Modified	
16	Abbreviations and acronyms	Modified	

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
IARC	International Agency for Research on Cancer
ΙΑΤΑ	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
РВТ	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
vPvB	Very Persistent and Very Bioaccumulative

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

BLV	Biological limit value
CAS-No.	Chemical Abstract Service number
EC-No.	European Community number
EN	European Standard
OEL	Occupational Exposure Limit
SDS	Safety Data Sheet
WGK	Water Hazard Class

Full text of H- and EUH-statements:		
Acute Tox. 2 (Inhalation)	Acute toxicity (inhal.), Category 2	
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3	
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3	
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1	
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2	
Flam. Gas 1A	Flammable gases, Category 1A	
Press. Gas (Comp.)	Gases under pressure : Compressed gas	
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B	
Skin Sens. 1A	Skin sensitisation, category 1A	
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation	
H220	Extremely flammable gas.	
H222	Extremely flammable aerosol.	
H229	Pressurised container: May burst if heated.	
H280	Contains gas under pressure; may explode if heated.	
H301	Toxic if swallowed.	
H311	Toxic in contact with skin.	
H314	Causes severe skin burns and eye damage.	
H317	May cause an allergic skin reaction.	
H330	Fatal if inhaled.	
H335	May cause respiratory irritation.	
H400	Very toxic to aquatic life.	
H411	Toxic to aquatic life with long lasting effects.	

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.