

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 Issue date: 20-9-2018 Revision date: 7-7-2020 Supersedes: 25-1-2019 Version: 1.2

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : White Vaseline
Product code : 07.10.31
Vaporizer : Aerosol
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public

Main use category : Industrial use, Professional use, Consumer use

Use of the substance/mixture : Lubricating agent

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Kroon Oil BV
Dollegoorweg 15
7602 EC Almelo - Netherlands
T 0031 (0)546 81 81 65
vib@kroon-oil.nl

1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
United Kingdom	National Poisons Information Service (Cardiff Centre) Gwenwyn Ward, Llandough Hospital	Penarth CF64 2XX Cardiff	0344 892 0111	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1 H222;H229
Skin corrosion/irritation, Category 2 H315
Serious eye damage/eye irritation, Category 2 H319
Specific target organ toxicity — Single exposure, Category 3, Narcosis H336
Aspiration hazard, Category 1 H304
Hazardous to the aquatic environment — Chronic Hazard, Category 3 H412

Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. May cause drowsiness or dizziness. Causes skin irritation. Causes serious eye irritation. May be fatal if swallowed and enters airways. Harmful to aquatic life with long lasting effects.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)





GHS02

GHS07

Signal word (CLP) : Danger

Hazardous ingredients : propan-2-ol; Hydrocarbons, C6, isoalkanes, <5% n-hexane; Pentane

Hazard statements (CLP) : H222 - Extremely flammable aerosol.

H229 - Pressurised container: May burst if heated.

H315 - Causes skin irritation.H319 - Causes serious eye irritation.H336 - May cause drowsiness or dizziness.

H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP) : P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use. P271 - Use only outdoors or in a well-ventilated area.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 $^{\circ}$ C/122 $^{\circ}$ F. P501 - Dispose of contents/container to hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
butane (containing < 0,1% butadiene (203-450-8)) substance with national workplace exposure limit(s) (GB, IE) (Note C)(Note U)	(CAS-No.) 106-97-8 (EC-No.) 203-448-7 (EC Index-No.) 601-004-00-0 (REACH-no) 01-2119474691-32	10 – 25	Flam. Gas 1A, H220 Press. Gas (Comp.), H280
propan-2-ol	(CAS-No.) 67-63-0 (EC-No.) 200-661-7 (EC Index-No.) 603-117-00-0 (REACH-no) 01-2119457558-25	10 – 25	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics, benzene <0,1%	(CAS-No.) (1174522-09-8) (EC-No.) 918-481-9 (REACH-no) 01-2119457273-39	10 – 25	Asp. Tox. 1, H304
Propane substance with a Community workplace exposure limit substance with national workplace exposure limit(s) (IE) (Note U)	(CAS-No.) 74-98-6 (EC-No.) 200-827-9 (EC Index-No.) 601-003-00-5 (REACH-no) 01-2119486944-21	10 – 25	Flam. Gas 1A, H220 Press. Gas (Comp.), H280

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Hydrocarbons, C6, isoalkanes, <5% n-hexane	(CAS-No.) 64742-49-0 (EC-No.) 931-254-9 (REACH-no) 01-2119484651-34	10 – 25	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Pentane	(CAS-No.) 109-66-0 (EC-No.) 203-692-4 (EC Index-No.) 601-006-00-1 (REACH-no) 01-2119459286-30	10 – 25	Flam. Liq. 1, H224 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

Comments : Benzene content : <0,1%

Note C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Note U (Table 3): When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case.

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: If you feel unwell, seek medical advice (show the label where possible). Call a physician

immediately.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get

medical advice/attention.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Do not induce vomiting. Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : Not expected to present a significant hazard under anticipated conditions of normal use.

May cause drowsiness or dizziness.

Symptoms/effects after skin contact : Irritation. Repeated exposure may cause skin dryness or cracking.

Symptoms/effects after eye contact : Eye irritation.

Symptoms/effects after ingestion : May result in aspiration into the lungs, causing chemical pneumonia. Risk of lung oedema.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Combustible liquid. Extremely flammable aerosol.

Explosion hazard : Pressurised container: May burst if heated.

Hazardous decomposition products in case of fire : Incomplete combustion releases dangerous carbon monoxide, carbon dioxide and other

toxic gases.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus. Complete protective clothing.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing

dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Mechanically recover the product.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. Wear personal

protective equipment.

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this

product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked

up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

Storage temperature : $< 40 \, ^{\circ}\text{C}$

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

butane (containing < 0,1% butadiene (203-450-8)) (106-97-8)		
Ireland - Occupational Exposure Limits		
Local name	Butane, all isomers: Butane	
OEL (15 min ref) (ppm)	1000 ppm	
Regulatory reference	Chemical Agents Code of Practice 2020	
United Kingdom - Occupational Exposure Limits		
Local name	Butane	
WEL TWA (mg/m³)	1450 mg/m³	
WEL TWA (ppm)	600 ppm	

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

WEL STEL (mg/m³)	1810 mg/m³
WEL STEL (ppm)	750 ppm
Remark (WEL)	Carc (Capable of causing cancer and/or heritable genetic damage, only applies if Butane contains more than 0.1% of buta-1,3-diene)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

propan-2-ol (67-63-0)		
United Kingdom - Occupational Exposure Limits		
Local name	Propan-2-ol	
WEL TWA (mg/m³)	999 mg/m³	
WEL TWA (ppm)	400 ppm	
WEL STEL (mg/m³)	1250 mg/m³	
WEL STEL (ppm)	500 ppm	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	

Propane (74-98-6)		
EU - Occupational Exposure Limits		
IOELV TWA (ppm) 1000 ppm		
Ireland - Occupational Exposure Limits		
Local name	Aliphatic hydrocarbon gases Alkanes (C1-C3): Propane	
Notes (IE)	Asphx. (Gaseous chemical substances which may not produce significant physiological effects in the exposed employee, but when present in high concentrations will act as simple asphyxiants)	
Regulatory reference	Chemical Agents Code of Practice 2020	

Pentane (109-66-0)		
EU - Occupational Exposure Limits		
Local name	Pentane	
IOELV TWA (mg/m³)	3000 mg/m³	
IOELV TWA (ppm)	1000 ppm	
Regulatory reference	COMMISSION DIRECTIVE 2006/15/EC	
United Kingdom - Occupational Exposure Limits		
Local name	Pentane	
WEL TWA (mg/m³)	1800 mg/m³	
WEL TWA (ppm)	600 ppm	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	

8.2. Exposure controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Hand protection:	
Protective gloves	

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Туре	Material	Permeation	Thickness (mm)	Penetration	Standard
Reusable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	≥ 0.35		EN ISO 374

Eye protection: Safety glasses Type Use Characteristics Standard Safety glasses Droplet clear EN 166

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):





Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid Appearance : Aerosol.

Colour : colourless to slightly yellow.

Odour : characteristic.

Odour threshold : No data available pH : No data available Relative evaporation rate (butylacetate=1) : No data available Melting point : Not applicable Freezing point : No data available

Boiling point : -44 °C
Flash point : -97 °C
Auto-ignition temperature : > 200 °C
Decomposition temperature : No data available

Flammability (solid, gas) : Extremely flammable aerosol.

Vapour pressure : 8300 hPa
Relative vapour density at 20 °C : No data available
Relative density : No data available
Density : 0,672 g/cm³

Solubility : Water: Insoluble / Slightly miscible

Partition coefficient n-octanol/water (Log Pow) : No data available
Viscosity, kinematic : < 20,5 mm²/s (40°C)
Viscosity, dynamic : No data available

Explosive properties : Pressurised container: May burst if heated.

Oxidising properties : No data available Lower explosive limit (LEL) : 0,7 vol % Upper explosive limit (UEL) : 12 vol %

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

9.2. Other information

VOC content : 571,2 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reacts violently with (strong) oxidizers.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified Acute toxicity (dermal) : Not classified Acute toxicity (inhalation) : Not classified

propan-2-ol (67-63-0)		
LD50 oral rat	5840 mg/kg (OECD 401 method)	
LD50 dermal rabbit	16,4 ml/kg (OECD 402 method)	
LC50 inhalation rat (ppm)	> 10000 ppm (ppm/6h, vapour) [OECD 403]	

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics, benzene <0,1% ((1174522-09-8))	
LD50 oral rat	> 5000 mg/kg (OESO 401)
LD50 dermal rabbit	> 3160 mg/kg (OESO 402)
LC50 inhalation rat (mg/l)	> 4,951 g/m³ (4h, OESO 403)

Hydrocarbons, C6, isoalkanes, <5% n-hexane (64742-49-0)	
LD50 oral rat	> 16750 mg/kg (OECD 401 method)
LD50 dermal rabbit	> 3350 mg/kg (OECD 402 method)
LC50 inhalation rat (mg/l)	259354 mg/m³ (OECD 403 method)

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitisation : Not classified Germ cell mutagenicity : Not classified Carcinogenicity : Not classified : Not classified

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Reproductive toxicity : Not classified

STOT-single exposure : May cause drowsiness or dizziness.

STOT-repeated exposure : Not classified

Aspiration hazard : May be fatal if swallowed and enters airways.

White Vaseline	
Vaporizer	Aerosol
Viscosity, kinematic	< 20,5 mm²/s (40°C)

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects.

: Not classified

Hazardous to the aquatic environment, short-term

(acute)

Hazardous to the aquatic environment, long-term

(chronic)

: Harmful to aquatic life with long lasting effects.

propan-2-ol (67-63-0)	
LC50 fish	9640 mg/l (Pimephales promelas, 96h) [OECD 203]
LC50 other aquatic organisms 1	> 10000 mg/l (Daphnia magna, 24h) [OECD 202]

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics, benzene <0,1% ((1174522-09-8))		
LC50 fish	> 1001 mg/l (OECD 203 method)	
EC50 Daphnia	> 1000 mg/l (OECD 202 method)	
EC50 72h algae (1)	W 1000 mg/l (OECD 201 method)	
ErC50 (algae) 1000 mg/l (Pseudokirhneriella subcapitata, EL0, 72h)		

Pentane (109-66-0)	
LC50 fish	4,26 mg/l 96h
EC50 Daphnia	2,7 mg/l 48h

12.2. Persistence and degradability

propan-2-ol (67-63-0)	
Biodegradation	53 % (5d)

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics, benzene <0,1% ((1174522-09-8))		
Persistence and degradability		Readily biodegradable.
	Biodegradation	80 % (28d)

12.3. Bioaccumulative potential

propan-2-ol (67-63-0)	
Partition coefficient n-octanol/water (Log Pow)	0,05

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics, benzene <0,1% ((1174522-09-8))

Partition coefficient n-octanol/water (Log Pow) 5,57 – 6,62

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods

: Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID	
14.1. UN number					
UN 1950	UN 1950	UN 1950	UN 1950	UN 1950	
14.2. UN proper shipping	g name				
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS	
Transport document descr	iption		1		
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1	UN 1950 AEROSOLS, 2.1	UN 1950 AEROSOLS, 2.1	
14.3. Transport hazard o	class(es)		I		
2.1	2.1	2.1	2.1	2.1	
2	2	2	2	2	
14.4. Packing group					
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable	
14.5. Environmental haz	ards				
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No	Dangerous for the environment : No	Dangerous for the environment : No	

14.6. Special precautions for user

Overland transport

Classification code (ADR) : 5F

Special provisions (ADR) : 190, 327, 344, 625

Limited quantities (ADR) : 1I Excepted quantities (ADR) : E0

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Packing instructions (ADR) : P207

Special packing provisions (ADR) : PR97 F

Special packing provisions (ADR) : PP87, RR6, L2

Mixed packing provisions (ADR): MP9Transport category (ADR): 2Special provisions for carriage - Packages (ADR): V14Special provisions for carriage - Loading, unloading: CV9, CV12

and handling (ADR)

Special provisions for carriage - Operation (ADR) : S2 Tunnel restriction code (ADR) : D

Transport by sea

Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959

Packing instructions (IMDG) : P207, LP200
Special packing provisions (IMDG) : PP87, L2
EmS-No. (Fire) : F-D
EmS-No. (Spillage) : S-U
Stowage category (IMDG) : None
Stowage and handling (IMDG) : SW1, SW22
Segregation (IMDG) : SG69

Air transport

PCA Excepted quantities (IATA) : E0
PCA Limited quantities (IATA) : Y203
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 203
PCA max net quantity (IATA) : 75kg
CAO packing instructions (IATA) : 203
CAO max net quantity (IATA) : 150kg

Special provisions (IATA) : A145, A167, A802

ERG code (IATA) : 10L

Inland waterway transport

Classification code (ADN) : 5F

Special provisions (ADN) : 190, 327, 344, 625

Limited quantities (ADN) : 1 L

Excepted quantities (ADN) : E0

Equipment required (ADN) : PP, EX, A

Ventilation (ADN) : VE01, VE04

Number of blue cones/lights (ADN) : 1

Rail transport

Classification code (RID) : 5F

Special provisions (RID) : 190, 327, 344, 625

Limited quantities (RID) : 1L

Excepted quantities (RID) : E0

Packing instructions (RID) : P207, LP200

Special packing provisions (RID) : PP87, RR6, L2

Mixed packing provisions (RID) : MP9

Transport category (RID) : 2

Special provisions for carriage – Packages (RID) : W14

Special provisions for carriage - Loading, unloading : CW9, CW12

and handling (RID)

Colis express (express parcels) (RID) : CE2
Hazard identification number (RID) : 23

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions Contains no substance on the REACH candidate list

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

VOC content : 571,2 g/l
Child-resistant fastening : Not applicable
Tactile warning : Not applicable

Directive 2012/18/EU (SEVESO III)

Seveso III Part I (Categories of dangerous substances)	Qualifying quantity (tonnes)	
	Lower-tier	Upper-tier
P3a FLAMMABLE AEROSOLS 'Flammable' aerosols Category 1 or 2, containing flammable gases Category 1 or 2 or flammable liquids Category 1	150	500

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes:			
Section	Changed item	Change	Comments
3	Composition/information on ingredients	Modified	
4.2	Symptoms/effects after skin contact	Modified	
9.1	Density	Modified	
16	Abbreviations and acronyms	Modified	

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
vPvB	Very Persistent and Very Bioaccumulative
BLV	Biological limit value
CAS-No.	Chemical Abstract Service number
EC-No.	European Community number
EN	European Standard
OEL	Occupational Exposure Limit
SDS	Safety Data Sheet
WGK	Water Hazard Class

Full text of H- and EUH-statements:		
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2	
Asp. Tox. 1	Aspiration hazard, Category 1	
EUH066		
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2	
Flam. Gas 1A	Flammable gases, Category 1A	
Flam. Liq. 1	Flammable liquids, Category 1	
Flam. Liq. 2	Flammable liquids, Category 2	
Press. Gas (Comp.)	Gases under pressure : Compressed gas	
Skin Irrit. 2	Skin corrosion/irritation, Category 2	
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis	
H220	Extremely flammable gas.	
H222	Extremely flammable aerosol.	
H224	Extremely flammable liquid and vapour.	
H225	Highly flammable liquid and vapour.	
H229	Pressurised container: May burst if heated.	
H280	Contains gas under pressure; may explode if heated.	
H304	May be fatal if swallowed and enters airways.	
H315	Causes skin irritation.	
H319	Causes serious eye irritation.	
H336	May cause drowsiness or dizziness.	
H411	Toxic to aquatic life with long lasting effects.	
H412	Harmful to aquatic life with long lasting effects.	

SDS EU (REACH Annex II)

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.