

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Issue date: 22-4-2020 Revision date: 7-6-2023 Supersedes version of: 6-1-2023 Version: 2.5

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	: Mixture
Trade name	: Kroon-Oil Industrial Chainspray
Product code	: 07.30.02
Type of product	: Lubricants
Vaporizer	: Aerosol
Product group	: Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public Main use category Use of the substance/mixture Function or use category

: Industrial use, Professional use, Consumer use

: Chain lubricant : Lubricant

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Kroon Oil BV B.V. Dollegoorweg, 15 NL– 7602 EC Almelo Netherlands T 0031 (0)546 81 81 65 vib@kroon-oil.nl

1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
United Kingdom	National Poisons Information Service (Cardiff Centre) University Hospital Llandough	Penlan Road CF64 2XX	0344 892 0111	Only for healthcare professionals

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1	H222;H229
Skin corrosion/irritation, Category 2	H315
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336
Aspiration hazard, Category 1	H304
Hazardous to the aquatic environment – Chronic Hazard, Category 2	H411
Full text of H- and EUH-statements: see section 16	

Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. May cause drowsiness or dizziness. Causes skin irritation. May be fatal if swallowed and enters airways. Toxic to aquatic life with long lasting effects.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2.2. Label elements Labelling according to Regulation (EC) No. 1272/2008 [CLP] Hazard pictograms (CLP) GHS02 GHS07 GHS09 Signal word (CLP) : Danger Contains : Pentane; Hydrocarbons, C6, isoalkanes, <5% n-hexane Hazard statements (CLP) : H222 - Extremely flammable aerosol. H229 - Pressurised container: May burst if heated. H315 - Causes skin irritation. H336 - May cause drowsiness or dizziness. H411 - Toxic to aquatic life with long lasting effects. Precautionary statements (CLP) : P101 - If medical advice is needed, have product container or label at hand. P102 - Keep out of reach of children. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 - Do not spray on an open flame or other ignition source. P251 - Do not pierce or burn, even after use. P271 - Use only outdoors or in a well-ventilated area. P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C, 122 °F P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation. Extra phrases For professional users only.

2.3. Other hazards

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

Component	
Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Distillates (petroleum), hydrotreated light paraffinic (Note L)	CAS-No.: 64742-55-8 EC-No.: 265-158-7 EC Index-No.: 649-468-00-3 REACH-no: 01-2119487077- 29	25 – 50	Asp. Tox. 1, H304

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Propane substance with a Community workplace exposure limit (Note U)	CAS-No.: 74-98-6 EC-No.: 200-827-9 EC Index-No.: 601-003-00-5 REACH-no: 01-2119486944- 21	10 – 25	Flam. Gas 1A, H220 Press. Gas (Comp.), H280
Hydrocarbons, C6, isoalkanes, <5% n-hexane	CAS-No.: 64742-49-0 EC-No.: 931-254-9 REACH-no: 01-2119484651- 34	10 – 25	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Pentane substance with national workplace exposure limit(s) (GB, IE); substance with a Community workplace exposure limit	CAS-No.: 109-66-0 EC-No.: 203-692-4 EC Index-No.: 601-006-00-1 REACH-no: 01-2119459286- 30	10 – 25	Flam. Liq. 1, H224 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 EUH066
Butane substance with national workplace exposure limit(s) (GB, IE) (Note K)	CAS-No.: 106-97-8 EC-No.: 203-448-7 EC Index-No.: 601-004-00-0 REACH-no: 01-2119474691- 32	2,5 – 10	Flam. Gas 1A, H220 Press. Gas (Comp.), H280
isobutane substance with national workplace exposure limit(s) (IE) (Note K)	CAS-No.: 75-28-5 EC-No.: 200-857-2 REACH-no: 01-2119485395- 27	1 – 2,5	Flam. Gas 1A, H220 Press. Gas (Comp.), H280

Note K: The harmonised classification as a carcinogen or mutagen applies unless it can be shown that the substance contains less than 0,1 % w/w 1,3- butadiene (Einecs No 203-450-8), in which case a classification in accordance with Title II of this Regulation shall be performed also for those hazard classes. Where the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-)P210-P403 shall apply.

Note L: The harmonised classification as a carcinogen applies unless it can be shown that the substance contains less than 3 % of dimethyl sulphoxide extract as measured by IP 346 ("Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions – Dimethyl sulphoxide extraction refractive index method" Institute of Petroleum, London), in which case a classification in accordance with Title II of this Regulation shall be performed also for that hazard class.

Note U: When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned:. Press. Gas (Comp.), Press. Gas (Liq.), Press. Gas (Ref. Liq.), Press. Gas (Diss.). Aerosols shall not be classified as gases under pressure (See Annex I, Part 2, Section 2.3.2.1, Note 2).

Product subject to CLP Article 1.1.3.7. The disclosure rules of the components is modified in this case. Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures	
4.1. Description of first aid measures	
First-aid measures general	: Call a physician immediately.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Do not induce vomiting. Call a physician immediately.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

4.2. Most important symptoms and effects, both acute and delayed			
Symptoms/effects Symptoms/effects after skin contact Symptoms/effects after ingestion	 May cause drowsiness or dizziness. Irritation. Repeated exposure may cause skin dryness or cracking. Risk of lung oedema. 		

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures	
5.1. Extinguishing media	
Suitable extinguishing media Unsuitable extinguishing media	Water spray. Dry powder. Foam. Carbon dioxide.Do not use a heavy water stream.
5.2. Special hazards arising from the subst	tance or mixture
Fire hazard Explosion hazard Hazardous decomposition products in case of fire	 Extremely flammable aerosol. Combustible liquid. Pressurised container: May burst if heated. Toxic fumes may be released. Incomplete combustion releases dangerous carbon monoxide, carbon dioxide and other toxic gases.
5.3. Advice for firefighters	
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures			
6.1. Personal precautions, protective eq	uinment and emergency procedures		
	alphent and emergency procedures		
6.1.1. For non-emergency personnel			
Emergency procedures	: Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.		
6.1.2. For emergency responders			
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".		
6.2. Environmental precautions			
Avoid release to the environment.			
6.3. Methods and material for containme	ent and cleaning up		
For containment Methods for cleaning up Other information	Collect spillage.Mechanically recover the product.Dispose of materials or solid residues at an authorized site.		
6.4. Reference to other sections			

For further information refer to section 13.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Precautions for safe handling	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. Wear personal protective equipment.
Hygiene measures	: Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
7.2. Conditions for safe storage, including a	any incompatibilities
Storage conditions	: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.
Storage temperature	: < 40 °C
7.3. Specific end use(s)	

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Kroon-Oil Industrial Chainspray			
EU - Indicative Occupational Exposure Limit (IOEL)			
Exposure limits/standards for materials that can be formed when handling this product. When mists/aerosols can occur the following is recommended	5 mg/m³ - ACGIH TLV (inhalable fraction).		
Butane (106-97-8)			
Ireland - Occupational Exposure Limits			
Local name	Butane, all isomers: Butane		
OEL STEL [ppm]	1000 ppm		
Regulatory reference	Chemical Agents Code of Practice 2021		
United Kingdom - Occupational Exposure Limits			
Local name	Butane		
WEL TWA (OEL TWA) [1]	1450 mg/m³		
WEL TWA (OEL TWA) [2]	600 ppm		
WEL STEL (OEL STEL)	1810 mg/m³		
WEL STEL (OEL STEL) [ppm]	750 ppm		
Remark	Carc (Capable of causing cancer and/or heritable genetic damage, only applies if Butane contains more than 0.1% of buta-1,3-diene)		
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE		
Propane (74-98-6)			
EU - Indicative Occupational Exposure Limit (IOEL)			
IOEL TWA [ppm]	1000 ppm		

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Propane (74-98-6)	
Ireland - Occupational Exposure Limits	
Local name	Aliphatic hydrocarbon gases Alkanes (C1-C3): Propane
Remark	Asphx. (Gaseous chemical substances which may not produce significant physiological effects in the exposed employee, but when present in high concentrations will act as simple asphyxiants)
Regulatory reference	Chemical Agents Code of Practice 2021
isobutane (75-28-5)	
Ireland - Occupational Exposure Limits	
Local name	Butane, all isomers: Isobutane
OEL STEL [ppm]	1000 ppm
Regulatory reference	Chemical Agents Code of Practice 2021
Pentane (109-66-0)	
EU - Indicative Occupational Exposure Limit	(IOEL)
Local name	Pentane
IOEL TWA	3000 mg/m ³ 3000 mg/m ³
IOEL TWA [ppm]	1000 ppm
Regulatory reference	COMMISSION DIRECTIVE 2006/15/EC COMMISSION DIRECTIVE 2006/15/EC
Ireland - Occupational Exposure Limits	· · · · · · · · · · · · · · · · · · ·
Local name	Pentane
OEL TWA [1]	3000 mg/m ³
OEL TWA [2]	1000 ppm
Remark	IOELV (Indicative Occupational Exposure Limit Values)
Regulatory reference	Chemical Agents Code of Practice 2021
United Kingdom - Occupational Exposure Lin	nits
Local name	Pentane
WEL TWA (OEL TWA) [1]	1800 mg/m³
WEL TWA (OEL TWA) [2]	600 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

Eye protection			
Туре	Field of application	Characteristics	Standard
Safety glasses	Droplet	clear	EN 166

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

Hand protection					
Туре	Material	Permeation	Thickness (mm)	Penetration	Standard
Reusable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	≥ 0.35		EN ISO 374

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

9.1. Information on basic phy	sical and chemical properties	
Physical state	: Liquid	
Colour	: light brown.	
Appearance	: Aerosol.	
Odour	: characteristic.	
Odour threshold	: Not available	
Melting point	: Not applicable	
Freezing point	Not available	
Boiling point	: -44,5 °C	
Flammability	: Extremely flammable aerosol.	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Explosive properties	: Pressurised container: May burst if heated.
Explosive limits	: Not available
Lower explosion limit	: 1,1 vol %
Upper explosion limit	: 10,9 vol %
Flash point	: -97 °C
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: substance/mixture is non-polar/aprotic
Viscosity, kinematic	: < 20,5 mm²/s (40 °C) - ASTM D7042
Solubility	: Water: Insoluble / Slightly miscible
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: 4200 hPa at 20 °C
Vapour pressure at 50°C	: Not available
Density	: 0,683 g/cm³ at 20 °C
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable
9.2. Other information	

9.2.1. Information with regard to physical hazard classes			
% of flammable ingredients	: 87,5 %		
9.2.2. Other safety characteristics			
VOC content	: 388,1 g/l		

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use. Reacts violently with (strong) oxidizers.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008			
Acute toxicity (oral) :	Not classified		
Acute toxicity (dermal) :	Not classified		
Acute toxicity (inhalation) :	Not classified		
Hydrocarbons, C6, isoalkanes, <5% n-hexane (64742-49-0)			
LD50 oral rat	> 16750 mg/kg (OECD 401 method)		
LD50 dermal rabbit	> 3350 mg/kg (OECD 402 method)		

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hydrocarbons, C6, isoalkanes, <5% n-hexane	(64742-49-0)
LC50 Inhalation - Rat	259354 mg/m³ (OECD 403 method)
Distillates (petroleum), hydrotreated light para	affinic (64742-55-8)
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 Inhalation - Rat (Dust/Mist)	5,53 mg/l/4h
Pentane (109-66-0)	
LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), Guideline: EU Method B.1 (Acute Toxicity (Oral))
LC50 Inhalation - Rat	> 25,3 mg/l Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
Skin corrosion/irritation :	Causes skin irritation.
Serious eye damage/irritation :	pH: substance/mixture is non-polar/aprotic Not classified pH: substance/mixture is non-polar/aprotic
Respiratory or skin sensitisation :	Not classified
Germ cell mutagenicity :	Not classified Not classified
Carcinogenicity : Reproductive toxicity :	Not classified
· · · · · · · · · · · · · · · · · · ·	May cause drowsiness or dizziness.
Hydrocarbons, C6, isoalkanes, <5% n-hexane	(64742-49-0)
STOT-single exposure	May cause drowsiness or dizziness.
Pentane (109-66-0)	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure :	Not classified
Distillates (petroleum), hydrotreated light para	affinic (64742-55-8)
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Pentane (109-66-0)	
NOAEC (inhalation, rat, vapour, 90 days)	30 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study), Guideline: other:, Guideline: EPA OTS 798.2450 (90-Day Inhalation Toxicity), Guideline: other:, Guideline: other:
Aspiration hazard :	May be fatal if swallowed and enters airways.
Kroon-Oil Industrial Chainspray	
Vaporizer	Aerosol
Viscosity, kinematic	< 20,5 mm²/s (40 °C) - ASTM D7042
Distillates (petroleum), hydrotreated light para	affinic (64742-55-8)
Viscosity, kinematic	< 20,5 mm²/s
Aliphatic, alicyclic or aromatic hydrocarbon	Yes
Pentane (109-66-0)	
Viscosity, kinematic	0,356 mm²/s
11.2. Information on other hazards	

No additional information available

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 12: Ecological information	
12.1. Toxicity	
Ecology - general : Hazardous to the aquatic environment, short–term : (acute)	Toxic to aquatic life with long lasting effects. Not classified Toxic to aquatic life with long lasting effects.
Distillates (petroleum), hydrotreated light para	affinic (64742-55-8)
LC50 - Fish [1]	> 100 mg/l 96h
EC50 - Crustacea [1]	> 10000 mg/l
EC50 72h - Algae [1]	≥ 100 mg/l
NOEC chronic crustacea	10 mg/l 21d
Pentane (109-66-0)	
LC50 - Fish [1]	4,26 mg/l 96h
EC50 - Crustacea [1]	2,7 mg/l 48h
12.2. Persistence and degradability	
Kroon-Oil Industrial Chainspray	
Persistence and degradability	Not readily biodegradable.
Distillates (petroleum), hydrotreated light para	affinic (64742-55-8)
Persistence and degradability	Not established.
Biodegradation	31 % (OECD 301F method)
12.3. Bioaccumulative potential	
Distillates (petroleum), hydrotreated light para	affinic (64742-55-8)
Partition coefficient n-octanol/water (Log Pow)	> 6
Bioaccumulative potential	Not established.
12.4. Mobility in soil	
No additional information available	
12.5. Results of PBT and vPvB assessment	
Kroon-Oil Industrial Chainspray	
This substance/mixture does not meet the PBT criteria	of REACH regulation, annex XIII
This substance/mixture does not meet the vPvB criteria	a of REACH regulation, annex XIII
Component	
Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
12.6. Endocrine disrupting properties	
No additional information available	
12.7. Other adverse effects	
No additional information available	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods

Product/Packaging disposal recommendations European List of Waste (LoW) code

HP Code

- : Dispose of contents/container in accordance with licensed collector's sorting instructions.
- : Do not remove as household garbage. Do not discharge waste into drains.
 - : 20 01 13* solvents
 - 15 01 04 metallic packaging
 - : HP3 "Flammable:"
 - flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C;
 - flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air;
 - flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction;
 - flammable gaseous waste: gaseous waste which is flammable in air at 20 $^\circ C$ and a standard pressure of 101.3 kPa;
 - water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities;
 - other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste.
 - HP14 "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID ADR IMDG ΙΑΤΑ ADN RID 14.1. UN number or ID number UN 1950 UN 1950 UN 1950 UN 1950 UN 1950 14.2. UN proper shipping name AEROSOLS AEROSOLS Aerosols, flammable AEROSOLS AEROSOLS (Hydrocarbons, C6, (Hydrocarbons, C6, (Hydrocarbons, C6, (Hydrocarbons, C6, (Hydrocarbons, C6, isoalkanes, <5% n-hexane) Transport document description **UN 1950 AEROSOLS UN 1950 AEROSOLS** UN 1950 Aerosols. **UN 1950 AEROSOLS UN 1950 AEROSOLS** (Hydrocarbons, C6, (Hydrocarbons, C6, flammable (Hydrocarbons, (Hydrocarbons, C6, (Hydrocarbons, C6, isoalkanes, <5% n-hexane), isoalkanes, <5% n-hexane), isoalkanes, <5% n-hexane), C6, isoalkanes, <5% nisoalkanes, <5% n-hexane), 2.1, ENVIRONMENTALLY 2.1, ENVIRONMENTALLY 2.1, (D), 2.1, MARINE hexane), 2.1, ENVIRONMENTALLY POLLUTANT/ENVIRONME HAZARDOUS HAZARDOUS ENVIRONMENTALLY HAZARDOUS NTALLY HAZARDOUS HAZARDOUS 14.3. Transport hazard class(es) 2.1 2.1 2.1 2.1 2.1 14.4. Packing group Not applicable Not applicable Not applicable Not applicable Not applicable

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	ΙΑΤΑ	ADN	RID
14.5. Environmental hazard	S			1
Dangerous for the	Dangerous for the	Dangerous for the	Dangerous for the	Dangerous for the
environment: Yes	environment: Yes	environment: Yes	environment: Yes	environment: Yes
	Marine pollutant: Yes			
No supplementary information av	vailable			·
14.6. Special precautions fo	r user			
Overland transport				
Classification code (ADR)	: -			
Special provisions (ADR)		190, 327, 344, 625		
Limited quantities (ADR)		11		
Excepted quantities (ADR)		Ξ0		
Packing instructions (ADR)		P207		
Special packing provisions (ADR)		PP87, RR6, L2		
Mixed packing provisions (ADR)		MP9		
Transport category (ADR)	: :			
Special provisions for carriage - P		V14		
Special provisions for carriage - L	oading, unloading :	CV9, CV12		
and handling (ADR)		20		
Special provisions for carriage - C				
Tunnel restriction code (ADR)	:			
Transport by sea				
Special provisions (IMDG)	: (63, 190, 277, 327, 344, 381, 959		
Limited quantities (IMDG)	: :	SP277		
Excepted quantities (IMDG)	:	Ξ0		
Packing instructions (IMDG)	:	P207, LP200		
Special packing provisions (IMDG		PP87, L2		
EmS-No. (Fire)		F-D		
EmS-No. (Spillage)		S-U		
Stowage category (IMDG)		None		
Stowage and handling (IMDG)		SW1, SW22		
Segregation (IMDG)		SG69		
Air transport				
PCA Excepted quantities (IATA)	:	EO		
PCA Limited quantities (IATA)	: `	Y203		
PCA limited quantity max net quantity	ntity (IATA) ::	30kgG		
PCA packing instructions (IATA)	: :	203		
PCA max net quantity (IATA)	: '	75kg		
CAO packing instructions (IATA)	: :	203		
CAO max net quantity (IATA)	:	150kg		
Special provisions (IATA)	: /	A145, A167, A802		
ERG code (IATA)	: '	10L		
Inland waterway transport				
Classification code (ADN)	: :	5F		
Special provisions (ADN)		190, 327, 344, 625		
Limited quantities (ADN)	-			
Excepted quantities (ADN)		EO		
Equipment required (ADN)		PP, EX, A		
Ventilation (ADN)		VE01, VE04		
Number of blue cones/lights (ADN				
Rail transport				
Classification code (RID)	: :			
Special provisions (RID)		190, 327, 344, 625		
7-6-2023 (Revision date)		EN (English)		12/

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Limited quantities (RID) Excepted quantities (RID)	-	1L E0
Packing instructions (RID)	:	P207, LP200
Special packing provisions (RID)	:	PP87, RR6, L2
Mixed packing provisions (RID)	:	MP9
Transport category (RID)	:	2
Special provisions for carriage – Packages (RID)	:	W14
Special provisions for carriage - Loading, unloading and handling (RID)	:	CW9, CW12
Colis express (express parcels) (RID)	:	CE2
Hazard identification number (RID)	:	23

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information	n
---	---

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

VOC Directive (2004/42)		
VOC content	:	388,1 g/l
Biocide Regulation (528/2012)		
Child-resistant fastening	:	Not applicable
Tactile warning	:	Not applicable

Seveso Directive (Disaster Risk Reduction)

Seveso III Part I (Categories of dangerous substances)	Qualifying quantity (tonnes)	
	Lower-tier	Upper-tier
P3a FLAMMABLE AEROSOLS 'Flammable' aerosols Category 1 or 2, containing flammable gases Category 1 or 2 or flammable liquids Category 1	150	500
E2 Hazardous to the Aquatic Environment in Category Chronic 2	200	500

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes			
Section	Changed item	Change	Comments
2.2	Extra phrases	Added	
12.2	Persistence and degradability	Modified	

Abbreviations and acronyms:		
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways	
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road	
ATE	Acute Toxicity Estimate	
BCF	Bioconcentration factor	
BLV	Biological limit value	
BOD	Biochemical oxygen demand (BOD)	
COD	Chemical oxygen demand (COD)	
DMEL	Derived Minimal Effect level	
DNEL	Derived-No Effect Level	
EC-No.	European Community number	
EC50	Median effective concentration	
EN	European Standard	
IARC	International Agency for Research on Cancer	
ΙΑΤΑ	International Air Transport Association	
IMDG	International Maritime Dangerous Goods	
LC50	Median lethal concentration	
LD50	Median lethal dose	
LOAEL	Lowest Observed Adverse Effect Level	
NOAEC	No-Observed Adverse Effect Concentration	
NOAEL	No-Observed Adverse Effect Level	
NOEC	No-Observed Effect Concentration	
OECD	Organisation for Economic Co-operation and Development	
OEL	Occupational Exposure Limit	
РВТ	Persistent Bioaccumulative Toxic	
PNEC	Predicted No-Effect Concentration	
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail	
SDS	Safety Data Sheet	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:		
STP	Sewage treatment plant	
ThOD	Theoretical oxygen demand (ThOD)	
TLM	Median Tolerance Limit	
VOC	Volatile Organic Compounds	
CAS-No.	Chemical Abstract Service number	
N.O.S.	Not Otherwise Specified	
vPvB	Very Persistent and Very Bioaccumulative	
ED	Endocrine disrupting properties	

Full text of H- and EUH-statements:		
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2	
Asp. Tox. 1	Aspiration hazard, Category 1	
EUH066	Repeated exposure may cause skin dryness or cracking.	
Flam. Gas 1A	Flammable gases, Category 1A	
Flam. Liq. 1	Flammable liquids, Category 1	
Flam. Liq. 2	Flammable liquids, Category 2	
H220	Extremely flammable gas.	
H222	Extremely flammable aerosol.	
H224	Extremely flammable liquid and vapour.	
H225	Highly flammable liquid and vapour.	
H229	Pressurised container: May burst if heated.	
H280	Contains gas under pressure; may explode if heated.	
H304	May be fatal if swallowed and enters airways.	
H315	Causes skin irritation.	
H336	May cause drowsiness or dizziness.	
H411	Toxic to aquatic life with long lasting effects.	
Press. Gas (Comp.)	Gases under pressure : Compressed gas	
Skin Irrit. 2	Skin corrosion/irritation, Category 2	
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis	

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.