

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 Issue date: 10-9-2018 Revision date: 25-7-2019 Supersedes: 23-7-2019 Version: 1.2

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form
Trade name
Product code
Product group

:	Mixture
:	Kroontex SDC
:	09.50.02
:	Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category Use of the substance/mixture Industrial use,Professional useAnti-rust coating

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Kroon Oil BV Dollegoorweg 15 7602 EC Almelo - Netherlands T 0031 (0)546 81 81 65 vib@kroon-oil.nl

1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
United Kingdom	National Poisons Information Service (Cardiff Centre) Gwenwyn Ward, Llandough Hospital	Penarth CF64 2XX Cardiff	0344 892 0111	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aspiration hazard, Category 1 Full text of H statements : see section 16 H304

Adverse physicochemical, human health and environmental effects

May be fatal if swallowed and enters airways.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP] Hazard pictograms (CLP)



: Danger

25-7-2019 (Version: 1.2)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Hazardous ingredients Hazard statements (CLP) Precautionary statements (CLP)	 Naphtha (petroleum), hydrotreated heavy; Mineral oil * H304 - May be fatal if swallowed and enters airways. P301+P310+P331 - IF SWALLOWED: Immediately call a doctor. Do NOT induce vomiting.
EUH-statements	 P405 - Store locked up. P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation. EUH066 - Repeated exposure may cause skin dryness or cracking. EUH208 - Contains Sulfonic acids, petroleum, calcium salts. May produce an allergic reaction.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	
Mineral oil * (Note L)		≥ 50	Asp. Tox. 1, H304	
Calcium bis(dinonyInaphthalenesulphonate)	(CAS-No.) 57855-77-3 (EC-No.) 260-991-2	1 – 2,5	Skin Irrit. 2, H315 Eye Irrit. 2, H319	
Sulfonic acids, petroleum, calcium salts	(CAS-No.) 61789-86-4 (EC-No.) 263-093-9 (REACH-no) 01-2119488992-18	1 – 2,5	Skin Sens. 1, H317	
2-(2-butoxyethoxy)ethanol substance with national workplace exposure limit(s) (GB, IE)	(CAS-No.) 112-34-5 (EC-No.) 203-961-6 (EC Index-No.) 603-096-00-8 (REACH-no) 01-2119475104-44	< 1	Eye Irrit. 2, H319	
Oleic acid, compound with (Z)-N-octadec-9- enylpropane-1,3-diamine (2:1)	(CAS-No.) 34140-91-5 (EC-No.) 251-846-4 (REACH-no) 01-2119974119-29	< 1	Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT RE 2, H373 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 2, H411	

Comments

: * contains one or more of the following CAS-numbers (REACH registration numbers): 64741-88-4 (01-2119488706-23), 64741-89-5 (01-2119487067-30), 64741-95-3 (01-2119487081-40), 64741-96-4 (01-2119483621-38), 64741-97-5 (01-2119480374-36), 64742-01-4 (01-2119488707-21), 64742-52-5 (01-2119467170-45), 64742-53-6 (01-2119480375-34), 64742-54-7 (01-2119484627-25), 64742-55-8 (01-2119487077-29), 64742-56-9 (01-2119480132-48), 64742-57-0 (01-2119489287-22), 64742-62-7 (01-2119480472-38), 64742-65-0 (01-2119471299-27), 64742-71-8 (01-2119485040-48), 72623-85-9 (01-2119555262-43), 72623-86-0 (01-2119474878-16), 72623-87-1 (01-2119474889-13), 74869-22-0 (01-2119495601-36)

The highly refined mineral oil contains <3% (w/w) DMSOextract, according to IP346.

Note L : The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346 'Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions — Dimethyl sulphoxide extraction refractive index method', Institute of Petroleum, London. This note applies only to certain complex oil-derived substances in Part 3. Full text of H-statements: see section 16

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 4: First aid measures

4.1. Description of first aid measures	
First-aid measures general	: Call a physician immediately.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a physician immediately. Do not induce vomiting.
4.2. Most important symptoms and effects	s, both acute and delayed
Symptoms/effects Symptoms/effects after skin contact Symptoms/effects after ingestion	 Not expected to present a significant hazard under anticipated conditions of normal use. Repeated exposure may cause skin dryness or cracking. May result in aspiration into the lungs, causing chemical pneumonia. Risk of lung oedema.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures				
5.1. Extinguishing media				
Suitable extinguishing media Unsuitable extinguishing media	Water spray. Dry powder. Foam. Carbon dioxide.Do not use a heavy water stream.			
5.2. Special hazards arising from the substance or mixture				
Fire hazard Hazardous decomposition products in case of fire	 Combustible liquid. Incomplete combustion releases dangerous carbon monoxide, carbon dioxide and other toxic gases. 			
5.3. Advice for firefighters				
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.			

SECTION 6: Accidental release measures					
6.1. Personal precautions, protective equipment and emergency procedures					
6.1.1. For non-emergency personnel					
Emergency procedures	: Ventilate spillage area.				
6.1.2. For emergency responders					
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".				
6.2. Environmental precautions					
Avoid release to the environment.					

6.3. Methods and material for containment and cleaning up					
Methods for cleaning up Other information	Take up liquid spill into absorbent material.Dispose of materials or solid residues at an authorized site.				
6.4. Reference to other sections					

For further information refer to section 13.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 7: Handling and stor	age
7.1. Precautions for safe handling	
Precautions for safe handling Hygiene measures	 Ensure good ventilation of the work station. Wear personal protective equipment. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
7.2. Conditions for safe storage, in	ncluding any incompatibilities
Storage conditions Storage temperature	 Store locked up. Store in a well-ventilated place. Keep cool. < 40 °C

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Kroontex SDC

EU - Occupational Exposure Limits

 Exposure limits/standards for materials that can be formed when handling this product. When mists/aerosols can occur the following is recommended
 5 mg/m³ - ACGIH TLV (inhalable fraction).

2-(2-butoxyethoxy)ethanol (112-34-5)				
Ireland - Occupational Exposure Limits				
Local name	2-(2-Butoxyethoxy)ethanol			
OEL (8 hours ref) (mg/m ³)	67,5 mg/m³			
OEL (8 hours ref) (ppm)	10 ppm			
OEL (15 min ref) (mg/m3)	101,2 mg/m³			
OEL (15 min ref) (ppm)	15 ppm			
Notes (IE)	IOELV (Indicative Occupational Exposure Limit Values)			
Regulatory reference	Chemical Agents Code of Practice 2020			
United Kingdom - Occupational Exposure Limits				
Local name	2-(2-Butoxyethoxy)ethanol			
WEL TWA (mg/m³)	67,5 mg/m³			
WEL TWA (ppm)	10 ppm			
WEL STEL (mg/m³)	101,2 mg/m³			
WEL STEL (ppm)	15 ppm			
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE			

8.2. Exposure controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Hand protection:			
Protective gloves			

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Туре	Material	Permeation	Thickness (mm)	Penetration	Standard
Reusable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	≥ 0.35		EN ISO 374
Reusable gloves	Butyl rubber	6 (> 480 minutes)	≥ 0.64		EN ISO 374

Eye protection:			
Safety glasses			
Туре	Use	Characteristics	Standard
Safety glasses	Droplet	clear	EN 166

Skin and body protection:
Wear suitable protective clothing
Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Colour Odour Odour threshold pH Relative evaporation rate (butylacetate=1) Melting point Freezing point Boiling point Flash point Auto-ignition temperature Decomposition temperature Flammability (solid, gas) Vapour pressure Relative vapour density at 20 °C Relative density Solubility Partition coefficient n-octanol/water (Log Pow) Viscosity, kinematic Viscosity, dynamic	 Liquid brown. Hydrocarbon. No data available 67 °C - ASTM D93 (PM) No data available < 20,5 mm²/s (40 °C) - ASTM D7279 No data available
Viscosity, kinematic	: < 20,5 mm²/s (40 °C) - ASTM D7279
9.2 Other information	

9.2. Other information

VOC content

: 65 % 2010/75/EU

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reacts violently with (strong) oxidizers.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Mineral oil *	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 5000 mg/kg
LC50 inhalation rat (Dust/Mist - mg/l/4h)	> 5 mg/l/4h

Sulfonic acids, petroleum, calcium salts (61789-86-4)		
LD50 oral rat	> 16000 mg/kg	
LD50 dermal rabbit	> 4000 mg/kg	

Calcium bis(dinonyInaphthalenesuIphonate) (57855-77-3)	
LD50 oral rat	> 2500 mg/kg
LD50 dermal	> 10000 mg/kg
LC50 inhalation rat (mg/l)	> 9000 mg/l (1h)

2-(2-butoxyethoxy)ethanol (112-34-5)	
LD50 oral rat	3384 mg/kg
LD50 dermal rabbit	2700 mg/kg

Oleic acid, compound with (Z)-N-octadec-9-enylpropane-1,3-diamine (2:1) (34140-91-5)		
LD50 oral rat	2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method)	

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal)), Guideline: EPA OPPTS 870.1200 (Acute Dermal Toxicity), Guideline: other:Japanese Ministry of Agriculture, Forestry and Fisheries (JMAFF), 12 Nohsan, Notification No. 8147 April 2011; including the most recent partial revisions.
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified

Calcium bis(dinonyInaphthalenesuIphonate) (57855-77-3)		
NOAEL (subacute, oral, animal/male, 28 days)	95 mg/kg bodyweight	

Oleic acid, compound with (Z)-N-octadec-9-enylpropane-1,3-diamine (2:1) (34140-91-5)		
LOAEL (oral, rat, 90 days)	20 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28- Day Oral Toxicity in Rodents), Guideline: EU Method B.7 (Repeated Dose (28 Days) Toxicity (Oral)), Guideline: other:OPPTS 870.3050 (Repeated dose 28-day oral toxicity study in rodents)	
NOAEL (oral, rat, 90 days)	0,4 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28- Day Oral Toxicity in Rodents), Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EU Method B.7 (Repeated Dose (28 Days) Toxicity (Oral)), Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90- Day Oral Toxicity Study in Rodents)	
Aspiration hazard	: May be fatal if swallowed and enters airways.	
Kroontex SDC		
Viscosity, kinematic	< 20,5 mm²/s (40 °C) - ASTM D7279	

SECTION 12: Ecological information	
12.1. Toxicity	
Ecology - general	The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	Not classified
Hazardous to the aquatic environment, long-term (chronic)	Not classified
Mineral oil *	
LC50 fish	> 100 mg/l
EC50 Daphnia	> 10000 mg/l
EC50 72h algae (1)	> 100 mg/l

Sulfonic acids, petroleum, calcium salts (61789-86-4)		
LC50 fish	> 101 mg/l	

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

EC50 Daphnia	> 1001 mg/l (Daphnia magna, 48h) [EPA OTS 797.1300]
EC50 72h algae (1)	> 1000 mg/l (Pseudokirchnerella subcapitata, 72h) [EPA OTS 797.1050]
EC50 72h algae (2)	> 101 mg/l

Calcium bis(dinonyInaphthalenesuIphonate) (57855-77-3)	
LC50 fish	> 0,28 mg/l (96h)
EC50 Daphnia	> 0,27 mg/l (48h)
NOEC (acute)	> 0,27 mg/l (72h, Algae)

2-(2-butoxyethoxy)ethanol (112-34-5)		
LC50 fish	1300 mg/l Lepomis macrochirus; 96 h	
LC50 fish	2750 mg/l Leuciscus idus melanotus; 48 h (DIN 38412)	
EC50 Daphnia	> 101 mg/l	
EC50 96h algae (1)	> 101 mg/l	
NOEC (acute)	> 100 mg/l Desmodesmus subspicatus (green algae); 96 h (OCDE Guideline 201)	

Oleic acid, compound with (Z)-N-octadec-9-enylpropane-1,3-diamine (2:1) (34140-91-5)		
LC50 fish	1,35 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)	
LC50 fish	1,34 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)	
EC50 72h algae (1)	0,41 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)	

12.2. Persistence and degradability

Sulfonic acids, petroleum, calcium salts (61789-86-4)	
Biodegradation	8,6 % (28d) (OECD 301F method)

2-(2-butoxyethoxy)ethanol (112-34-5)		
Persistence and degradability	Readily biodegradable.	
Biodegradation	76 % (28 d) [OECD 301 D]	
12.3. Bioaccumulative potential		
Sulfonic acids, petroleum, calcium salts (6178	9-86-4)	
Partition coefficient n-octanol/water (Log Pow)	> 5,47 (20°C)	
Calcium bis(dinonylnaphthalenesulphonate) (57855-77-3)	
Bioconcentration factor (BCF REACH)	3,16	
Partition coefficient n-octanol/water (Log Kow)	> 6,6	
2-(2-butoxyethoxy)ethanol (112-34-5)		
Partition coefficient n-octanol/water (Log Kow)	0,56	
12.4. Mobility in soil		
Calcium bis(dinonyInaphthalenesulphonate) (57855-77-3)		
Partition coefficient n-octanol/water (Log Koc) 5,24 (20°C)		

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods

: Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

ADR	IMDG	ΙΑΤΑ	ADN	RID
I4.1. UN number	-	'	'	
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.2. UN proper shippi	ng name	· · · · ·	'	
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard	class(es)	· · · · · ·	·	
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group		· · · · ·	'	
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental ha	zards	· · · · ·	'	
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated

14.6. Special precautions for user

Overland transport Not regulated Transport by sea Not regulated Air transport Not regulated Inland waterway transport Not regulated Rail transport Not regulated

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions Contains no substance on the REACH candidate list Contains no REACH Annex XIV substances

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

VOC content

: 65 % 2010/75/EU

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes:			
Section	Changed item	Change	Comments
3	Composition/information on ingredients	Modified	

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
IARC	International Agency for Research on Cancer
ΙΑΤΑ	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
vPvB	Very Persistent and Very Bioaccumulative

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Full text of H- and EUH-statements:	
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
Н373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH208	Contains Sulfonic acids, petroleum, calcium salts. May produce an allergic reaction.

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.