



Kroon-Oil Diesel Treatment

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830
Date of issue: 28-6-2018 Revision date: 27-12-2018 Supersedes: 28-6-2018 Version: 1.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : Kroon-Oil Diesel Treatment
Product code : 98.70.02
Type of product : Additive
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use, Industrial use
Use of the substance/mixture : Fuel additive

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Kroon Oil BV
Dollegoorweg 15
7602 EC Almelo - Netherlands
T 0031 (0)546 81 81 65
vib@kroon_oil.nl

1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
United Kingdom	National Poisons Information Service (Cardiff Centre) Gwenwyn Ward, Llandough Hospital	Penarth CF64 2XX Cardiff	0344 892 0111	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin corrosion/irritation, Category 2 H315
Serious eye damage/eye irritation, Category 2 H319
Carcinogenicity, Category 2 H351
Specific target organ toxicity — Single exposure, Category 3, Narcosis H336
Aspiration hazard, Category 1 H304
Hazardous to the aquatic environment — Chronic Hazard, Category 2 H411
Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

Suspected of causing cancer. May cause drowsiness or dizziness. Causes skin irritation. Causes serious eye irritation. May be fatal if swallowed and enters airways. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS07

GHS08

GHS09

Signal word (CLP) :

Danger

Hazardous ingredients :

Hydrocarbons, C10, aromatics, <1% naphthalene; naphthalene

Hazard statements (CLP) :

H304 - May be fatal if swallowed and enters airways.
H315 - Causes skin irritation.
H319 - Causes serious eye irritation.
H336 - May cause drowsiness or dizziness.
H351 - Suspected of causing cancer.
H411 - Toxic to aquatic life with long lasting effects.

Kroon-Oil Diesel Treatment

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Precautionary statements (CLP) : P201 - Obtain special instructions before use.
P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 - Wash hands, forearms and face thoroughly after handling.
P273 - Avoid release to the environment.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310+P331 - IF SWALLOWED: Immediately call a POISON CENTER/doctor/.... Do NOT induce vomiting.
P308+P313 - IF exposed or concerned: Get medical advice/attention.
P391 - Collect spillage.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrocarbons, C10, aromatics, <1% naphthalene	(EC-No.) 918-811-1 (REACH-no) 01-2119463583-34	25 - 80	STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
2-butoxyethanol	(CAS-No.) 111-76-2 (EC-No.) 203-905-0 (EC Index-No.) 603-014-00-0 (REACH-no) 01-2119475108-36	5 - 20	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319
2-ethylhexyl nitrate	(CAS-No.) 27247-96-7 (EC-No.) 248-363-6 (REACH-no) 01-2119539586-27	2,5 - 10	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Aquatic Chronic 2, H411
2-ethylhexan-1-ol	(CAS-No.) 104-76-7 (EC-No.) 203-234-3	1 - 5	Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Aquatic Chronic 2, H411
1,2,4-Trimethylbenzene	(CAS-No.) 95-63-6 (EC-No.) 202-436-9 (EC Index-No.) 601-043-00-3 (REACH-no) 01-2119472135-42	0,1 - 2,5	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Aquatic Chronic 2, H411
naphthalene	(CAS-No.) 91-20-3 (EC-No.) 202-049-5 (EC Index-No.) 601-052-00-2 (REACH-no) 01-2119561346-37	0,1 - 2,5	Acute Tox. 4 (Oral), H302 Carc. 2, H351 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention. Call a poison center or a doctor if you feel unwell. Get medical advice/attention if you feel unwell. Call a physician immediately.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse eyes with water as a precaution. Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Do not induce vomiting. Call a physician immediately. Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : May cause drowsiness or dizziness.

Symptoms/effects after skin contact : Irritation. Repeated exposure may cause skin dryness or cracking.

Kroon-Oil Diesel Treatment

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Symptoms/effects after eye contact : Eye irritation.
Symptoms/effects after ingestion : Risk of lung oedema.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.
Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

2-butoxyethanol (111-76-2)		
EU	Local name	2-Butoxyethanol
EU	IOELV TWA (mg/m ³)	98 mg/m ³
EU	IOELV TWA (ppm)	20 ppm
EU	IOELV STEL (mg/m ³)	246 mg/m ³
EU	IOELV STEL (ppm)	50 ppm
EU	Notes	Skin
EU	Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Germany	TRGS 910 Acceptable concentration notes	
United Kingdom	Local name	2-Butoxyethanol

Kroon-Oil Diesel Treatment

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

2-butoxyethanol (111-76-2)		
United Kingdom	WEL TWA (mg/m ³)	123 mg/m ³
United Kingdom	WEL TWA (ppm)	25 ppm
United Kingdom	WEL STEL (mg/m ³)	246 mg/m ³
United Kingdom	WEL STEL (ppm)	50 ppm
United Kingdom	Remark (WEL)	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
United Kingdom	Regulatory reference	EH40/2005 (Third edition, 2018). HSE

2-ethylhexan-1-ol (104-76-7)		
EU	Local name	2-ethylhexan-1-ol
EU	IOELV TWA (mg/m ³)	5,4 mg/m ³
EU	IOELV TWA (ppm)	1 ppm
EU	Regulatory reference	COMMISSION DIRECTIVE (EU) 2017/164
Germany	TRGS 910 Acceptable concentration notes	
United Kingdom	Local name	2-ethylhexan-1-ol
United Kingdom	WEL TWA (mg/m ³)	5,4 mg/m ³
United Kingdom	WEL TWA (ppm)	1 ppm
United Kingdom	Regulatory reference	EH40/2005 (Third edition, 2018). HSE

1,2,4-Trimethylbenzene (95-63-6)		
EU	Local name	1,2,4-Trimethylbenzene
EU	IOELV TWA (mg/m ³)	100 mg/m ³
EU	IOELV TWA (ppm)	20 ppm
EU	Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Germany	TRGS 910 Acceptable concentration notes	
United Kingdom	WEL TWA (mg/m ³)	125 mg/m ³
United Kingdom	WEL TWA (ppm)	25 ppm

naphthalene (91-20-3)		
EU	Local name	Naphthalene
EU	IOELV TWA (mg/m ³)	50 mg/m ³
EU	IOELV TWA (ppm)	10 ppm
EU	Notes	(Year of adoption 2010)
EU	Regulatory reference	COMMISSION DIRECTIVE 91/322/EEC; SCOEL Recommendations
Germany	TRGS 910 Acceptable concentration notes	
United Kingdom	WEL TWA (mg/m ³)	50 mg/m ³

8.2. Exposure controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Hand protection:					
Protective gloves					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Reusable gloves	Nitrile rubber (NBR), Neoprene rubber (HNBR)	5 (> 240 minutes), 6 (> 480 minutes)	>=0,35		EN ISO 374

Kroon-Oil Diesel Treatment

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Eye protection:			
Safety glasses			
Type	Use	Characteristics	Standard
Safety glasses	Droplet	clear	EN 166
Skin and body protection:			
Wear suitable protective clothing			
Respiratory protection:			
In case of insufficient ventilation, wear suitable respiratory equipment			

Personal protective equipment symbol(s):



Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: orange.
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 62 °C - ASTM D93 (PM)
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: < 20,5 mm ² /s (40 °C) - ASTM D7279
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

Kroon-Oil Diesel Treatment

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

2-butoxyethanol (111-76-2)	
LD50 oral rat	470 mg/kg
LD50 oral	300 mg/kg rabbit
LD50 dermal rat	2270 mg/kg
LD50 dermal rabbit	2000 mg/kg
LC50 inhalation rat (mg/l)	> 2 mg/l/4h

2-ethylhexyl nitrate (27247-96-7)	
LD50 oral rat	> 10 ml/kg
LD50 dermal rabbit	> 5 ml/kg
LC50 inhalation rat (Vapours - mg/l/4h)	2,7 mg/l/4h

1,2,4-Trimethylbenzene (95-63-6)	
LD50 oral rat	3400 - 6000 mg/kg
LD50 dermal rabbit	3160 mg/kg
LC50 inhalation rat (mg/l)	18000 mg/m ³ (4h)

naphthalene (91-20-3)	
LD50 oral rat	> 2000 mg/kg
LD50 dermal rat	> 2000 mg/kg

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Suspected of causing cancer.
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
Aspiration hazard	: May be fatal if swallowed and enters airways.

Kroon-Oil Diesel Treatment	
Viscosity, kinematic	< 20,5 mm ² /s (40 °C) - ASTM D7279

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Toxic to aquatic life with long lasting effects. Before neutralisation, the product may represent a danger to aquatic organisms.
Acute aquatic toxicity	: Not classified
Chronic aquatic toxicity	: Toxic to aquatic life with long lasting effects.

2-butoxyethanol (111-76-2)	
LC50 fish 1	1474 mg/l (Oncorhynchus mykiss, 96h)
EC50 Daphnia 1	1550 mg/l (Daphnia magna, 48h)
ErC50 (algae)	911 mg/l (Pseudokirchneriella subcapitata, 72h)

Kroon-Oil Diesel Treatment

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

2-ethylhexyl nitrate (27247-96-7)	
LC50 fish 1	2 mg/l (Danio rerio, 96h) (OECD 203 method)
EC50 Daphnia 1	> 12,6 mg/l (Daphnia magna, 48h) (OECD 202 method)
EC50 72h algae (1)	3,22 mg/l (Pseudokirchnerella subcapitata, 72h) (OECD 201 method)
NOEC (acute)	1,52 mg/l (Danio rerio, 96h) (OECD 203 method)

1,2,4-Trimethylbenzene (95-63-6)	
EC50 Daphnia 1	6,14 mg/l (48h)

naphthalene (91-20-3)	
LC50 fish 1	0,51 mg/l 96h
EC50 Daphnia 1	3,4 mg/l Daphnia magna - 48h

12.2. Persistence and degradability

2-butoxyethanol (111-76-2)	
Persistence and degradability	Readily biodegradable.

2-ethylhexyl nitrate (27247-96-7)	
Persistence and degradability	Not readily biodegradable.
Biodegradation	0 % (28d) (OECD 310 method)

12.3. Bioaccumulative potential

2-butoxyethanol (111-76-2)	
Bioaccumulative potential	None.

2-ethylhexyl nitrate (27247-96-7)	
Bioconcentration factor (BCF REACH)	>= 500
Log Kow	5,24 (OECD 117 method)

2-ethylhexan-1-ol (104-76-7)	
Log Pow	2,9

naphthalene (91-20-3)	
Log Pow	3,01

12.4. Mobility in soil

2-butoxyethanol (111-76-2)	
Ecology - soil	Material highly soluble in water.

2-ethylhexyl nitrate (27247-96-7)	
Log Koc	3,8 (0.1d)

12.5. Results of PBT and vPvB assessment

Component	
2-butoxyethanol (111-76-2)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.






Kroon-Oil Diesel Treatment

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN


ADR	IMDG	IATA	ADN	RID
14.1. UN number				
UN 3082	UN 3082	UN 3082	UN 3082	UN 3082
14.2. UN proper shipping name				
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	Environmentally hazardous substance, liquid, n.o.s.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
Transport document description				
UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., 9, III, (-)	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., 9, III, MARINE POLLUTANT	UN 3082 Environmentally hazardous substance, liquid, n.o.s., 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., 9, III
14.3. Transport hazard class(es)				
9	9	9	9	9
				
14.4. Packing group				
III	III	III	III	III
14.5. Environmental hazards				
Dangerous for the environment : Yes	Dangerous for the environment : Yes Marine pollutant : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes

No supplementary information available

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: M6
Special provisions (ADR)	: 274, 335, 375, 601
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E1
Packing instructions (ADR)	: P001, IBC03, LP01, R001
Special packing provisions (ADR)	: PP1
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T4
Portable tank and bulk container special provisions (ADR)	: TP1, TP29
Tank code (ADR)	: LGBV
Vehicle for tank carriage	: AT
Transport category (ADR)	: 3
Special provisions for carriage - Packages (ADR)	: V12
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV13
Hazard identification number (Kemler No.)	: 90
Orange plates	:



Tunnel restriction code (ADR) : -

Kroon-Oil Diesel Treatment

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

EAC code : •3Z

Transport by sea

Special provisions (IMDG) : 274, 335, 969
Packing instructions (IMDG) : P001, LP01
Special packing provisions (IMDG) : PP1
IBC packing instructions (IMDG) : IBC03
Tank instructions (IMDG) : T4
Tank special provisions (IMDG) : TP2, TP29
EmS-No. (Fire) : F-A
EmS-No. (Spillage) : S-F
Stowage category (IMDG) : A

Air transport

PCA Excepted quantities (IATA) : E1
PCA Limited quantities (IATA) : Y964
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 964
PCA max net quantity (IATA) : 450L
CAO packing instructions (IATA) : 964
CAO max net quantity (IATA) : 450L
Special provisions (IATA) : A97, A158, A197
ERG code (IATA) : 9L

Inland waterway transport

Classification code (ADN) : M6
Special provisions (ADN) : 274, 335, 375, 601
Limited quantities (ADN) : 5 L
Excepted quantities (ADN) : E1
Carriage permitted (ADN) : T
Equipment required (ADN) : PP
Number of blue cones/lights (ADN) : 0

Rail transport

Classification code (RID) : M6
Special provisions (RID) : 274, 335, 375, 601
Excepted quantities (RID) : E1
Packing instructions (RID) : P001, IBC03, LP01, R001
Special packing provisions (RID) : PP1
Mixed packing provisions (RID) : MP19
Portable tank and bulk container instructions (RID) : T4
Portable tank and bulk container special provisions (RID) : TP1, TP29
Tank codes for RID tanks (RID) : LGBV
Transport category (RID) : 3
Special provisions for carriage – Packages (RID) : W12
Special provisions for carriage - Loading, unloading and handling (RID) : CW13, CW31
Colis express (express parcels) (RID) : CE8
Hazard identification number (RID) : 90

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to REGULATION (EU) No 649/2012 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 4 July 2012 concerning the export and import of hazardous chemicals.

Kroon-Oil Diesel Treatment

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Substance(s) are not subject to Regulation (EC) No 850/2004 of the European Parliament and of the Council of 29 April 2004 on persistent organic pollutants and amending Directive 79/117/EEC.

Directive 2012/18/EU (SEVESO III)

Seveso III Part I (Categories of dangerous substances)	Qualifying quantity (tonnes)	
	Lower-tier	Upper-tier
E2 Hazardous to the Aquatic Environment in Category Chronic 2	200	500

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes:			
Section	Changed item	Change	Comments
	Revision date	Added	
	Date of issue	Modified	
4.1	First-aid measures after ingestion	Modified	
4.1	First-aid measures after eye contact	Modified	
4.1	First-aid measures general	Modified	
12.1	Ecology - general	Modified	

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
STP	Sewage treatment plant
TLM	Median Tolerance Limit

Kroon-Oil Diesel Treatment

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SDS	Safety Data Sheet
vPvB	Very Persistent and Very Bioaccumulative

Full text of H- and EUH-statements:	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 2	Carcinogenicity, Category 2
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product