



# Textile Proof & Protect

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830  
Issue date: 6-12-2018 Revision date: 17-7-2020 Supersedes: 28-1-2019 Version: 1.2

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Trade name : Textile Proof & Protect  
Product code : PW.40.17  
Type of product : Detergent  
Vaporizer : Aerosol  
Product group : Trade product

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Intended for general public  
Main use category : Industrial use, Professional use, Consumer use  
Use of the substance/mixture : Leather care products

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

Putoline Oil  
Dollegoorweg 15  
7602 EC Almelo - Netherlands  
T 0031 (0)546 81 81 65  
[vib@putoline.com](mailto:vib@putoline.com)

#### 1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
United Kingdom	National Poisons Information Service (Cardiff Centre) Gwenwyn Ward, Llandough Hospital	Penarth CF64 2XX Cardiff	0344 892 0111	

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1 H222;H229  
Serious eye damage/eye irritation, Category 2 H319  
Specific target organ toxicity — Single exposure, Category 3, Narcosis H336  
Aspiration hazard, Category 1 H304  
Hazardous to the aquatic environment — Chronic Hazard, Category 3 H412  
Full text of H statements : see section 16

##### Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. May cause drowsiness or dizziness. Causes serious eye irritation. May be fatal if swallowed and enters airways. Harmful to aquatic life with long lasting effects.

# Textile Proof & Protect

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS02

GHS07

Signal word (CLP)

: Danger

Hazardous ingredients

: propan-2-ol; Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics ; Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics; n-butyl acetate

Hazard statements (CLP)

: H222 - Extremely flammable aerosol.

H229 - Pressurised container: May burst if heated.

H319 - Causes serious eye irritation.

H336 - May cause drowsiness or dizziness.

H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP)

: P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use.

P261 - Avoid breathing spray.

P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear protective gloves, eye protection.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 - Call a doctor if you feel unwell.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

EUH-statements

: EUH066 - Repeated exposure may cause skin dryness or cracking.

### 2.3. Other hazards

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
propan-2-ol	(CAS-No.) 67-63-0 (EC-No.) 200-661-7 (EC Index-No.) 603-117-00-0 (REACH-no) 01-2119457558-25	25 – 50	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	(CAS-No.) (68920-06-9) (EC-No.) 920-750-0 (REACH-no) 01-2119473851-33	10 – 25	Flam. Liq. 2, H225 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Butane substance with national workplace exposure limit(s) (GB, IE) (Note K)	(CAS-No.) 106-97-8 (EC-No.) 203-448-7 (EC Index-No.) 601-004-00-0 (REACH-no) 01-2119474691-32	10 – 25	Flam. Gas 1A, H220 Press. Gas (Comp.), H280

# Textile Proof & Protect

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Propane substance with a Community workplace exposure limit substance with national workplace exposure limit(s) (IE) (Note U)	(CAS-No.) 74-98-6 (EC-No.) 200-827-9 (EC Index-No.) 601-003-00-5 (REACH-no) 01-2119486944-21	10 – 25	Flam. Gas 1A, H220 Press. Gas (Comp.), H280
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics	(EC-No.) 927-241-2 (REACH-no) 01-2119471843-32	2,5 – 10	Flam. Liq. 3, H226 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 3, H412
n-butyl acetate substance with a Community workplace exposure limit substance with national workplace exposure limit(s) (GB, IE)	(CAS-No.) 123-86-4 (EC-No.) 204-658-1 (EC Index-No.) 607-025-00-1 (REACH-no) 01-2119485493-29	2,5 – 10	Flam. Liq. 3, H226 STOT SE 3, H336
	(CAS-No.) 1793072-86-2 (EC-No.) 938-722-1	0,1 – 1	Acute Tox. 2 (Inhalation), H330

Note K : The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w 1,3-butadiene (EINECS No 203-450-8). If the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-)P210-P403 (Table 3.1) or the S-phrases (2-)9-16 (Table 3.2) should apply. This note applies only to certain complex oil-derived substances in Part 3.

Note U (Table 3): When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case.

Full text of H-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: Call a physician immediately.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Do not induce vomiting. Call a physician immediately.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	: Eye irritation.
Symptoms/effects after ingestion	: Risk of lung oedema.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: Extremely flammable aerosol.
Explosion hazard	: Pressurised container: May burst if heated.
Hazardous decomposition products in case of fire	: Toxic fumes may be released. Incomplete combustion releases dangerous carbon monoxide, carbon dioxide and other toxic gases.

# Textile Proof & Protect

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Mechanically recover the product.  
Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. Wear personal protective equipment.  
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.  
Storage temperature : 5 – 40 °C

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### propan-2-ol (67-63-0)

#### United Kingdom - Occupational Exposure Limits

Local name	Propan-2-ol
WEL TWA (mg/m <sup>3</sup> )	999 mg/m <sup>3</sup>
WEL TWA (ppm)	400 ppm

# Textile Proof & Protect

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

WEL STEL (mg/m <sup>3</sup> )	1250 mg/m <sup>3</sup>
WEL STEL (ppm)	500 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

### Butane (106-97-8)

#### Ireland - Occupational Exposure Limits

Local name	Butane, all isomers: Butane
OEL (15 min ref) (ppm)	1000 ppm
Regulatory reference	Chemical Agents Code of Practice 2020

#### United Kingdom - Occupational Exposure Limits

Local name	Butane
WEL TWA (mg/m <sup>3</sup> )	1450 mg/m <sup>3</sup>
WEL TWA (ppm)	600 ppm
WEL STEL (mg/m <sup>3</sup> )	1810 mg/m <sup>3</sup>
WEL STEL (ppm)	750 ppm
Remark (WEL)	Carc (Capable of causing cancer and/or heritable genetic damage, only applies if Butane contains more than 0.1% of buta-1,3-diene)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

### Propane (74-98-6)

#### EU - Occupational Exposure Limits

IOELV TWA (ppm)	1000 ppm
-----------------	----------

#### Ireland - Occupational Exposure Limits

Local name	Aliphatic hydrocarbon gases Alkanes (C1-C3): Propane
Notes (IE)	Asphx. (Gaseous chemical substances which may not produce significant physiological effects in the exposed employee, but when present in high concentrations will act as simple asphyxiants)
Regulatory reference	Chemical Agents Code of Practice 2020

### n-butyl acetate (123-86-4)

#### EU - Occupational Exposure Limits

Local name	n-Butyl acetate
IOELV TWA (mg/m <sup>3</sup> )	241 mg/m <sup>3</sup>
IOELV TWA (ppm)	50 ppm
IOELV STEL (mg/m <sup>3</sup> )	723 mg/m <sup>3</sup>
IOELV STEL (ppm)	150 ppm
Regulatory reference	COMMISSION DIRECTIVE (EU) 2019/1831

#### Ireland - Occupational Exposure Limits

Local name	Butyl acetate
OEL (8 hours ref) (mg/m <sup>3</sup> )	710 mg/m <sup>3</sup>
OEL (8 hours ref) (ppm)	150 ppm
OEL (15 min ref) (mg/m <sup>3</sup> )	950 mg/m <sup>3</sup>
OEL (15 min ref) (ppm)	200 ppm

# Textile Proof & Protect

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Regulatory reference	Chemical Agents Code of Practice 2020
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	Butyl acetate
WEL TWA (mg/m <sup>3</sup> )	724 mg/m <sup>3</sup>
WEL TWA (ppm)	150 ppm
WEL STEL (mg/m <sup>3</sup> )	966 mg/m <sup>3</sup>
WEL STEL (ppm)	200 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

### 8.2. Exposure controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station.

<b>Hand protection:</b>					
Protective gloves					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Reusable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	≥ 0.35		EN ISO 374

<b>Eye protection:</b>			
Safety glasses			
Type	Use	Characteristics	Standard
Safety glasses	Droplet	clear	EN 166

<b>Skin and body protection:</b>	
Wear suitable protective clothing	

<b>Respiratory protection:</b>	
In case of insufficient ventilation, wear suitable respiratory equipment	

#### Personal protective equipment symbol(s):



#### Environmental exposure controls:

Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Aerosols.
Colour	: Colourless.
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable

# Textile Proof & Protect

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Freezing point	: No data available
Boiling point	: -44,5 °C
Flash point	: -97 °C
Critical temperature	: > 200 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Extremely flammable aerosol.
Vapour pressure	: 8300 hPa at 20 °C
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 0,697 g/cm <sup>3</sup> at 20 °C
Solubility	: Water: Insoluble / Slightly miscible
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: < 20,5 mm <sup>2</sup> /s (40 °C) - ASTM D7279
Viscosity, dynamic	: No data available
Explosive properties	: Pressurised container: May burst if heated.
Oxidising properties	: No data available
Lower explosive limit (LEL)	: 0,6 vol %
Upper explosive limit (UEL)	: 12 vol %

### 9.2. Other information

VOC content : 691,8 g/l

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

propan-2-ol (67-63-0)	
LD50 oral rat	5840 mg/kg (OECD 401 method)
LD50 dermal rabbit	16,4 ml/kg (OECD 402 method)
LC50 inhalation rat (ppm)	> 10000 ppm (ppm/6h, vapour) [OECD 403]

# Textile Proof & Protect

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics ((68920-06-9))	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2800 mg/kg
LC50 inhalation rat (Dust/Mist - mg/l/4h)	> 23 mg/l/4h

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics	
LD50 oral rat	> 5000 mg/kg (OECD 401 method)
LD50 dermal rabbit	> 5000 mg/kg (OECD 402 method)
LC50 inhalation rat (Vapours - mg/l/4h)	> 4,951 mg/l/4h (OECD 403 method)

n-butyl acetate (123-86-4)	
LD50 oral rat	10760 mg/kg
LD50 oral	10700 mg/kg bodyweight
LD50 dermal rabbit	> 14000 mg/kg
LD50 dermal	> 14100 mg/kg bodyweight
LC50 inhalation rat (mg/l)	> 20 mg/m <sup>3</sup>
LC50 inhalation rat (Dust/Mist - mg/l/4h)	> 21100 mg/l

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
Aspiration hazard	: May be fatal if swallowed and enters airways.

Textile Proof & Protect	
Vaporizer	Aerosol
Viscosity, kinematic	< 20,5 mm <sup>2</sup> /s (40 °C) - ASTM D7279

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general	: Harmful to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Harmful to aquatic life with long lasting effects.
Not rapidly degradable	

propan-2-ol (67-63-0)	
LC50 fish	9640 mg/l (Pimephales promelas, 96h) [OECD 203]
LC50 other aquatic organisms 1	> 10000 mg/l (Daphnia magna, 24h) [OECD 202]



# Textile Proof & Protect

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics

ErC50 (algae)	> 1000 mg/l Pseudokirchneriella subcapitata - 72h
---------------	---

### n-butyl acetate (123-86-4)

LC50 fish	18 mg/l (96h, Pimephales promelas)
-----------	------------------------------------

EC50 Daphnia	44 mg/l (48h, Daphnia magna)
--------------	------------------------------

EC50 other aquatic organisms 1	44 mg/l waterflea
--------------------------------	-------------------

EC50 other aquatic organisms 2	648 mg/l
--------------------------------	----------

ErC50 (algae)	647,7 mg/l (72h, Desmodesmus subspicatus)
---------------	---

### 12.2. Persistence and degradability

#### propan-2-ol (67-63-0)

Biodegradation	53 % (5d)
----------------	-----------

#### Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics ((68920-06-9))

Persistence and degradability	Readily biodegradable.
-------------------------------	------------------------

#### Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics

Persistence and degradability	Readily biodegradable.
-------------------------------	------------------------

#### n-butyl acetate (123-86-4)

Biodegradation	98 %
----------------	------

### 12.3. Bioaccumulative potential

#### propan-2-ol (67-63-0)

Partition coefficient n-octanol/water (Log Pow)	0,05
---	------

#### n-butyl acetate (123-86-4)

Partition coefficient n-octanol/water (Log Pow)	2,3
---	-----

Partition coefficient n-octanol/water (Log Kow)	1,81
---	------

### 12.4. Mobility in soil

#### Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics ((68920-06-9))

Ecology - soil	Extremely volatile.
----------------	---------------------

### 12.5. Results of PBT and vPvB assessment

#### Component

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics ((68920-06-9))	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
--	---

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics ( )	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
---	---

### 12.6. Other adverse effects

No additional information available

# Textile Proof & Protect

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods






Waste treatment methods

HP Code

- : Dispose of contents/container in accordance with licensed collector's sorting instructions.
- : HP3 - "Flammable:"
  - flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C;
  - flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air;
  - flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction;
  - flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa;
  - water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities;
  - other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste.
- HP4 - "Irritant — skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye.
- HP5 - "Specific Target Organ Toxicity (STOT)/Aspiration Toxicity:" waste which can cause specific target organ toxicity either from a single or repeated exposure, or which cause acute toxic effects following aspiration.
- HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

### SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number</b>				
UN 1950	UN 1950	UN 1950	UN 1950	UN 1950
<b>14.2. UN proper shipping name</b>				
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS
<b>Transport document description</b>				
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1	UN 1950 AEROSOLS, 2.1	UN 1950 AEROSOLS, 2.1
<b>14.3. Transport hazard class(es)</b>				
2.1	2.1	2.1	2.1	2.1
				
<b>14.4. Packing group</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.5. Environmental hazards</b>				
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No	Dangerous for the environment : No	Dangerous for the environment : No
No supplementary information available				

# Textile Proof & Protect

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 14.6. Special precautions for user

#### Overland transport

Classification code (ADR)	: 5F
Special provisions (ADR)	: 190, 327, 344, 625
Limited quantities (ADR)	: 1I
Excepted quantities (ADR)	: E0
Packing instructions (ADR)	: P207
Special packing provisions (ADR)	: PP87, RR6, L2
Mixed packing provisions (ADR)	: MP9
Transport category (ADR)	: 2
Special provisions for carriage - Packages (ADR)	: V14
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV9, CV12
Special provisions for carriage - Operation (ADR)	: S2
Tunnel restriction code (ADR)	: D

#### Transport by sea

Special provisions (IMDG)	: 63, 190, 277, 327, 344, 381, 959
Packing instructions (IMDG)	: P207, LP200
Special packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D
EmS-No. (Spillage)	: S-U
Stowage category (IMDG)	: None
Stowage and handling (IMDG)	: SW1, SW22
Segregation (IMDG)	: SG69

#### Air transport

PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provisions (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L

#### Inland waterway transport

Classification code (ADN)	: 5F
Special provisions (ADN)	: 190, 327, 344, 625
Limited quantities (ADN)	: 1 L
Excepted quantities (ADN)	: E0
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01, VE04
Number of blue cones/lights (ADN)	: 1

#### Rail transport

Classification code (RID)	: 5F
Special provisions (RID)	: 190, 327, 344, 625
Limited quantities (RID)	: 1L
Excepted quantities (RID)	: E0
Packing instructions (RID)	: P207, LP200
Special packing provisions (RID)	: PP87, RR6, L2
Mixed packing provisions (RID)	: MP9
Transport category (RID)	: 2
Special provisions for carriage – Packages (RID)	: W14
Special provisions for carriage - Loading, unloading and handling (RID)	: CW9, CW12
Colis express (express parcels) (RID)	: CE2
Hazard identification number (RID)	: 23

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

# Textile Proof & Protect

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

VOC content : 691,8 g/l  
Child-resistant fastening : Not applicable  
Tactile warning : Not applicable

Detergent Regulation : Labelling of contents (648/2004/EC):

Component	%
aliphatic hydrocarbons	≥30%

##### Directive 2012/18/EU (SEVESO III)

Seveso III Part I (Categories of dangerous substances)	Qualifying quantity (tonnes)	
	Lower-tier	Upper-tier
P3a FLAMMABLE AEROSOLS 'Flammable' aerosols Category 1 or 2, containing flammable gases Category 1 or 2 or flammable liquids Category 1	150	500

##### 15.1.2. National regulations

No additional information available

#### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

### SECTION 16: Other information

Indication of changes:			
Section	Changed item	Change	Comments
2.2	Precautionary statements (CLP)	Modified	
3	Composition/information on ingredients	Modified	
9.1	Critical temperature	Added	
9.1	Density	Modified	
9.2	VOC content	Modified	
13.1	H code	Added	
15.1	VOC content	Modified	
16	Abbreviations and acronyms	Modified	

#### Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road

# Textile Proof & Protect

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LD50	Median lethal dose
LC50	Median lethal concentration
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
STP	Sewage treatment plant
TLM	Median Tolerance Limit
SDS	Safety Data Sheet
vPvB	Very Persistent and Very Bioaccumulative
BLV	Biological limit value
CAS-No.	Chemical Abstract Service number
EC-No.	European Community number
EN	European Standard
OEL	Occupational Exposure Limit
WGK	Water Hazard Class

### Full text of H- and EUH-statements:

Acute Tox. 2 (Inhalation)	Acute toxicity (inhal.), Category 2
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
EUH066	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1A	Flammable gases, Category 1A
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3

# Textile Proof & Protect

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Press. Gas (Comp.)	Gases under pressure : Compressed gas
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.