

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Product form : Mixture
Trade name : SynMat 7GT LV
Product code : VG.20.12
Type of product : Lubricants
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against**1.2.1. Relevant identified uses**

Intended for general public
Main use category : Industrial use, Professional use, Consumer use
Use of the substance/mixture : Transmission oil

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

VatOil
Dollegoorweg 15
7602 EC Almelo - Netherlands
T 0031 (0)546 81 81 65
vib@vatoil.com

1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
United Kingdom	National Poisons Information Service (Cardiff Centre) Gwenwyn Ward, Llandough Hospital	Penarth CF64 2XX Cardiff	0344 892 0111	

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Acute toxicity (inhalation:dust,mist) Category 4 H332
Aspiration hazard, Category 1 H304
Hazardous to the aquatic environment — Chronic Hazard, Category 3 H412
Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

Harmful if inhaled. May be fatal if swallowed and enters airways. Harmful to aquatic life with long lasting effects.

SynMat 7GT LV

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS07

GHS08

Signal word (CLP) :

Danger

Contains :

Distillates (petroleum), hydrotreated heavy paraffinic; Dec-1-ene, dimers, hydrogenated; Distillates (petroleum), hydrotreated light paraffinic; Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based; Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based

Hazard statements (CLP) :

H304 - May be fatal if swallowed and enters airways.
H332 - Harmful if inhaled.
H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP) :

P101 - If medical advice is needed, have product container or label at hand.
P102 - Keep out of reach of children.
P261 - Avoid breathing mist, vapours.
P271 - Use only outdoors or in a well-ventilated area.
P273 - Avoid release to the environment.
P301+P310+P331 - IF SWALLOWED: Immediately call a doctor. Do NOT induce vomiting.
P405 - Store locked up.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

EUH-statements :

EUH208 - Contains 4,4'-thiodiethylene hydrogen -2-octadecenylsuccinate. May produce an allergic reaction.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Comments :

Highly refined mineral oils and additives.

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Distillates (petroleum), hydrotreated heavy paraffinic (Note L)	(CAS-No.) 64742-54-7 (EC-No.) 265-157-1 (EC Index-No.) 649-467-00-8 (REACH-no) 01-2119484627-25	50 – 80	Asp. Tox. 1, H304
Dec-1-ene, dimers, hydrogenated	(CAS-No.) 68649-11-6 (EC-No.) 500-228-5 (REACH-no) 01-2119493069-28	25 – 50	Acute Tox. 4 (Inhalation:dust,mist), H332 Asp. Tox. 1, H304
Oil Soluble Polyalkylene Glycol	(EC-No.) Polymer	2,5 – 5	Aquatic Chronic 3, H412
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate	(CAS-No.) 125643-61-0 (EC-No.) 406-040-9 (EC Index-No.) 607-530-00-7 (REACH-no) 01-0000015551-76	0,1 – 2,5	Aquatic Chronic 4, H413
Bis(nonylphenyl)amine	(CAS-No.) 36878-20-3 (EC-No.) 253-249-4 (REACH-no) 01-2119488911-28	0,1 – 2,5	Aquatic Chronic 4, H413

SynMat 7GT LV

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Phosphonic acid, dibutyl ester, reaction products with 2-(octylthio)- ethanol	(EC-No.) 424-820-7 (REACH-no) 01-0000017126-75	0,1 – 1	Acute Tox. 4 (Dermal), H312 Skin Corr. 1B, H314 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=10)
4,4'-thiodiethylene hydrogen -2-octadecenylsuccinate	(CAS-No.) 93882-40-7 (EC-No.) 299-434-3 (REACH-no) 01-2120735527-50	< 1	Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411

Comments : The highly refined mineral oil contains <3% (w/w) DMSOextract, according to IP346.

Note L : The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346 'Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions — Dimethyl sulphoxide extraction refractive index method', Institute of Petroleum, London. This note applies only to certain complex oil-derived substances in Part 3.

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Call a physician immediately.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.
First-aid measures after skin contact : Wash skin with plenty of water.
First-aid measures after eye contact : Rinse eyes with water as a precaution.
First-aid measures after ingestion : Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : Not expected to present a significant hazard under anticipated conditions of normal use.
Symptoms/effects after ingestion : May result in aspiration into the lungs, causing chemical pneumonia. Risk of lung oedema.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Combustible liquid.
Hazardous decomposition products in case of fire : Incomplete combustion releases dangerous carbon monoxide, carbon dioxide and other toxic gases.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid breathing dust/fume/gas/mist/vapours/spray.

SynMat 7GT LV

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Provide good ventilation in process area to prevent formation of vapour.
Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep container closed when not in use. Keep in a cool, well-ventilated place away from heat.
Storage temperature : 0 – 40 °C

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

SynMat 7GT LV

EU - Occupational Exposure Limits

Exposure limits/standards for materials that can be formed when handling this product. When mists/aerosols can occur the following is recommended	5 mg/m ³ - ACGIH TLV (inhalable fraction).
---	---

8.2. Exposure controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Materials for protective clothing:

Wear suitable protective clothing

Hand protection:

Protective gloves

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Reusable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	≥ 0.35		EN ISO 374

SynMat 7GT LV

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Eye protection:

Safety glasses

Type	Use	Characteristics	Standard
Safety glasses	Droplet	clear	EN 166

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

Personal protective equipment symbol(s):



Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Blue.
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: -57 °C - ASTM D5950 (pour point)
Boiling point	: No data available
Flash point	: 188 °C - ASTM D92 (COC)
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 0,835 kg/l (15 °C) - ASTM D4052
Solubility	: Water: Insoluble / Slightly miscible
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: 18,8 mm ² /s (40 °C) - ASTM D7279
Viscosity, dynamic	: No data available
Explosive properties	: Presents no particular fire or explosion hazard.
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

VOC content : 0 %

SynMat 7GT LV

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reacts violently with (strong) oxidizers.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

No decomposition if stored normally.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Harmful if inhaled.

SynMat 7GT LV

ATE CLP (dust,mist)	4,206 mg/l/4h
---------------------	---------------

Dec-1-ene, dimers, hydrogenated (68649-11-6)

LD50 oral rat	> 5000 mg/kg
---------------	--------------

LD50 dermal rabbit	> 3000 mg/kg
--------------------	--------------

LC50 Inhalation - Rat (Dust/Mist)	1,17 mg/l/4h
-----------------------------------	--------------

reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)

LD50 oral rat	> 2000 mg/kg (OECD 401 method)
---------------	--------------------------------

LD50 dermal rat	> 2000 mg/kg (OECD 402 method)
-----------------	--------------------------------

Phosphonic acid, dibutyl ester, reaction products with 2-(octylthio)- ethanol

LD50 oral rat	> 2000 mg/kg bodyweight
---------------	-------------------------

LD50 dermal rabbit	> 500 mg/kg bodyweight
--------------------	------------------------

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

LD50 oral rat	> 5000 mg/kg
---------------	--------------

LD50 dermal rabbit	> 2000 mg/kg
--------------------	--------------

LC50 Inhalation - Rat	> 5,53 mg/l/4h
-----------------------	----------------

SynMat 7GT LV

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

4,4'-thiodiethylene hydrogen -2-octadecenylsuccinate (93882-40-7)	
LD50 oral rat	10000 mg/kg bodyweight
LD50 dermal rabbit	3160 mg/kg bodyweight

Bis(nonylphenyl)amine (36878-20-3)	
LD50 oral rat	> 5000 mg/kg bodyweight (OECD 401 method)
LD50 dermal rat	> 2000 mg/kg bodyweight (OECD 402 method)

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: May be fatal if swallowed and enters airways.

SynMat 7GT LV	
Viscosity, kinematic	18,8 mm ² /s (40 °C) - ASTM D7279

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Harmful to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Harmful to aquatic life with long lasting effects.

Dec-1-ene, dimers, hydrogenated (68649-11-6)	
LC50 fish	> 1000 mg/l

reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)	
LC50 fish	> 100 mg/l (Oncorhynchus mykiss, 14d) (OECD 204 method)
LC50 other aquatic organisms 1	> 74 mg/l Danio rerio (zebra fish), 96h
EC50 Daphnia	> 100 mg/l (Daphnia magna, 48h) (OECD 202 method)
EC50 72h algae (1)	> 3 mg/l (Desmodesmus subspicatus, 72h) (OECD 201 method)
NOEC (acute)	≥ 3 mg/l (Desmodesmus subspicatus, 72h) (OECD 201 method)

Phosphonic acid, dibutyl ester, reaction products with 2-(octylthio)- ethanol	
LC50 fish	1,5 mg/l (Oncorhynchus mykiss, 96h, OECD 203)
EC50 Daphnia	0,09 mg/l (Daphnia magna, 48h, OECD 202)
ErC50 (algae)	0,31 mg/l (Pseudokirchneriella subcapitata, 72h, 67/548/EEG Annex V C.3)
NOEC chronic algae	0,14 mg/l (Daphnia, 21d)

SynMat 7GT LV

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LC50 fish	> 100 mg/l (Pimephales promelas, 96h) (OECD 203 method)
EC50 Daphnia	> 10000 mg/l (Gammarus pulex, 48h) (OECD 202 method)
EC50 Daphnia	> 10000 mg/l (Daphnia magna, 48h) (OECD 202 method)
NOEC (acute)	≥ 100 mg/l (Pseudokirchnerella subcapitata, 72h) (OECD 201 method)
NOEC chronic fish	≥ 1000 mg/l (Oncorhynchus mykiss - QSAR Petrotox, 14/28d)
NOEC chronic crustacea	10 mg/l (Daphnia magna, 21d) (OECD 211 method)

4,4'-thiodiethylene hydrogen -2-octadecenylsuccinate (93882-40-7)	
LC50 fish	> 1000 mg/l (Cyprinodon variegatus)
LC50 fish	> 100 mg/l (Oryzias latipes)
EC50 other aquatic organisms 1	9,5 mg/l
ErC50 (algae)	> 100 mg/l (Pseudokirchneriella subcapitata)

Bis(nonylphenyl)amine (36878-20-3)	
LC50 fish	> 100 mg/l Brachydanio rerio (zebra-fish)
EC50 Daphnia	> 100 mg/l (OECD 202 method)
EC50 72h algae (1)	> 100 mg/l
NOEC chronic crustacea	> 10 mg/l
NOEC chronic algae	> 10 mg/l

12.2. Persistence and degradability

reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)	
Persistence and degradability	Not readily biodegradable.

Phosphonic acid, dibutyl ester, reaction products with 2-(octylthio)- ethanol	
Biodegradation	52,9 % (60d, OECD 301 B)

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
Biodegradation	31 % (28d) (OECD 301F method)

4,4'-thiodiethylene hydrogen -2-octadecenylsuccinate (93882-40-7)	
Persistence and degradability	Not readily biodegradable.

Bis(nonylphenyl)amine (36878-20-3)	
Biodegradation	1 % (test concentration 20,1 mg/l)

Oil Soluble Polyalkylene Glycol	
Persistence and degradability	Not readily biodegradable.

12.3. Bioaccumulative potential

reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)	
Bioconcentration factor (BCF REACH)	260 (Oncorhynchus mykiss, 35d) (OECD 305 method)
Partition coefficient n-octanol/water (Log Pow)	9,2

SynMat 7GT LV

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

4,4'-thiodiethylene hydrogen -2-octadecenylsuccinate (93882-40-7)

Bioaccumulative potential	Bioaccumulative potential.
---------------------------	----------------------------

12.4. Mobility in soil

reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)

Ecology - soil	Product adsorbs little onto the soil.
----------------	---------------------------------------

12.5. Results of PBT and vPvB assessment

Component

reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
---	---

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.
European List of Waste (LoW) code : 13 02 06* - synthetic engine, gear and lubricating oils

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.2. UN proper shipping name				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available				

14.6. Special precautions for user

Overland transport

Not regulated

Transport by sea

Not regulated

Air transport

Not regulated

Inland waterway transport

Not regulated

SynMat 7GT LV

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Rail transport

Not regulated

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

VOC content : 0 %
Child-resistant fastening : Applicable
Tactile warning : Applicable

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes:

Section	Changed item	Change	Comments
	Revision date	Modified	
	Supersedes	Modified	
11.1	ATE CLP (dust,mist)	Modified	

Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration

SynMat 7GT LV

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
vPvB	Very Persistent and Very Bioaccumulative
BLV	Biological limit value
CAS-No.	Chemical Abstract Service number
EC-No.	European Community number
EN	European Standard
OEL	Occupational Exposure Limit
SDS	Safety Data Sheet
WGK	Water Hazard Class
STP	Sewage treatment plant
TLM	Median Tolerance Limit

Full text of H- and EUH-statements:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Aquatic Chronic 4	Hazardous to the aquatic environment — Chronic Hazard, Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Sens. 1	Skin sensitisation, Category 1
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

SynMat 7GT LV

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.
EUH208	Contains 4,4'-thiodiethylene hydrogen -2-octadecenylsuccinate. May produce an allergic reaction.

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.