

Informações sobre o produto 05.20.31

09-04-2024

Maestrol 2T Pro

Descrição

Maestrol 2T Pro is a 2-stroke (petrol) motor oil that is semi-synthetic. It is supplemented with special additives to achieve the following properties:

- Outstanding lubrication of all engine parts thanks to effective adhesion: wear is reduced and the service life of the engine is extended
- Powerful detergency, as a result of which the combustion chamber and the exhaust ports remain clear of deposits, even at high temperatures
- Almost complete combustion so that the spark plugs remain clean, ensuring optimal performance of the engine
- Excellent resistance to corrosion and wear
- Limited formation of smoke and odour
- Can also be mixed with unleaded petrol

Aplicação

Maestrol 2T Pro semi-synthetic motor oil is suitable for high speed and heavy-duty, air-cooled 2-stroke engines in mopeds, motorcycles, scooters, chainsaws, lawnmowers, generators, etc. It is also suitable for 2-stroke engines with water cooling. Can be used as a self-mixing product, or in automatic lubrication systems. Mixing ratio: 1 part oil to 50 parts fuel or use the mixing ratio recommended by the manufacturer.

Especificações

API TC

JASO FD

Típicas

| | |
|--|-------|
| Densidade a 15 °C, kg/l | 0,866 |
| Viscosidade 40 °C, mm ² /s | 38,70 |
| Viscosidade 100 °C, mm ² /s | 7,10 |
| Índice de viscosidade | 147 |
| Ponto de inflamação COC, °C | 122 |
| Ponto de fluidez, °C | -45 |
| Número de base total, mgKOH/g | 1,4 |

Embalagens disponíveis

| | | | |
|---|---|---|---|
|  |  |  |  |
| 36260 1 L bottle | 36456 Bidão de 5 l | 36733 20 L Bag in Box | 36457 Balde de 20 l |

Os dados mencionados nesta ficha informativa do produto têm a finalidade de permitir ao leitor orientar-se em relação às propriedades e possíveis aplicações dos nossos produtos. Apesar desta descrição geral ter sido redigida com o máximo de cuidado na data expressa, o compilador rejeita quaisquer responsabilidades por danos causados pela não plenitude e/ou imprecisões nestas informações, especialmente quando estes forem causados por erros ortográficos evidentes. Os termos de entrega do fornecedor aplicam-se a todos os fornecimentos de produtos. Aconselhamos o leitor a realizar a escolha final do produto, particularmente para aplicações críticas, após consultar o fornecedor. Devido à contínua pesquisa e desenvolvimento de produtos, as informações aqui contidas estão sujeitas a alterações sem notificação.