



Kroon-Oil Welding Fluid

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 16-5-2018 Revision date: 5-7-2023 Supersedes version of: 27-10-2022 Version: 1.8

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : Kroon-Oil Welding Fluid
UFI : Y34Y-A8NS-Q00H-YES4
Product code : 09.10.18
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public
Main use category : Industrial use, Professional use, Consumer use
Use of the substance/mixture : Pneumatic tools oil
Function or use category : Anti-freezing agents

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Kroon-Oil B.V
Dollegoorweg
NL- 7602 EC Almelo
Netherlands
T 0031 (0)546 81 81 65
vib@kroon-oil.nl

1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
United Kingdom	National Poisons Information Service (Cardiff Centre) University Hospital Llandough	Penlan Road CF64 2XX	0344 892 0111	Only for healthcare professionals

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Acute toxicity (oral), Category 4 H302
Serious eye damage/eye irritation, Category 2 H319
Specific target organ toxicity – Repeated exposure, Category 2 H373
Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

May cause damage to organs through prolonged or repeated exposure. Harmful if swallowed. Causes serious eye irritation.

Kroon-Oil Welding Fluid

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS07

GHS08

Signal word (CLP) :

Warning

Contains :

1,2-ethanediol

Hazard statements (CLP) :

H302 - Harmful if swallowed.

H319 - Causes serious eye irritation.

H373 - May cause damage to organs (kidneys) through prolonged or repeated exposure (if swallowed).

Precautionary statements (CLP) :

P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P260 - Do not breathe vapours, mist.

P270 - Do not eat, drink or smoke when using this product.

P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P314 - Get medical advice/attention if you feel unwell.

P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

EUH-statements :

EUH208 - Contains Benzotriazol, ar-methyl-, reaction product with formaldehyde and Diethanolamine. May produce an allergic reaction.

2.3. Other hazards

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
1,2-ethanediol substance with national workplace exposure limit(s) (GB, IE); substance with a Community workplace exposure limit	CAS-No.: 107-21-1 EC-No.: 203-473-3 EC Index-No.: 603-027-00-1 REACH-no: 01-2119456816-28	20 – 50	Acute Tox. 4 (Oral), H302 STOT RE 2, H373
Potassium 2-ethyl hexanoate	CAS-No.: 3164-85-0 EC-No.: 221-625-7 REACH-no: 01-2119980714-29; 01-2119989496-14	0,3 – 2,5	Skin Irrit. 2, H315 Eye Dam. 1, H318 Repr. 2, H361d

Kroon-Oil Welding Fluid

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Benzotriazol, ar-methyl-, reaction product with formaldehyde and Diethanolamine	CAS-No.: 1474044-75-1 EC-No.: 939-703-0	< 0,3	Acute Tox. 4 (Oral), H302 Eye Dam. 1, H318 Skin Sens. 1B, H317 Repr. 2, H361d Aquatic Chronic 3, H412

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth. Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: No additional information available.
Symptoms/effects after inhalation	: Inhalation may affect the nervous system causing headache, possibly dizziness, nausea, weakness, loss of coordination and unconsciousness.
Symptoms/effects after eye contact	: Eye irritation.
Symptoms/effects after ingestion	: Ingestion may cause nausea, vomiting and diarrhea.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

Kroon-Oil Welding Fluid

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Provide good ventilation in process area to prevent formation of vapour.
Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep container closed when not in use. Keep in a cool, well-ventilated place away from heat.
Storage temperature : 0 – 40 °C

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

1,2-ethanediol (107-21-1)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Ethylene glycol
IOEL TWA	52 mg/m ³
IOEL TWA [ppm]	20 ppm
IOEL STEL	104 mg/m ³
IOEL STEL [ppm]	40 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Ireland - Occupational Exposure Limits	
Local name	Ethane-1,2-diol [Ethylene glycol]
OEL TWA [1]	10 mg/m ³ particulate 52 mg/m ³ vapour
OEL TWA [2]	20 ppm vapour
OEL STEL	104 mg/m ³ vapour
OEL STEL [ppm]	40 ppm vapour

Kroon-Oil Welding Fluid

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

1,2-ethanediol (107-21-1)	
Remark	Sk (Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body), IOELV (Indicative Occupational Exposure Limit Values)
Regulatory reference	Chemical Agents Code of Practice 2021
United Kingdom - Occupational Exposure Limits	
Local name	Ethane-1,2-diol
WEL TWA (OEL TWA) [1]	10 mg/m ³ particulate 52 mg/m ³ vapour
WEL TWA (OEL TWA) [2]	20 ppm vapour
WEL STEL (OEL STEL)	104 mg/m ³ vapour
WEL STEL (OEL STEL) [ppm]	40 ppm vapour
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

Eye protection			
Type	Field of application	Characteristics	Standard
Safety goggles	Droplet	clear	EN 166

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Kroon-Oil Welding Fluid

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hand protection:

Protective gloves

Hand protection					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Reusable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	≥0.35		EN ISO 374

Other skin protection

Materials for protective clothing:

Wear suitable protective clothing

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Green.
Odour	: characteristic.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: -26 °C
Boiling point	: 100 – 197 °C
Flammability	: Not applicable
Explosive properties	: Presents no particular fire or explosion hazard.
Explosive limits	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: Derived from flash point MEG (CAS: 107-21-1): 111 °C. Because of the presence of water, a flashpoint cannot be measured.
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: 8,2
Viscosity, kinematic	: Not available
Solubility	: Water: Miscible in all proportions
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: 1,068 kg/l (15 °C) - ASTM D4052
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

Kroon-Oil Welding Fluid

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

9.2.2. Other safety characteristics

VOC content : 0 %

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

No decomposition if stored normally.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Harmful if swallowed.
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Kroon-Oil Welding Fluid	
ATE CLP (oral)	1188,911 mg/kg bodyweight
Benzotriazol, ar-methyl-, reaction product with formaldehyde and Diethanolamine (1474044-75-1)	
LD50 oral rat	1472 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 1104 - 2298
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal)), Guideline: EPA OPPTS 870.1200 (Acute Dermal Toxicity), Guideline: other:
1,2-ethanediol (107-21-1)	
LD50 oral rat	7712 mg/kg bodyweight
LD50 oral	There is a marked difference in acute oral toxicity between rodents and man, man being more susceptible than rodents. The estimated fatal dose for man is 30-100 milliliters. This material has also been shown to be toxic and potentially lethal by ingestion to cats and dogs.
LD50 dermal	3500 mg/kg bodyweight mouse
LC50 Inhalation - Rat	> 2,5 mg/l
Potassium 2-ethyl hexanoate (3164-85-0)	
LD50 oral	2400 – 2400 mg/kg bodyweight Animal: other:, Remarks on results: other:

Kroon-Oil Welding Fluid

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Potassium 2-ethyl hexanoate (3164-85-0)	
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
Skin corrosion/irritation	: Not classified pH: 8,2
Serious eye damage/irritation	: Causes serious eye irritation. pH: 8,2
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

1,2-ethanediol (107-21-1)	
NOAEL (chronic, oral, animal/male, 2 years)	1500 mg/kg bodyweight Animal: mouse, Animal sex: male, Remarks on results: other:Effect type: carcinogenicity (migrated information)
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: May cause damage to organs (kidneys) through prolonged or repeated exposure (if swallowed).

1,2-ethanediol (107-21-1)	
STOT-repeated exposure	May cause damage to organs (kidneys) through prolonged or repeated exposure (if swallowed).

Potassium 2-ethyl hexanoate (3164-85-0)	
NOAEL (subchronic, oral, animal/male, 90 days)	180 mg/kg bodyweight Animal: mouse, Animal sex: male, Guideline: other:
NOAEL (subchronic, oral, animal/female, 90 days)	205 mg/kg bodyweight Animal: mouse, Animal sex: female, Guideline: other:
Aspiration hazard	: Not classified

Benzotriazol, ar-methyl-, reaction product with formaldehyde and Diethanolamine (1474044-75-1)	
Viscosity, kinematic	118,148 mm ² /s

1,2-ethanediol (107-21-1)	
Viscosity, kinematic	14,505 mm ² /s

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

Benzotriazol, ar-methyl-, reaction product with formaldehyde and Diethanolamine (1474044-75-1)	
LC50 - Fish [1]	134,2 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
LC50 - Fish [2]	135 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 - Crustacea [1]	80 mg/l Test organisms (species): Daphnia magna
EC50 - Crustacea [2]	83 mg/l Test organisms (species): Daphnia magna

Kroon-Oil Welding Fluid

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Benzotriazol, ar-methyl-, reaction product with formaldehyde and Diethanolamine (1474044-75-1)	
EC50 72h - Algae [1]	29 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
EC50 72h - Algae [2]	16,7 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
1,2-ethanediol (107-21-1)	
LC50 - Fish [1]	72860 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	> 100 mg/l Test organisms (species): Daphnia magna
EC50 96h - Algae [1]	3536 mg/l Test organisms (species): other:greenn algae
EC50 96h - Algae [2]	6500 – 13000 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
NOEC (chronic)	≥ 1000 mg/l Test organisms (species): Americamysis bahia (previous name: Mysidopsis bahia) Duration: '23 d'
Potassium 2-ethyl hexanoate (3164-85-0)	
LC50 - Fish [1]	> 100 mg/l Test organisms (species): Oryzias latipes
EC50 - Crustacea [1]	910 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	49,3 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
LOEC (chronic)	63 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	25 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

12.2. Persistence and degradability

Kroon-Oil Welding Fluid	
Persistence and degradability	Biodegradable.
1,2-ethanediol (107-21-1)	
Biodegradation	90 % > 10d (OECD 301A method)

12.3. Bioaccumulative potential

Benzotriazol, ar-methyl-, reaction product with formaldehyde and Diethanolamine (1474044-75-1)	
Partition coefficient n-octanol/water (Log Pow)	-1,73 – 1,73
1,2-ethanediol (107-21-1)	
Partition coefficient n-octanol/water (Log Kow)	-1,36

12.4. Mobility in soil

1,2-ethanediol (107-21-1)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

Kroon-Oil Welding Fluid

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods	: Do not allow into drains or water courses. Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.
European List of Waste (LoW) code	: 16 01 14* - antifreeze fluids containing dangerous substances
HP Code	: HP3 - "Flammable:" – flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C; – flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air; – flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction; – flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa; – water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities; – other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste. HP5 - "Specific Target Organ Toxicity (STOT)/Aspiration Toxicity:" waste which can cause specific target organ toxicity either from a single or repeated exposure, or which cause acute toxic effects following aspiration. HP6 - "Acute Toxicity:" waste which can cause acute toxic effects following oral or dermal administration, or inhalation exposure.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.2. UN proper shipping name				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available				

14.6. Special precautions for user

Overland transport

Not regulated

Kroon-Oil Welding Fluid

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Transport by sea

Not regulated

Air transport

Not regulated

Inland waterway transport

Not regulated

Rail transport

Not regulated

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

VOC Directive (2004/42)

VOC content : 0 %

Biocide Regulation (528/2012)

Child-resistant fastening : Not applicable

Tactile warning : Applicable

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

Kroon-Oil Welding Fluid

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 16: Other information

Indication of changes			
Section	Changed item	Change	Comments
	Revision date	Modified	
	Supersedes	Modified	
9.1	Flash point	Added	
9.1	Boiling point	Added	

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit

Kroon-Oil Welding Fluid

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Full text of H- and EUH-statements:	
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
EUH208	Contains Benzotriazol, ar-methyl-, reaction product with formaldehyde and Diethanolamine. May produce an allergic reaction.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1B	Skin sensitisation, category 1B
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.