

产品信息 01.20.68

04-07-2025

Dieselfleet Super G 15W-50

说明

This modern, universal applicable engine oil is produced with high quality solvent refined base oils and a well-balanced choice of additives. This multigrade engine oil has the following properties:

- a very good detergency prevents deposits in the engine
- a very good dispersion that prevents from precipitation and sludge
- a powerful action against corrosion and foam
- a high and stable viscosity index
- a low sulphated ash content
- a powerful activity against wear resulting in strongly reduced wear of piston-rings and cylinder-liners

应用

This universal engine oil is suitable for the lubrication of gasoline and diesel engines, with or without turbo-loading, under heavy operating conditions and all the year round. This oil is excellent suitable for mixed fleets and can be applied in e.g. Euro 3 and Euro 4 engines. Due to its special composition longer drain intervals are possible with this motor oil.

规格

ACEA A3/B4, E7

API CI-4/SL

DTFR 15B110

典型

15 °C 时密度, kg/l 0,867

粘度 -20 °C, mPa.s 6000

粘度 40 °C, mm²/s 134,00粘度 100 °C, mm²/s 17,50

粘度指数 144

闪点 COC, °C 215

流点, °C -33

总碱值, mgKOH/g 11,1

灰分, % 1,45

包装规格



35737

200 升圆桶装