

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Issue date: 20-9-2018 Revision date: 6-1-2023 Supersedes version of: 17-10-2022 Version: 2.4

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

 Trade name
 : Kroon-Oil PTO MoS2

 UFI
 : EM30-U0E8-400P-F5SP

Product code : 09.20.09
Type of product : Lubricants
Vaporizer : Aerosol
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public

Main use category : Industrial use, Professional use, Consumer use

Use of the substance/mixture : Penetrating oil Function or use category : Lubricant

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Kroon Oil BV B.V.
Dollegoorweg, 15
NL- 7602 EC Almelo
Netherlands
T 0031 (0)546 81 81 65
vib@kroon-oil.nl

1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
United Kingdom	National Poisons Information Service (Cardiff Centre) University Hospital Llandough	Penlan Road CF64 2XX Cardiff	0344 892 0111	Only for healthcare professionals

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1 H222;H229
Aspiration hazard, Category 1 H304

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. May be fatal if swallowed and enters airways.

6-1-2023 (Revision date) EN (English) 1/14

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS02

Signal word (CLP) : Danger

Hazard statements (CLP) : H222 - Extremely flammable aerosol.

H229 - Pressurised container: May burst if heated.

Precautionary statements (CLP) : P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

: EUH066 - Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

FUH-statements

Contains no PBT/vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Butane substance with national workplace exposure limit(s) (GB, IE) (Note K)	CAS-No.: 106-97-8 EC-No.: 203-448-7 EC Index-No.: 601-004-00-0 REACH-no: 01-2119474691- 32	25 – 50	Flam. Gas 1A, H220 Press. Gas (Comp.), H280
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics substance with national workplace exposure limit(s) (GB)	CAS-No.: 1174522-09-8 EC-No.: 918-481-9 REACH-no: 01-2119457273- 39	25 – 50	Asp. Tox. 1, H304 EUH066
Propane substance with a Community workplace exposure limit (Note U)	CAS-No.: 74-98-6 EC-No.: 200-827-9 EC Index-No.: 601-003-00-5 REACH-no: 01-2119486944- 21	2,5 – 10	Flam. Gas 1A, H220 Press. Gas (Comp.), H280
isobutane substance with national workplace exposure limit(s) (IE) (Note K)	CAS-No.: 75-28-5 EC-No.: 200-857-2 REACH-no: 01-2119485395- 27	2,5 – 10	Flam. Gas 1A, H220 Press. Gas (Comp.), H280

6-1-2023 (Revision date) EN (English) 2/14

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Specific concentration limits:			
Name	Product identifier	Specific concentration limits	
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	CAS-No.: 1174522-09-8 EC-No.: 918-481-9 REACH-no: 01-2119457273- 39	(25 ≤C < 100) EUH066	

Note K: The harmonised classification as a carcinogen or mutagen applies unless it can be shown that the substance contains less than 0.1 % w/w 1,3- butadiene (Einecs No 203-450-8), in which case a classification in accordance with Title II of this Regulation shall be performed also for those hazard classes. Where the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-)P210-P403 shall

Note U (Table 3): When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned: Press. Gas (Comp.), Press. Gas (Liq.), Press. Gas (Ref. Liq.), Press. Gas (Diss.). Aerosols shall not be classified as gases under pressure (See Annex I, Part 2, Section 2.3.2.1, Note 2)

Product subject to CLP Article 1.1.3.7. The disclosure rules of the components is modified in this case.

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Call a physician immediately.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Wash skin with plenty of water.

First-aid measures after eye contact : Rinse eyes with water as a precaution.

First-aid measures after ingestion : Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact : Repeated exposure may cause skin dryness or cracking.

Symptoms/effects after ingestion : Risk of lung oedema.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol, Combustible liquid.

Explosion hazard : Pressurised container: May burst if heated.

Hazardous decomposition products in case of fire Toxic fumes may be released. Incomplete combustion releases dangerous carbon

monoxide, carbon dioxide and other toxic gases.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus. Complete protective clothing.

6-1-2023 (Revision date) EN (English) 3/14

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Mechanically recover the product.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Do not spray on an open flame or other ignition source. Do not pierce or burn, even after

use.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the

product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked

up. Store in a well-ventilated place. Keep cool.

Storage temperature : $< 40 \, ^{\circ}\text{C}$

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Kroon-Oil PTO MoS2		
EU - Indicative Occupational Exposure Limit (IOEL)		
Exposure limits/standards for materials that can be formed when handling this product. When mists/aerosols can occur the following is recommended 5 mg/m³ - ACGIH TLV (inhalable fraction).		
Butane (106-97-8)		
Ireland - Occupational Exposure Limits		
Local name Butane, all isomers: Butane		

6-1-2023 (Revision date) EN (English) 4/14

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

DEL STEL [pm] 1000 pm Regulatory reference 1chemical Agents Code of Practice 2021 United Kingdom - Occupational Exposure Limits Local name Butane 8 Butane WEL TWA (OEL TWA) [1] 1450 mg/m² WEL TWA (OEL TWA) [2] 600 pm WEL STEL (OEL STEL) 1810 mg/m² WEL STEL (OEL STEL) 1810 mg/m² WEL STEL (OEL STEL) 19pm] 750 ppm Remark Care (Capable of causing cancer and/or heritable genetic damage, only applies if Butane contains more than 0.1% of buta-1,3-diene) Regulatory reference EH40/2005 (Fourth edition, 2020). HSE Propane (74-98-6) EU - Indicative Occupational Exposure Limits (IOEL TWA) [pm] 1000 ppm Ireland - Occupational Exposure Limits (IOEL TWA) [pm] 1000 ppm Ireland - Occupational Exposure Limits (IOEL TWA) [pm] 24,000 ppm Regulatory reference Aphr. (Gaseous chemical substances which may not produce significant physiological effects in the exposed employee, but when present in high concentrations will act as simple asphyxiants) Regulatory reference Butane, all isomers: Isobutane OEL STEL [pm] 1000 ppm Regulatory reference Butane, all isomers: Isobutane OEL STEL [pm] 1000 ppm Regulatory reference Chemical Agents Code of Practice 2021 Hydrocarbons, C10-C13, nalkanes, isoalkarus-tyclics, < 2% aromatics (1174522-09-8) United Kingdom - Occupational Exposure Limits United Kingdom - Occupational Exposure Limits WEL TWA (OEL TWA) [1] 1200 mg/m² WEL TWA (OEL TWA) [2] 184 ppm				
Regulatory reference Chemical Agents Code of Practice 2021 United Kingdom - Occupational Exposure Limits Local name Butane WEL TWA (OEL TWA) [1] 1450 mg/m³ WEL TWA (OEL TWA) [2] 600 ppm WEL STEL (OEL STEL) 1810 mg/m³ WEL STEL (OEL STEL) 1750 ppm Remark Care (Capable of causing cancer and/or heritable genetic damage, only applies if Butane contains more than 0.1% of buta-1,3-diene) Regulatory reference EH40/2005 (Fourth edition, 2020). HSE Propane (74-98-6) EU - Indicative Occupational Exposure Limit (IOEL) IOEL TWA (ppm] 1000 ppm Ireland - Occupational Exposure Limit (IOEL) Local name Aliphatic hydrocarbon gases Alkanes (C1-C3): Propane Remark Asphx. (Gaseous chemical substances which may not produce significant physiological effects in the exposed employee, but when present in high concentrations will act as simple asphyxiants) Regulatory reference Chemical Agents Code of Practice 2021 Isobutane (75-28-5) Ireland - Occupational Exposure Limits Local name Butane, all isomers: Isobutane OEL STEL (ppm] 1000 ppm Regulatory reference Chemical Agents Code of Practice 2021 Hydrocarbons, C10-C13, n-alkanes, isoalkanes cyclics, < 2% aromatics (1174522-09-8) United Kingdom - Occupational Exposure Limits United Kingdom - Occupational Exposure Limits WEL TWA (OEL TWA) [1] 1200 mg/m²	Butane (106-97-8)			
United Kingdom - Occupational Exposure Limits Local name Butane WEL TWA (OEL TWA) [1] 1450 mg/m² WEL TWA (OEL TWA) [2] 600 ppm WEL STEL (OEL STEL) 1810 mg/m² WEL STEL (OEL STEL) 5750 ppm Remark Carc (Capable of causing cancer and/or heritable genetic damage, only applies if Butane contains more than 0.1% of buta-1,3-diene) Regulatory reference EH40/2005 (Fourth edition, 2020). HSE Propane (74-98-6) EU - Indicative Occupational Exposure Limit (IOEL) IOEL TWA (ppm) 1000 ppm Ireland - Occupational Exposure Limit (Security of Endition) Regulatory reference Aliphatic hydrocarbon gases Alkanes (C1-C3): Propane Remark Asphx, (Gaseous chemical substances which may not produce significant physiological effects in the exposed employee, but when present in high concentrations will act as simple asphyxiants) Regulatory reference Chemical Agents Code of Practice 2021 isobutane (75-28-5) Ireland - Occupational Exposure Limits Local name Butane, all isomers: Isobutane OEL STEL (ppm) 1000 ppm Regulatory reference Chemical Agents Code of Practice 2021 Hydrocarbons, C10-C13, n-alkanes, isoalkanes cyclics, < 2% aromatics (1174522-09-8) United Kingdom - Occupational Exposure Limits WEL TWA (OEL TWA) [1] 1200 mg/m²	OEL STEL [ppm]	1000 ppm		
Local name Butane WEL TWA (OEL TWA) [1] 1450 mg/m² WEL TWA (OEL TWA) [2] 600 ppm WEL STEL (OEL STEL) 1810 mg/m² WEL STEL (OEL STEL) [ppm] 750 ppm Remark Carc (Capable of causing cancer and/or heritable genetic damage, only applies if Butane contains more than 0.1% of buta-1,3-diene) Regulatory reference EH40/2005 (Fourth edition, 2020). HSE Propane (74-98-6) EU - Indicative Occupational Exposure Limit (IOEL) IOEL TWA [ppm] 1000 ppm Ireland - Occupational Exposure Limits Local name Aliphatic hydrocarbon gases Alkanes (C1-C3): Propane Remark Asphx. (Gaseous chemical substances which may not produce significant physiological effects in the exposed employee, but when present in high concentrations will act as simple asphyxiants) Regulatory reference Chemical Agents Code of Practice 2021 Ireland - Occupational Exposure Limits Local name Butane, all isomers: Isobutane OEL STEL [ppm] 1000 ppm Regulatory reference Chemical Agents Code of Practice 2021 Hydrocarbons, C10-C13, n-alkanes, isoalkanes, isoalkanes, cyclics, < 2% aromatics (1174522-09-8)	Regulatory reference	Chemical Agents Code of Practice 2021		
WEL TWA (OEL TWA) [1] 1450 mg/m² WEL TWA (OEL TWA) [2] 600 ppm WEL STEL (OEL STEL) 1810 mg/m² WEL STEL (OEL STEL) [ppm] 750 ppm Remark Carc (Capable of causing cancer and/or heritable genetic damage, only applies if Butane contains more than 0.1% of buta-1,3-diene) Regulatory reference EH40/2005 (Fourth edition, 2020), HSE Propane (74-98-6) EU - Indicative Occupational Exposure Limit (IOEL) IOEL TWA (ppm] 1000 ppm Ireland - Occupational Exposure Limits Local name Aliphatic hydrocarbon gases Alkanes (C1-C3): Propane Regulatory reference Asphx, (Gaseous chemical substances which may not produce significant physiological effects in the exposed employee, but when present in high concentrations will act as simple asphyxiants) Regulatory reference Chemical Agents Code of Practice 2021 Isobutane (75-28-5) Ireland - Occupational Exposure Limits Local name Butane, all isomers: Isobutane OEL STEL (ppm] 1000 ppm Regulatory reference Chemical Agents Code of Practice 2021 Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics (1174522-09-8) United Kingdom - Occupational Exposure Limits WEL TWA (OEL TWA) [1] 1200 mg/m²	United Kingdom - Occupational Exposure Limits			
WEL TWA (OEL TWA) [2] 600 ppm WEL STEL (OEL STEL) 1810 mg/m² WEL STEL (OEL STEL) [ppm] 750 ppm Remark Carc (Capable of causing cancer and/or heritable genetic damage, only applies if Butane contains more than 0.1% of buta-1,3-diene) Regulatory reference EH40/2005 (Fourth edition, 2020). HSE Propane (74-98-6) EU - Indicative Occupational Exposure Limit (IOEL TWA) [ppm] 1000 ppm Ireland - Occupational Exposure Limits Local name Aliphatic hydrocarbon gases Alkanes (C1-C3). Propane Remark Asphx. (Gaseous chemical substances which may not produce significant physiological effects in the exposed employee, but when present in high concentrations will act as simple asphyxiants) Regulatory reference Chemical Agents Code of Practice 2021 Isobutane (75-28-5) Ireland - Occupational Exposure Limits Local name Butane, all isomers: Isobutane OEL STEL [ppm] 1000 ppm Regulatory reference Chemical Agents Code of Practice 2021 Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics (1174522-09-8) United Kingdom - Occupational Exposure Limits WEL TWA (OEL TWA) [1] 1200 mg/m²	Local name	Butane		
WEL STEL (OEL STEL) 1810 mg/m³ WEL STEL (OEL STEL) [ppm] 750 ppm Remark Carc (Capable of causing cancer and/or heritable genetic damage, only applies if Butane contains more than 0.1% of buta-1,3-diene) Regulatory reference EH40/2005 (Fourth edition, 2020). HSE Propane (74-98-6) EU - Indicative Occupational Exposure Limit (IOEL) IOEL TWA [ppm] 1000 ppm Ireland - Occupational Exposure Limits Local name Aliphatic hydrocarbon gases Alkanes (C1-C3): Propane Remark Asphx. (Gaseous chemical substances which may not produce significant physiological effects in the exposed employee, but when present in high concentrations will act as simple asphyxiants) Regulatory reference Chemical Agents Code of Practice 2021 isobutane (75-28-5) ireland - Occupational Exposure Limits Local name Butane, all isomers: Isobutane OEL STEL [ppm] 1000 ppm Regulatory reference Chemical Agents Code of Practice 2021 Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics (1174522-09-8) United Kingdom - Occupational Exposure Limits WEL TWA (OEL TWA) [1] 1200 mg/m³	WEL TWA (OEL TWA) [1]	1450 mg/m³		
WEL STEL (OEL STEL) [ppm] 750 ppm Remark Carc (Capable of causing cancer and/or heritable genetic damage, only applies if Butane contains more than 0.1% of buta-1,3-diene) Regulatory reference EH40/2005 (Fourth edition, 2020). HSE Propane (74-98-6) EU - Indicative Occupational Exposure Limit (IOEL) IOEL TWA [ppm] 1000 ppm Ireland - Occupational Exposure Limits Local name Aliphatic hydrocarbon gases Alkanes (C1-C3): Propane Remark Asphx. (Gaseous chemical substances which may not produce significant physiological effects in the exposed employee, but when present in high concentrations will act as simple asphyxiants) Regulatory reference Chemical Agents Code of Practice 2021 isobutane (75-28-5) Ireland - Occupational Exposure Limits Local name Butane, all isomers: Isobutane OEL STEL [ppm] 1000 ppm Regulatory reference Chemical Agents Code of Practice 2021 Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics (1174522-09-8) United Kingdom - Occupational Exposure Limits WEL TWA (OEL TWA) [1] 1200 mg/m³	WEL TWA (OEL TWA) [2]	600 ppm		
Remark Carc (Capable of causing cancer and/or heritable genetic damage, only applies if Butane contains more than 0.1% of buta-1,3-diene) Regulatory reference EH40/2005 (Fourth edition, 2020). HSE Propane (74-98-6) EU - Indicative Occupational Exposure Limit (IOEL) IOEL TWA [ppm] 1000 ppm Ireland - Occupational Exposure Limits Local name Aliphatic hydrocarbon gases Alkanes (C1-C3): Propane Remark Asphx. (Gaseous chemical substances which may not produce significant physiological effects in the exposed employee, but when present in high concentrations will act as simple asphyxiants) Regulatory reference Chemical Agents Code of Practice 2021 isobutane (75-28-5) ireland - Occupational Exposure Limits Local name Butane, all isomers: Isobutane OEL STEL [ppm] 1000 ppm Regulatory reference Chemical Agents Code of Practice 2021 Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics (1174522-09-8) United Kingdom - Occupational Exposure Limits United TWA (OEL TWA) [1] 1200 mg/m³	WEL STEL (OEL STEL)	1810 mg/m³		
contains more than 0.1% of buta-1,3-diene) Regulatory reference EH40/2005 (Fourth edition, 2020). HSE Propane (74-98-6) EU - Indicative Occupational Exposure Limit (IOEL) IOEL TWA [ppm] 1000 ppm Ireland - Occupational Exposure Limits Local name Aliphatic hydrocarbon gases Alkanes (C1-C3): Propane Remark Asphx. (Gaseous chemical substances which may not produce significant physiological effects in the exposed employee, but when present in high concentrations will act as simple asphyxiants) Regulatory reference Chemical Agents Code of Practice 2021 Ireland - Occupational Exposure Limits Local name Butane, all isomers: Isobutane OEL STEL [ppm] 1000 ppm Regulatory reference Chemical Agents Code of Practice 2021 Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics (1174522-09-8)	WEL STEL (OEL STEL) [ppm]	750 ppm		
Propane (74-98-6) EU - Indicative Occupational Exposure Limit (IOEL) IOEL TWA [ppm] 1000 ppm Ireland - Occupational Exposure Limits Local name Aliphatic hydrocarbon gases Alkanes (C1-C3): Propane Remark Asphx. (Gaseous chemical substances which may not produce significant physiological effects in the exposed employee, but when present in high concentrations will act as simple asphyxiants) Regulatory reference Chemical Agents Code of Practice 2021 isobutane (75-28-5) Ireland - Occupational Exposure Limits Local name Butane, all isomers: Isobutane OEL STEL [ppm] 1000 ppm Regulatory reference Chemical Agents Code of Practice 2021 Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics (1174522-09-8) United Kingdom - Occupational Exposure Limits WEL TWA (OEL TWA) [1] 1200 mg/m³	Remark			
EU - Indicative Occupational Exposure Limit (IOEL) IOEL TWA [ppm] 1000 ppm Ireland - Occupational Exposure Limits Local name Aliphatic hydrocarbon gases Alkanes (C1-C3): Propane Remark Asphx. (Gaseous chemical substances which may not produce significant physiological effects in the exposed employee, but when present in high concentrations will act as simple asphyxiants) Regulatory reference Chemical Agents Code of Practice 2021 Isobutane (75-28-5) Ireland - Occupational Exposure Limits Local name Butane, all isomers: Isobutane OEL STEL [ppm] 1000 ppm Regulatory reference Chemical Agents Code of Practice 2021 Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics (1174522-09-8) United Kingdom - Occupational Exposure Limits WEL TWA (OEL TWA) [1] 1200 mg/m³	Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE		
IOEL TWA [ppm] 1000 ppm Ireland - Occupational Exposure Limits Local name Aliphatic hydrocarbon gases Alkanes (C1-C3): Propane Remark Asphx. (Gaseous chemical substances which may not produce significant physiological effects in the exposed employee, but when present in high concentrations will act as simple asphyxiants) Regulatory reference Chemical Agents Code of Practice 2021 Ireland - Occupational Exposure Limits Local name Butane, all isomers: Isobutane OEL STEL [ppm] 1000 ppm Regulatory reference Chemical Agents Code of Practice 2021 Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics (1174522-09-8) United Kingdom - Occupational Exposure Limits WEL TWA (OEL TWA) [1] 1200 mg/m³	Propane (74-98-6)			
Ireland - Occupational Exposure Limits Local name Aliphatic hydrocarbon gases Alkanes (C1-C3): Propane Remark Asphx. (Gaseous chemical substances which may not produce significant physiological effects in the exposed employee, but when present in high concentrations will act as simple asphyxiants) Regulatory reference Chemical Agents Code of Practice 2021 Ireland - Occupational Exposure Limits Local name Butane, all isomers: Isobutane OEL STEL [ppm] 1000 ppm Regulatory reference Chemical Agents Code of Practice 2021 Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics (1174522-09-8) United Kingdom - Occupational Exposure Limits WEL TWA (OEL TWA) [1] 1200 mg/m³	EU - Indicative Occupational Exposure Limit (IOEL)			
Local name Aliphatic hydrocarbon gases Alkanes (C1-C3): Propane Remark Asphx. (Gaseous chemical substances which may not produce significant physiological effects in the exposed employee, but when present in high concentrations will act as simple asphyxiants) Regulatory reference Chemical Agents Code of Practice 2021 Ireland - Occupational Exposure Limits Local name Butane, all isomers: Isobutane OEL STEL [ppm] 1000 ppm Regulatory reference Chemical Agents Code of Practice 2021 Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics (1174522-09-8) United Kingdom - Occupational Exposure Limits WEL TWA (OEL TWA) [1] 1200 mg/m³	IOEL TWA [ppm]	1000 ppm		
Remark Asphx. (Gaseous chemical substances which may not produce significant physiological effects in the exposed employee, but when present in high concentrations will act as simple asphyxiants) Regulatory reference Chemical Agents Code of Practice 2021 Ireland - Occupational Exposure Limits Local name Butane, all isomers: Isobutane OEL STEL [ppm] 1000 ppm Regulatory reference Chemical Agents Code of Practice 2021 Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics (1174522-09-8) United Kingdom - Occupational Exposure Limits WEL TWA (OEL TWA) [1] 1200 mg/m³	Ireland - Occupational Exposure Limits			
effects in the exposed employee, but when present in high concentrations will act as simple asphyxiants) Regulatory reference Chemical Agents Code of Practice 2021 Ireland - Occupational Exposure Limits Local name Butane, all isomers: Isobutane OEL STEL [ppm] Regulatory reference Chemical Agents Code of Practice 2021 Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics (1174522-09-8) United Kingdom - Occupational Exposure Limits WEL TWA (OEL TWA) [1] 1200 mg/m³	Local name	Aliphatic hydrocarbon gases Alkanes (C1-C3): Propane		
isobutane (75-28-5) Ireland - Occupational Exposure Limits Local name Butane, all isomers: Isobutane OEL STEL [ppm] 1000 ppm Regulatory reference Chemical Agents Code of Practice 2021 Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics (1174522-09-8) United Kingdom - Occupational Exposure Limits WEL TWA (OEL TWA) [1] 1200 mg/m³	Remark	effects in the exposed employee, but when present in high concentrations will act as		
Ireland - Occupational Exposure Limits Local name Butane, all isomers: Isobutane OEL STEL [ppm] 1000 ppm Regulatory reference Chemical Agents Code of Practice 2021 Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics (1174522-09-8) United Kingdom - Occupational Exposure Limits WEL TWA (OEL TWA) [1] 1200 mg/m³	Regulatory reference	Chemical Agents Code of Practice 2021		
Local name DEL STEL [ppm] Regulatory reference Chemical Agents Code of Practice 2021 Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics (1174522-09-8) United Kingdom - Occupational Exposure Limits WEL TWA (OEL TWA) [1] 1200 mg/m³	isobutane (75-28-5)			
OEL STEL [ppm] 1000 ppm Regulatory reference Chemical Agents Code of Practice 2021 Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics (1174522-09-8) United Kingdom - Occupational Exposure Limits WEL TWA (OEL TWA) [1] 1200 mg/m³	Ireland - Occupational Exposure Limits			
Regulatory reference Chemical Agents Code of Practice 2021 Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics (1174522-09-8) United Kingdom - Occupational Exposure Limits WEL TWA (OEL TWA) [1] 1200 mg/m³	Local name	Butane, all isomers: Isobutane		
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics (1174522-09-8) United Kingdom - Occupational Exposure Limits WEL TWA (OEL TWA) [1] 1200 mg/m³	OEL STEL [ppm]	1000 ppm		
United Kingdom - Occupational Exposure Limits WEL TWA (OEL TWA) [1] 1200 mg/m³	Regulatory reference	Chemical Agents Code of Practice 2021		
WEL TWA (OEL TWA) [1] 1200 mg/m³	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics (1174522-09-8)			
	United Kingdom - Occupational Exposure Limits			
WEL TWA (OEL TWA) [2] 184 ppm	WEL TWA (OEL TWA) [1]	1200 mg/m³		
	WEL TWA (OEL TWA) [2]	184 ppm		

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

6-1-2023 (Revision date) 6-1-2023 (Printing date) EN (English) 5/14

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):







8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

Eye protection			
Туре	Field of application	Characteristics	Standard
Safety glasses	Droplet	clear	EN 166

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

Hand protection					
Туре	Material	Permeation	Thickness (mm)	Penetration	Standard
Reusable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	≥0.35		EN ISO 374

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Respiratory protection			
Device	Filter type	Condition	Standard
Self-contained breathing apparatus (SCBA)	Type AX - Low-boiling (<65 °C) organic compounds, Type P2		

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Colour : Light grey.

6-1-2023 (Revision date) EN (English) 6/14 6-1-2023 (Printing date)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Appearance : Aerosol. Odour : characteristic. Odour threshold Not available Melting point Not applicable Freezing point : Not available Boiling point -44,5 °C

Flammability Extremely flammable aerosol.

Explosive properties Pressurised container: May burst if heated.

Explosive limits : Not available : 0,7 vol % Lower explosion limit Upper explosion limit : 8,5 vol % -60 °C Flash point Not available Auto-ignition temperature Decomposition temperature : Not available рΗ : Not available Viscosity, kinematic $< 20.5 \text{ mm}^2/\text{s}$

Solubility : Water: Insoluble / Slightly miscible

Partition coefficient n-octanol/water (Log Kow) : Not available : 2100 hPa @20°C Vapour pressure Vapour pressure at 50°C : Not available Density : 0,695 g/cm3 at 20 °C Relative density : Not available Relative vapour density at 20°C : Not available Particle characteristics : Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

: 119.999999999996 % of flammable ingredients

Critical temperature : 236 °C

9.2.2. Other safety characteristics

VOC content : 487,2 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use. Reacts violently with (strong) oxidizers.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

6-1-2023 (Revision date) EN (English) 7/14

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified Acute toxicity (dermal) Not classified Acute toxicity (inhalation) Not classified

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics (1174522-09-8)		
LD50 oral rat > 5000 mg/kg (OESO 401)		
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)	
LD50 dermal rabbit	≥ 3160 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)	
LC50 Inhalation - Rat > 4,951 g/m³ (4h, OESO 403)		

Skin corrosion/irritation : Not classified Serious eye damage/irritation : Not classified Respiratory or skin sensitisation : Not classified Germ cell mutagenicity : Not classified : Not classified Carcinogenicity Reproductive toxicity : Not classified STOT-single exposure : Not classified STOT-repeated exposure : Not classified

Aspiration hazard : May be fatal if swallowed and enters airways.

Kroon-Oil PTO MoS2	
Vaporizer	Aerosol
Viscosity, kinematic	< 20,5 mm²/s

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics (1174522-09-8)	
Viscosity, kinematic	1,8 mm²/s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm²/s)'

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse

effects in the environment.

Hazardous to the aquatic environment, short-term

(acute)

: Not classified

Hazardous to the aquatic environment, long-term

: Not classified

(chronic)

Not rapidly degradable

· · · · · · · · · · · · · · · · · · ·		
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics (1174522-09-8)		
LC50 - Fish [1] > 1001 mg/l (OECD 203 method)		
EC50 - Crustacea [1]	> 1000 mg/l (OECD 202 method)	
EC50 72h - Algae [1]	W 1000 mg/l (OECD 201 method)	
ErC50 algae	1000 mg/l (Pseudokirhneriella subcapitata, EL0, 72h)	

6-1-2023 (Revision date) 6-1-2023 (Printing date) EN (English) 8/14

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.2. Persistence and degradability

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics (1174522-09-8)		
Persistence and degradability Readily biodegradable.		
Biodegradation	80 % (28d)	

12.3. Bioaccumulative potential

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics (1174522-09-8)	
Partition coefficient n-octanol/water (Log Pow)	5,57 - 6,62

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods **HP Code**

- : Dispose of contents/container in accordance with licensed collector's sorting instructions.
- HP3 "Flammable:"
- flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C;
- flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air;
- flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction;
- flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa;
- water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities;
- other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 1950	UN 1950 UN 1950 UN 1950		UN 1950	
14.2. UN proper shipping name				
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS

6-1-2023 (Revision date) EN (English) 9/14

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
Transport document descr	iption			
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1	UN 1950 AEROSOLS, 2.1	UN 1950 AEROSOLS, 2.1
14.3. Transport hazard	class(es)		'	
2.1	2.1	2.1	2.1	2.1
2	2	2	2	2
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental haz	ards			
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information	n available		1	1

14.6. Special precautions for user

Overland transport

Classification code (ADR) : 5F

Special provisions (ADR) : 190, 327, 344, 625

Limited quantities (ADR) : 11

Excepted quantities (ADR) : E0

Packing instructions (ADR) : P207

Special packing provisions (ADR) : PP87, RR6, L2

Mixed packing provisions (ADR) : MP9

Transport category (ADR) : 2

Special provisions for carriage - Packages (ADR) : V14

Special provisions for carriage - Loading, unloading : CV9, CV12

and handling (ADR)

Special provisions for carriage - Operation (ADR) : S2
Tunnel restriction code (ADR) : D

Transport by sea

Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959

Limited quantities (IMDG) : SP277

Excepted quantities (IMDG) : E0

Packing instructions (IMDG) : P207, LP200

Special packing provisions (IMDG) : PP87, L2

EmS-No. (Fire) : F-D

EmS-No. (Spillage) : S-U

Stowage category (IMDG) : None

Stowage and handling (IMDG) : SW1, SW22 Segregation (IMDG) : SG69

Air transport

PCA Excepted quantities (IATA) : E0
PCA Limited quantities (IATA) : Y203
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 203
PCA max net quantity (IATA) : 75kg
CAO packing instructions (IATA) : 203
CAO max net quantity (IATA) : 150kg

6-1-2023 (Revision date) EN (English) 10/14

6-1-2023 (Revision date 6-1-2023 (Printing date)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Special provisions (IATA) : A145, A167, A802

ERG code (IATA) : 10L

Inland waterway transport

Classification code (ADN) : 5F

Special provisions (ADN) : 190, 327, 344, 625

Limited quantities (ADN) : 1 L Excepted quantities (ADN) : E0 : PP, EX, A Equipment required (ADN) : VE01, VE04 Ventilation (ADN)

Number of blue cones/lights (ADN) . 1

Rail transport

Classification code (RID) : 5F

Special provisions (RID) : 190, 327, 344, 625

Limited quantities (RID) : 1L Excepted quantities (RID) : E0

Packing instructions (RID) : P207, LP200 Special packing provisions (RID) : PP87, RR6, L2

: MP9 Mixed packing provisions (RID) Transport category (RID) : 2 : W14 Special provisions for carriage – Packages (RID) Special provisions for carriage - Loading, unloading : CW9, CW12

and handling (RID)

Colis express (express parcels) (RID) : CE2 Hazard identification number (RID)

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

VOC Directive (2004/42)

VOC content : 487,2 g/l

Biocide Regulation (528/2012)

Child-resistant fastening : Not applicable Tactile warning : Not applicable

6-1-2023 (Revision date) EN (English) 11/14

6-1-2023 (Printing date)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Seveso Directive (Disaster Risk Reduction)

Seveso III Part I (Categories of dangerous substances)	Qualifying quantity (tonnes)	
	Lower-tier	Upper-tier
P3a FLAMMABLE AEROSOLS 'Flammable' aerosols Category 1 or 2, containing flammable gases Category 1 or 2 or flammable liquids Category 1	150	500

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes			
Section	Changed item	Change	Comments
	Limited quantities (IMDG)	Added	
	Excepted quantities (IMDG)	Added	
	SDS EU format	Added	
	Type of product	Added	
1.2	Use of the substance/mixture	Added	
1.2	Function or use category	Added	
4.1	First-aid measures general	Modified	
4.1	First-aid measures after ingestion	Modified	
4.2	Symptoms/effects after ingestion	Modified	
5.2	Hazardous decomposition products in case of fire	Modified	
5.2	Fire hazard	Modified	
9.1	Upper explosive limit (UEL)	Modified	
9.1	Solubility in water	Modified	
10.3	Possibility of hazardous reactions	Modified	
15.1	REACH Annex XVII	Modified	
16	Abbreviations and acronyms	Modified	

Abbreviations and acronyms:		
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways	
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road	
ATE	Acute Toxicity Estimate	

6-1-2023 (Revision date) EN (English) 12/14

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:		
BCF	Bioconcentration factor	
BLV	Biological limit value	
BOD	Biochemical oxygen demand (BOD)	
COD	Chemical oxygen demand (COD)	
DMEL	Derived Minimal Effect level	
DNEL	Derived-No Effect Level	
EC-No.	European Community number	
EC50	Median effective concentration	
EN	European Standard	
IARC	International Agency for Research on Cancer	
IATA	International Air Transport Association	
IMDG	International Maritime Dangerous Goods	
LC50	Median lethal concentration	
LD50	Median lethal dose	
LOAEL	Lowest Observed Adverse Effect Level	
NOAEC	No-Observed Adverse Effect Concentration	
NOAEL	No-Observed Adverse Effect Level	
NOEC	No-Observed Effect Concentration	
OECD	Organisation for Economic Co-operation and Development	
OEL	Occupational Exposure Limit	
PBT	Persistent Bioaccumulative Toxic	
PNEC	Predicted No-Effect Concentration	
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail	
SDS	Safety Data Sheet	
STP	Sewage treatment plant	
ThOD	Theoretical oxygen demand (ThOD)	
TLM	Median Tolerance Limit	
VOC	Volatile Organic Compounds	
CAS-No.	Chemical Abstract Service number	
N.O.S.	Not Otherwise Specified	
vPvB	Very Persistent and Very Bioaccumulative	
ED	Endocrine disrupting properties	

Full text of H- and EUH-statements:	
Asp. Tox. 1	Aspiration hazard, Category 1
EUH066	Repeated exposure may cause skin dryness or cracking.
Flam. Gas 1A	Flammable gases, Category 1A
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.

6-1-2023 (Revision date) 6-1-2023 (Printing date)

EN (English)

13/14

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
Press. Gas (Comp.)	Gases under pressure : Compressed gas

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.